

NAG Library Routine Document

C05ZAF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

C05ZAF checks the user-supplied gradients of a set of nonlinear functions in several variables, for consistency with the functions themselves. The routine must be called twice.

2 Specification

```
SUBROUTINE C05ZAF(M, N, X, FVEC, FJAC, LDFJAC, XP, FVECP, MODE, ERR)
INTEGER          M, N, LDFJAC, MODE
double precision X(N), FVEC(M), FJAC(LDFJAC,N), XP(*), FVECP(M), ERR(*)
```

3 Description

C05ZAF is based on the MINPACK routine CHKDER (see Moré *et al.* (1980)). It checks the i th gradient for consistency with the i th function by computing a forward-difference approximation along a suitably chosen direction and comparing this approximation with the user-supplied gradient along the same direction. The principal characteristic of C05ZAF is its invariance under changes in scale of the variables or functions.

4 References

Moré J J, Garbow B S and Hillstom K E (1980) User guide for MINPACK-1 *Technical Report ANL-80-74* Argonne National Laboratory

5 Parameters

- 1: M – INTEGER *Input*
On entry: the number of functions.
- 2: N – INTEGER *Input*
On entry: the number of variables. For use with C05PBF/C05PBA and C05PCF/C05PCA, $M = N$.
- 3: X(N) – ***double precision*** array *Input*
On entry: the components of a point x , at which the consistency check is to be made. (See Section 8.)
- 4: FVEC(M) – ***double precision*** array *Input*
On entry: when $MODE = 2$, FVEC must contain the functions evaluated at x .
- 5: FJAC(LDFJAC,N) – ***double precision*** array *Input*
On entry: when $MODE = 2$, FJAC must contain the user-supplied gradients. (The i th row of FJAC must contain the gradient of the i th function evaluated at the point x .)

- 6: LDFJAC – INTEGER *Input*
On entry: the first dimension of the array FJAC as declared in the (sub)program from which C05ZAF is called.
Constraint: $LDFJAC \geq M$.
- 7: XP(*) – **double precision** array *Output*
Note: the dimension of the array XP must be at least N if $MODE = 1$, and at least 1 otherwise.
On exit: when $MODE = 1$, XP is set to a neighbouring point to X.
- 8: FVECP(M) – **double precision** array *Input*
On entry: when $MODE = 2$, FVECP must contain the functions evaluated at XP.
- 9: MODE – INTEGER *Input*
On entry: the value 1 on the first call and the value 2 on the second call of C05ZAF.
- 10: ERR(*) – **double precision** array *Output*
Note: the dimension of the array ERR must be at least M if $MODE = 2$, and at least 1 otherwise.
On exit: when $MODE = 2$, ERR contains measures of correctness of the respective gradients. If there is no loss of significance (see Section 8), then if $ERR(i)$ is 1.0 the i th user-supplied gradient is correct, whilst if $ERR(i)$ is 0.0 the i th gradient is incorrect. For values of $ERR(i)$ between 0.0 and 1.0 the categorisation is less certain. In general, a value of $ERR(i) > 0.5$ indicates that the i th gradient is probably correct.

6 Error Indicators and Warnings

None.

7 Accuracy

See Section 8.

8 Further Comments

The time required by C05ZAF increases with M and N.

C05ZAF does not perform reliably if cancellation or rounding errors cause a severe loss of significance in the evaluation of a function. Therefore, none of the components of x should be unusually small (in particular, zero) or any other value which may cause loss of significance. The relative differences between corresponding elements of FVECP and FVEC should be at least two orders of magnitude greater than the *machine precision*.

9 Example

This example checks the Jacobian matrix for a problem with 15 functions of three variables. The results indicate that the first seven gradients are probably incorrect (this is caused by a deliberate error in the code to calculate the Jacobian).

9.1 Program Text

```
* C05ZAF Example Program Text
* Mark 14 Revised. NAG Copyright 1989.
* .. Parameters ..
INTEGER      M, N, LDFJAC
PARAMETER    (M=15,N=3,LDFJAC=M)
INTEGER      NOUT
PARAMETER    (NOUT=6)
```

```

*      .. Local Scalars ..
      INTEGER          I, MODE
*      .. Local Arrays ..
      DOUBLE PRECISION ERR(M), FJAC(LDFJAC,N), FVEC(M), FVECP(M), X(N),
+      XP(N)
*      .. External Functions ..
      LOGICAL          A00ACF
      EXTERNAL          A00ACF
*      .. External Subroutines ..
      EXTERNAL          C05ZAF, FCN
*      .. Executable Statements ..
      WRITE (NOUT,*) 'C05ZAF Example Program Results'
*
      IF (A00ACF()) THEN
*
*         X(1) = 9.2D-1
*         X(2) = 1.3D-1
*         X(3) = 5.4D-1
*         MODE = 1
*
*         CALL C05ZAF(M,N,X,FVEC,FJAC,LDFJAC,XP,FVECP,MODE,ERR)
*
*         CALL FCN(M,N,X,FVEC,FJAC,LDFJAC,1)
*         CALL FCN(M,N,X,FVEC,FJAC,LDFJAC,2)
*         CALL FCN(M,N,XP,FVECP,FJAC,LDFJAC,1)
*
*         WRITE (NOUT,*)
*         WRITE (NOUT,99999) '      FVEC at X = ', (X(I),I=1,N)
*         WRITE (NOUT,*)
*         WRITE (NOUT,99998) (FVEC(I),I=1,M)
*         WRITE (NOUT,*)
*         WRITE (NOUT,99999) '      FVECP at XP = ', (XP(I),I=1,N)
*         WRITE (NOUT,*)
*         WRITE (NOUT,99998) (FVECP(I),I=1,M)
*
*         MODE = 2
*
*         CALL C05ZAF(M,N,X,FVEC,FJAC,LDFJAC,XP,FVECP,MODE,ERR)
*
*         WRITE (NOUT,*)
*         WRITE (NOUT,*) '      ERR'
*         WRITE (NOUT,*)
*         WRITE (NOUT,99998) (ERR(I),I=1,M)
*
      ELSE
*         WRITE (NOUT,*)
*         WRITE (NOUT,*) ' ** No valid licence key was found'
      END IF
*
99999 FORMAT (1X,A,3F12.7)
99998 FORMAT (5X,3F12.4)
      END
*
      SUBROUTINE FCN(M,N,X,FVEC,FJAC,LDFJAC,IFLAG)
*      .. Parameters ..
      INTEGER          M1
      PARAMETER        (M1=15)
*      .. Scalar Arguments ..
      INTEGER          IFLAG, LDFJAC, M, N
*      .. Array Arguments ..
      DOUBLE PRECISION FJAC(LDFJAC,N), FVEC(M), X(N)
*      .. Local Scalars ..
      DOUBLE PRECISION TMP1, TMP2, TMP3, TMP4
      INTEGER          I
*      .. Local Arrays ..
      DOUBLE PRECISION Y(M1)
*      .. Data statements ..
      DATA
+      Y/1.4D-1, 1.8D-1, 2.2D-1, 2.5D-1, 2.9D-1, 3.2D-1,
+      3.5D-1, 3.9D-1, 3.7D-1, 5.8D-1, 7.3D-1, 9.6D-1,
+      1.34D0, 2.1D0, 4.39D0/
*      .. Executable Statements ..

```

```

      IF (IFLAG.NE.2) THEN
        DO 20 I = 1, M
          TMP1 = I
          TMP2 = M + 1 - I
          TMP3 = TMP1
          IF (I.GT.(M+1)/2) TMP3 = TMP2
          FVEC(I) = Y(I) - (X(1)+TMP1/(X(2)*TMP2+X(3)*TMP3))
20      CONTINUE
      ELSE
        DO 40 I = 1, M
          TMP1 = I
          TMP2 = M + 1 - I
*
*      Error introduced into next statement for illustration.
*      Corrected statement should read      TMP3 = TMP1 .
*
          TMP3 = TMP2
          IF (I.GT.(M+1)/2) TMP3 = TMP2
          TMP4 = (X(2)*TMP2+X(3)*TMP3)**2
          FJAC(I,1) = -1.0D0
          FJAC(I,2) = TMP1*TMP2/TMP4
          FJAC(I,3) = TMP1*TMP3/TMP4
40      CONTINUE
      END IF
      RETURN
      END

```

9.2 Program Data

None.

9.3 Program Results

C05ZAF Example Program Results

FVEC at X =	0.9200000	0.1300000	0.5400000
-1.1816	-1.4297	-1.6063	
-1.7453	-1.8407	-1.9216	
-1.9841	-2.0225	-2.4690	
-2.8276	-3.4736	-4.4376	
-6.0477	-9.2678	-18.9181	
FVECP at XP =	0.9200000	0.1300000	0.5400000
-1.1816	-1.4297	-1.6063	
-1.7453	-1.8407	-1.9216	
-1.9841	-2.0225	-2.4690	
-2.8276	-3.4736	-4.4376	
-6.0477	-9.2678	-18.9181	
ERR			
0.1120	0.0976	0.0949	
0.0979	0.1053	0.1197	
0.1498	1.0000	0.9950	
0.9718	1.0000	0.9686	
1.0000	0.9802	1.0000	
