

NAG Library Routine Document

E04NYF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

E04NYF is used to get the value of a ***double precision*** optional parameter. E04NYF can be used before or after calling E04NQF.

2 Specification

```
SUBROUTINE E04NYF (STRING, RVALUE, CW, IW, RW, IFAIL)
```

```
INTEGER                IW(*), IFAIL
double precision      RVALUE, RW(*)
CHARACTER*(*)          STRING
CHARACTER*8            CW(*)
```

3 Description

E04NYF obtains the current value of a ***double precision*** option. For example

```
CALL E04NYF ('Feasibility Tolerance', FEATOL, CW, IW, RW, IFAIL)
```

will result in the value of the optional parameter Feasibility Tolerance being output in FEATOL.

A complete list of optional parameters, their abbreviations, synonyms and default values is given in Section 11 in E04NQF.

4 References

None.

5 Parameters

- 1: STRING – CHARACTER*(*) *Input*
On entry: a single valid keyword of a ***double precision*** optional parameter (as described in Section 11 in E04NQF).
- 2: RVALUE – ***double precision*** *Output*
On exit: the ***double precision*** value associated with the keyword in STRING.
- 3: CW(*) – CHARACTER*8 array *Communication Array*
Note: the dimension of the array CW must be at least LENCW (see E04NPF).
- 4: IW(*) – INTEGER array *Communication Array*
Note: the dimension of the array IW must be at least LENIW (see E04NPF).
- 5: RW(*) – ***double precision*** array *Communication Array*
Note: the dimension of the array RW must be at least LENRW (see E04NPF).

6: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

The initialization routine E04NPF has not been called.

IFAIL = 2

The supplied option is invalid. Check that the keywords are neither ambiguous nor misspelt.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

See Section 9 in E04NRF.
