

# NAG Library Routine Document

## E04VHF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

**Note:** *this routine uses optional parameters to define choices in the problem specification and in the details of the algorithm. If you wish to use default settings for all of the optional parameters, you need only read Sections 1 to 9 of this document. If, however, you wish to reset some or all of the settings please refer to Section 10 for a detailed description of the algorithm, to Section 11 for a detailed description of the specification of the optional parameters and to Section 12 for a detailed description of the monitoring information produced by the routine.*

### 1 Purpose

E04VHF solves sparse nonlinear programming problems.

### 2 Specification

```

SUBROUTINE E04VHF(START, NF, N, NXNAME, NFNAME, OBJADD, OBJROW, PROB,
1          USRFUN, IAFUN, JAVAR, A, LENA, NEA, IGFUN, JGVAR,
2          LENG, NEG, XLOW, XUPP, XNAMES, FLOW, FUPP, FNAMES, X,
3          XSTATE, XMUL, F, FSTATE, FMUL, NS, NINF, SINP, CW,
4          LENCW, IW, LENIW, RW, LENRW, CUSER, IUSER, RUSER,
5          IFAIL)

    INTEGER          START, NF, N, NXNAME, NFNAME, OBJROW, IAFUN(LENA),
1          JAVAR(LENA), LENA, NEA, IGFUN(LENG), JGVAR(LENG),
2          LENG, NEG, XSTATE(N), FSTATE(NF), NS, NINF, LENCW,
3          IW(LENIW), LENIW, LENRW, IUSER(*), IFAIL

    double precision    OBJADD, A(LENA), XLOW(N), XUPP(N), FLOW(NF), FUPP(NF),
1          X(N), XMUL(N), F(NF), FMUL(NF), SINP, RW(LENRW),
2          RUSER(*)

    CHARACTER*8      PROB, XNAMES(NXNAME), FNAMES(NFNAME), CW(LENCW),
1          CUSER(*)

    EXTERNAL          USRFUN

```

Before calling E04VHF, or one of the option setting routines E04VKF, E04VLF, E04VMF or E04VNF, routine E04VGF **must** be called. The specification for E04VGF is:

```

SUBROUTINE E04VGF(PRINT_REC, CW, LENCW, IW, LENIW, RW, LENRW, IFAIL)

    INTEGER          LENCW, IW(LENIW), LENIW, LENRW, IFAIL

    double precision    RW(LENRW)

    CHARACTER*8      CW(LENCW)

    EXTERNAL          PRINT_REC

```

E04VGF should be called with LENCW, LENIW and LENRW, the declared lengths of CW, IW and RW respectively, must satisfy:

$$\text{LENCW} \geq 600$$

$$\text{LENIW} \geq 600$$

$$\text{LENRW} \geq 600$$

The contents of the arrays CW, IW and RW **must not** be altered between calling routines E04VGF, E04VHF, E04VJF, E04VKF, E04VLF, E04VMF and E04VNF.

### 3 Description

E04VHF is designed to minimize a linear or nonlinear function subject to bounds on the variables and sparse linear or nonlinear constraints. It is suitable for large-scale linear and quadratic programming and for linearly constrained optimization, as well as for general nonlinear programs of the form

$$\underset{x}{\text{minimize}} f_0(x) \quad \text{subject to } l \leq \begin{pmatrix} x \\ f(x) \\ A_L x \end{pmatrix} \leq u, \quad (1)$$

where  $x$  is an  $n$ -vector of variables,  $l$  and  $u$  are constant lower and upper bounds,  $f_0(x)$  is a smooth scalar objective function,  $A_L$  is a sparse matrix, and  $f(x)$  is a vector of smooth nonlinear constraint functions  $\{f_i(x)\}$ . The optional parameter `Maximize` specifies that  $f_0(x)$  should be maximized instead of minimized.

Ideally, the first derivatives (gradients) of  $f_0(x)$  and  $f_i(x)$  should be known and coded by you. If only some of the gradients are known, E04VHF estimates the missing ones by finite differences.

If  $f_0(x)$  is linear and  $f(x)$  is absent, (1) is a linear program (LP) and E04VHF applies the primal simplex method (see Dantzig (1963)). Sparse basis factors are maintained by LUSOL (see Gill *et al.* (1987)) as in MINOS (see Murtagh and Saunders (1995)).

If only the objective is nonlinear, the problem is linearly constrained (LC) and tends to solve more easily than the general case with nonlinear constraints (NC). For both nonlinear cases, E04VHF applies a sparse sequential quadratic programming (SQP) method (see Gill *et al.* (2002)), using limited-memory quasi-Newton approximations to the Hessian of the Lagrangian. The merit function for step-length control is an augmented Lagrangian, as in the dense SQP solver E04WDF (see Gill *et al.* (1986) and Gill *et al.* (1992)).

E04VHF is suitable for nonlinear problems with thousands of constraints and variables, and is most efficient if only some of the variables enter nonlinearly, or there are relatively few degrees of freedom at a solution (i.e., many constraints are active). However, there is no limit on the number of degrees of freedom.

E04VHF allows linear and nonlinear constraints and variables to be entered in an *arbitrary order*, and uses one subroutine to define all the nonlinear functions.

The optimization problem is assumed to be in the form

$$\underset{x}{\text{minimize}} F_{\text{obj}}(x) \quad \text{subject to } l_x \leq x \leq u_x, \quad l_F \leq F(x) \leq u_F, \quad (2)$$

where the upper and lower bounds are constant,  $F(x)$  is a vector of smooth linear and nonlinear constraint functions  $\{F_i(x)\}$ , and  $F_{\text{obj}}(x)$  is one of the components of  $F$  to be minimized, as specified by the input parameter `OBJROW`. E04VHF reorders the variables and constraints so that the problem is in the form (1).

Upper and lower bounds are specified for all variables and functions. The  $j$ th constraint may be defined as an equality by setting  $l_j = u_j$ . If certain bounds are not present, the associated elements of  $l$  or  $u$  should be set to special values that are treated as  $-\infty$  or  $+\infty$ . Free variables and free constraints ('free rows') have both bounds infinite.

In general, the components of  $F$  are *structured* in the sense that they are formed from sums of linear and nonlinear functions of just some of the variables. This structure can be exploited by E04VHF.

In many cases, the vector  $F(x)$  is a sum of linear and nonlinear functions. E04VHF allows these terms to be specified separately, so that the linear part is defined just once by the input arguments `IAFUN`, `JAVAR` and `A`. Only the nonlinear part is recomputed at each  $x$ .

Suppose that each component of  $F(x)$  is of the form

$$F_i(x) = f_i(x) + \sum_{j=1}^n A_{ij}x_j,$$

where  $f_i(x)$  is a nonlinear function (possibly zero) and the elements  $A_{ij}$  are constant. The  $n \times f$  by  $n$  Jacobian of  $F(x)$  is the sum of two sparse matrices of the same size:  $F'(x) = G(x) + A$ , where  $G(x) = f'(x)$  and  $A$  is the matrix with elements  $\{A_{ij}\}$ . The two matrices must be *non-overlapping* in the sense that each element of the Jacobian  $F'(x) = G(x) + A$  comes from  $G(x)$  or  $A$ , but *not both*. The element cannot be split between  $G(x)$  and  $A$ .

For example, the function

$$F(x) = \begin{pmatrix} 3x_1 + e^{x_2}x_4 + x_2^2 + 4x_4 - x_3 + x_5 \\ x_2 + x_3^2 + \sin x_4 - 3x_5 \\ x_1 - x_3 \end{pmatrix}$$

can be written as

$$F(x) = f(x) + Ax = \begin{pmatrix} e^{x_2}x_4 + x_2^2 + 4x_4 \\ x_3^2 + \sin x_4 \\ 0 \end{pmatrix} + \begin{pmatrix} 3x_1 - x_3 + x_5 \\ x_2 - 3x_5 \\ x_1 - x_3 \end{pmatrix},$$

in which case

$$F'(x) = \begin{pmatrix} 3 & e^{x_2}x_4 + 2x_2 & -1 & e^{x_2} + 4 & 1 \\ 0 & 1 & 2x_3 & \cos x_4 & -3 \\ 1 & 0 & -1 & 0 & 0 \end{pmatrix}$$

can be written as  $F'(x) = f'(x) + A = G(x) + A$ , where

$$G(x) = \begin{pmatrix} 0 & e^{x_2}x_4 + 2x_2 & 0 & e^{x_2} + 4 & 0 \\ 0 & 0 & 2x_3 & \cos x_4 & 0 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}, \quad A = \begin{pmatrix} 3 & 0 & -1 & 0 & 1 \\ 0 & 1 & 0 & 0 & -3 \\ 1 & 0 & -1 & 0 & 0 \end{pmatrix}.$$

**Note:** the element  $e^{x_2} + 4$  of  $F'(x)$  appears in  $G(x)$  and is not split between  $G(x)$  and  $A$  although it contains a linear term.

The nonzero elements of  $A$  and  $G$  are provided to E04VHF in co-ordinate form. The elements of  $A$  are entered as triples  $(i, j, A_{ij})$  in the arrays IAFUN, JAVAR and A. The sparsity pattern  $G$  is entered as pairs  $(i, j)$  in the arrays IGFUN and JGVAR. The corresponding entries  $G_{ij}$  (any that are known) are assigned to appropriate array elements  $G(k)$  in USRFUN.

The elements of  $A$  and  $G$  may be stored in any order. Duplicate entries are ignored. IGFUN and JGVAR may be defined automatically by subroutine E04VJF when Derivative Option = 0 is specified and USRFUN does not provide any gradients.

Throughout this document the symbol  $\epsilon$  is used to represent the *machine precision* (see X02AJF).

E04VHF is based on SNOPTA, which is part of the SNOPT package described in Gill *et al.* (2005b).

## 4 References

Dantzig G B (1963) *Linear Programming and Extensions* Princeton University Press

Eldersveld S K (1991) Large-scale sequential quadratic programming algorithms *PhD Thesis* Department of Operations Research, Stanford University, Stanford

Fourer R (1982) Solving staircase linear programs by the simplex method *Math. Programming* **23** 274–313

Gill P E, Murray W and Saunders M A (2002) *SNOPT: An SQP Algorithm for Large-scale Constrained Optimization* **12** 979–1006 SIAM J. Optim.

Gill P E, Murray W and Saunders M A (2005a) Users' guide for SQOPT 7: a Fortran package for large-scale linear and quadratic programming *Report NA 05-1* Department of Mathematics, University of California, San Diego <http://www.cam.ucsd.edu/pub/peg/reports/sqdoc7.pdf>

Gill P E, Murray W and Saunders M A (2005b) Users' guide for SNOPT 7.1: a Fortran package for large-scale linear nonlinear programming *Report NA 05-2* Department of Mathematics, University of California, San Diego <http://www.cam.ucsd.edu/pub/peg/reports/sndoc7.pdf>

Gill P E, Murray W, Saunders M A and Wright M H (1986) Users' guide for NPSOL (Version 4.0): a Fortran package for nonlinear programming *Report SOL 86-2* Department of Operations Research, Stanford University

Gill P E, Murray W, Saunders M A and Wright M H (1987) Maintaining  $LU$  factors of a general sparse matrix *Linear Algebra and its Applics.* **88/89** 239–270

Gill P E, Murray W, Saunders M A and Wright M H (1992) Some theoretical properties of an augmented Lagrangian merit function *Advances in Optimization and Parallel Computing* (ed P M Pardalos) 101–128 North Holland

Hock W and Schittkowski K (1981) *Test Examples for Nonlinear Programming Codes. Lecture Notes in Economics and Mathematical Systems* **187** Springer-Verlag

Murtagh B A and Saunders M A (1978) Large-scale linearly constrained optimization *14* 41–72 Math. Program.

Murtagh B A and Saunders M A (1982) A projected Lagrangian algorithm and its implementation for sparse nonlinear constraints *Math. Program. Stud.* **16** 84–118

Murtagh B A and Saunders M A (1995) MINOS 5.4 Users' Guide *Report SOL 83-20R* Department of Operations Research, Stanford University

## 5 Parameters

1: START – INTEGER *Input*

*On entry:* indicates how a starting point is to be obtained.

START = 0

Requests that the Crash procedure be used, unless a Basis file is provided via optional parameters Old Basis File, Insert File or Load File.

START = 1

Is the same as START = 0 but is more meaningful when a Basis file is given.

START = 2

Means that XSTATE and FSTATE define a valid starting point (probably from an earlier call, though not necessarily).

*Constraint:* START = 0, 1 or 2.

2: NF – INTEGER *Input*

*On entry:*  $nf$ , the number of problem functions in  $F(x)$ , including the objective function (if any) and the linear and nonlinear constraints. Upper and lower bounds on  $x$  can be defined using the parameters XLOW and XUPP and should not be included in  $F$ .

*Constraint:* NF > 0.

3: N – INTEGER *Input*

*On entry:*  $n$ , the number of variables.

*Constraint:* N > 0.

4: NXNAME – INTEGER *Input*

*On entry:* the number of names provided in the array XNAMES.

NXNAME = 1

There are no names provided and generic names will be used in the output.

NXNAME = N

Names for all variables must be provided and will be used in the output.

*Constraint:* NXNAME = 1 or N.

5: NFNAME – INTEGER *Input*

*On entry:* the number of names provided in the array FNAMES.

NFNAME = 1

There are no names provided and generic names will be used in the output.

NFNAME = NF

Names for all functions must be provided and will be used in the output.

*Constraint:* NFNAME = 1 or NF.

**Note:** If NXNAME = 1 then NFNAME must also be 1 (and vice versa). Similarly, if NXNAME = N then NFNAME must be NF (and vice versa).

6: OBJADD – *double precision* *Input*

*On entry:* is a constant that will be added to the objective row  $F_{\text{obj}}$  for printing purposes. Typically, OBJADD = 0.0D+0.

7: OBJROW – INTEGER *Input*

*On entry:* says which row of  $F(x)$  is to act as the objective function. If there is no such row, set OBJROW = 0. Then E04VHF will seek a feasible point such that  $l_F \leq F(x) \leq u_F$  and  $l_x \leq x \leq u_x$ .

*Constraint:*  $1 \leq \text{OBJROW} \leq \text{NF}$  or OBJROW = 0 (or a feasible point problem).

8: PROB – CHARACTER\*8 *Input*

*On entry:* is an 8-character name for the problem. PROB is used in the printed solution and in some routines that output Basis files. A blank name may be used.

9: USRFUN – SUBROUTINE, supplied by the user. *External Procedure*

USRFUN must define the nonlinear portion  $f(x)$  of the problem functions  $F(x) = f(x) + Ax$ , along with its gradient elements  $G_{ij}(x) = \frac{\partial f_i(x)}{\partial x_j}$ . (A dummy subroutine is needed even if  $f \equiv 0$  and all functions are linear.)

In general, USRFUN should return all function and gradient values on every entry except perhaps the last. This provides maximum reliability and corresponds to the default option setting, Derivative Option = 1.

The elements of  $G(x)$  are stored in the array G(1 : LENG) in the order specified by the input arrays IGFUN and JGVAR.

In practice it is often convenient *not* to code gradients. E04VHF is able to estimate them by finite differences, using a call to USRFUN for each variable  $x_j$  for which some  $\frac{\partial f_i(x)}{\partial x_j}$  needs to be estimated. However, this reduces the reliability of the optimization algorithm, and it can be very expensive if there are many such variables  $x_j$ .

As a compromise, E04VHF allows you to code *as many gradients as you like*. This option is implemented as follows. Just before USRFUN is called, each element of the derivative array G is initialized to a specific value. On exit, any element retaining that value must be estimated by finite differences.

Some rules of thumb follow:

- (i) for maximum reliability, compute all gradients;
- (ii) if the gradients are expensive to compute, specify optional parameter Nonderivative Linesearch and use the value of the input parameter NEEDG to avoid computing them on certain entries. (There is no need to compute gradients if NEEDG = 0 on entry to USRFUN.);
- (iii) if not all gradients are known, you must specify Derivative Option = 0. You should still compute as many gradients as you can. (It often happens that some of them are constant or zero.);
- (iv) again, if the known gradients are expensive, don't compute them if NEEDG = 0 on entry to USRFUN;

- (v) use the input parameter STATUS to test for special actions on the first or last entries;
- (vi) while USRFUN is being developed, use the optional parameter Verify Level to check the computation of gradients that are supposedly known;
- (vii) USRFUN is not called until the linear constraints and bounds on  $x$  are satisfied. This helps confine  $x$  to regions where the functions  $f_i(x)$  are likely to be defined. However, be aware of the optional parameter Minor Feasibility Tolerance if the functions have singularities on the constraint boundaries;
- (viii) set STATUS = -1 if some of the functions are undefined. The linesearch will shorten the step and try again;
- (ix) set STATUS  $\leq -2$  if you want E04VHF to stop.

The specification of USRFUN is:

```

SUBROUTINE USRFUN(STATUS, N, X, NEEDF, NF, F, NEEDG, LENG, G, CUSER,
1 IUSER, RUSER)
      INTEGER          STATUS, N, NEEDF, NF, NEEDG, LENG, IUSER(*)
      double precision X(N), F(NF), G(LENG), RUSER(*)
      CHARACTER*8      CUSER(*)

```

1: STATUS – INTEGER *Input/Output*

*On entry:* indicates the first and last calls to USRFUN.

STATUS = 0

There is nothing special about the current call to USRFUN.

STATUS = 1

E04VHF is calling your subroutine for the *first* time. You may wish to do something special such as read data from a file.

STATUS  $\geq 2$

E04VHF is calling your subroutine for the *last* time. This parameter setting allows you to perform some additional computation on the final solution.

STATUS = 2

The current X is *optimal*.

STATUS = 3

The problem appears to be infeasible.

STATUS = 4

The problem appears to be unbounded.

STATUS = 5

An iterations limit was reached.

If the functions are expensive to evaluate, it may be desirable to do nothing on the last call. The first executable statement could be

```
IF (STATUS .GE. 2) RETURN.
```

*On exit:* may be used to indicate that you are unable to evaluate  $f$  or its gradients at the current  $x$ . (For example, the problem functions may not be defined there.)

During the linesearch,  $f(x)$  is evaluated at points  $x = x_k + \alpha p_k$  for various step lengths  $\alpha$ , where  $f(x_k)$  has already been evaluated satisfactorily. For any such  $x$ , if you set STATUS = -1, E04VHF will reduce  $\alpha$  and evaluate  $f$  again (closer to  $x_k$ , where  $f(x_k)$  is more likely to be defined).

If for some reason you wish to terminate the current problem, set STATUS  $\leq -2$ .

|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |              |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| 2: | N – INTEGER                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Input        |
|    | <i>On entry:</i> $n$ , the number of variables, as defined in the call to E04VHF.                                                                                                                                                                                                                                                                                                                                                                            |              |
| 3: | X(N) – <b>double precision</b> array                                                                                                                                                                                                                                                                                                                                                                                                                         | Input        |
|    | <i>On entry:</i> the variables $x$ at which the problem functions are to be calculated. The array $x$ must not be altered.                                                                                                                                                                                                                                                                                                                                   |              |
| 4: | NEEDF – INTEGER                                                                                                                                                                                                                                                                                                                                                                                                                                              | Input        |
| 5: | NF – INTEGER                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Input        |
| 6: | F(NF) – <b>double precision</b> array                                                                                                                                                                                                                                                                                                                                                                                                                        | Input/Output |
|    | <i>On entry:</i> concerns the calculation of $f(x)$ .                                                                                                                                                                                                                                                                                                                                                                                                        |              |
|    | NF is the length of the full vector $F(x) = f(x) + Ax$ as defined in the call to E04VHF.                                                                                                                                                                                                                                                                                                                                                                     |              |
|    | NEEDF indicates if F must be assigned during this call of USRFUN.                                                                                                                                                                                                                                                                                                                                                                                            |              |
|    | NEEDF = 0                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |
|    | F is not required and is ignored.                                                                                                                                                                                                                                                                                                                                                                                                                            |              |
|    | NEEDF > 0                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |
|    | The components of $f(x)$ corresponding to the nonlinear part of $F(x)$ must be calculated and assigned to F.                                                                                                                                                                                                                                                                                                                                                 |              |
|    | If $F_i(x)$ is linear and completely defined by the $i$ th row of $A$ , $A'_i$ , then the associated value $f_i(x)$ is ignored and need not be assigned. However, if $F_i(x)$ has a nonlinear portion $f_i(x)$ that happens to be zero at $x$ , then it is still necessary to set $f_i(x) = 0$ . If the linear part $A'_i$ of a nonlinear $F_i(x)$ is provided using the arrays IAFUN, JAVAR and A, then it must not be computed again as part of $f_i(x)$ . |              |
|    | To simplify the code, you may ignore the value of NEEDF and compute $f(x)$ on every entry to USRFUN.                                                                                                                                                                                                                                                                                                                                                         |              |
|    | NEEDF may also be ignored with Derivative Linesearch and Derivative Option = 1. In this case, NEEDF is always 1, and F must always be assigned.                                                                                                                                                                                                                                                                                                              |              |
|    | <i>On exit:</i> F contains the computed functions $f(x)$ (except perhaps if NEEDF = 0).                                                                                                                                                                                                                                                                                                                                                                      |              |
| 7: | NEEDG – INTEGER                                                                                                                                                                                                                                                                                                                                                                                                                                              | Input        |
| 8: | LENG – INTEGER                                                                                                                                                                                                                                                                                                                                                                                                                                               | Input        |
| 9: | G(LENG) – <b>double precision</b> array                                                                                                                                                                                                                                                                                                                                                                                                                      | Input/Output |
|    | <i>On entry:</i> concerns the calculations of the derivatives of the function $f(x)$ .                                                                                                                                                                                                                                                                                                                                                                       |              |
|    | LENG is the length of the co-ordinate arrays JGVAR and IGFUN in the call to E04VHF.                                                                                                                                                                                                                                                                                                                                                                          |              |
|    | NEEDG indicates if G must be assigned during this call of USRFUN.                                                                                                                                                                                                                                                                                                                                                                                            |              |
|    | NEEDG = 0                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |
|    | G is not required and is ignored.                                                                                                                                                                                                                                                                                                                                                                                                                            |              |
|    | NEEDG > 0                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |
|    | The partial derivatives of $f(x)$ must be calculated and assigned to G. For each $k = 1 : \text{LENG}$ , the value of $G(k)$ should be $\frac{\partial f_i(x)}{\partial x_j}$ , where $i = \text{IGFUN}(k)$ , $j = \text{JGVAR}(k)$ , for $k = 1, 2, \dots, \text{LENG}$ .                                                                                                                                                                                   |              |
|    | <i>On exit:</i> G contains the computed derivatives $G(x)$ (except perhaps if NEEDG = 0).                                                                                                                                                                                                                                                                                                                                                                    |              |
|    | These derivative elements must be stored in G in exactly the same positions as implied by the definitions of arrays IGFUN and JGVAR. There is no internal check for consistency (except indirectly via the optional parameter Verify Level), so great care is essential.                                                                                                                                                                                     |              |

|     |                                          |                |
|-----|------------------------------------------|----------------|
| 10: | CUSER(*) – CHARACTER*8 array             | User Workspace |
| 11: | IUSER(*) – INTEGER array                 | User Workspace |
| 12: | RUSER(*) – <b>double precision</b> array | User Workspace |

**Note:** the dimension of the arrays CUSER, IUSER and RUSER is 1.

USRFUN is called from E04VHF with the parameters CUSER, IUSER and RUSER as supplied to E04VHF. These parameters are not touched by E04VHF and can be used as an alternative to COMMON.

USRFUN must be declared as EXTERNAL in the (sub)program from which E04VHF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

|     |                                         |       |
|-----|-----------------------------------------|-------|
| 10: | IAFUN(LENA) – INTEGER array             | Input |
| 11: | JAVAR(LENA) – INTEGER array             | Input |
| 12: | A(LENA) – <b>double precision</b> array | Input |

*On entry:* define the co-ordinates  $(i, j)$  and values  $A_{ij}$  of the nonzero elements of the linear part  $A$  of the function  $F(x) = f(x) + Ax$ .

In particular, NEA triples  $(IAFUN(k), JAVAR(k), A(k))$  define the row and column indices  $i = IAFUN(k)$  and  $j = JAVAR(k)$  of the element  $A_{ij} = A(k)$ .

The co-ordinates may define the elements of  $A$  in any order.

|     |                |       |
|-----|----------------|-------|
| 13: | LENA – INTEGER | Input |
|-----|----------------|-------|

*On entry:* the dimension of the arrays IAFUN, JAVAR and A that hold  $(i, j, A_{ij})$  as declared in the (sub)program from which E04VHF is called.

*Constraint:*  $LENA \geq 1$ .

|     |               |       |
|-----|---------------|-------|
| 14: | NEA – INTEGER | Input |
|-----|---------------|-------|

*On entry:* is the number of nonzero entries in  $A$  such that  $F(x) = f(x) + Ax$ .

*Constraint:*  $0 \leq NEA \leq LENA$ .

|     |                             |       |
|-----|-----------------------------|-------|
| 15: | IGFUN(LENG) – INTEGER array | Input |
| 16: | JGVAR(LENG) – INTEGER array | Input |

*On entry:* define the co-ordinates  $(i, j)$  of the nonzero elements of  $G$ , the nonlinear part of the derivative  $J(x) = G(x) + A$  of the function  $F(x) = f(x) + Ax$ . E04VJF may be used to define these two arrays.

The co-ordinates can define the elements of  $G$  in any order. However, USRFUN must define the actual elements of  $G$  in exactly the same order as defined by the co-ordinates (IGFUN, JGVAR).

|     |                |       |
|-----|----------------|-------|
| 17: | LENG – INTEGER | Input |
|-----|----------------|-------|

*On entry:* the dimension of the arrays IGFUN and JGVAR that define the varying Jacobian elements  $(i, j, G_{ij})$  as declared in the (sub)program from which E04VHF is called.

*Constraint:*  $LENG \geq 1$ .

|     |               |       |
|-----|---------------|-------|
| 18: | NEG – INTEGER | Input |
|-----|---------------|-------|

*On entry:* the number of nonzero entries in  $G$ .

*Constraint:*  $0 \leq NEG \leq LENG$ .

|     |                                         |       |
|-----|-----------------------------------------|-------|
| 19: | XLOW(N) – <b>double precision</b> array | Input |
| 20: | XUPP(N) – <b>double precision</b> array | Input |

*On entry:* contain the lower and upper bounds  $l_x$  and  $u_x$  on the variables  $x$ .

To specify a nonexistent lower bound  $[l_x]_j = -\infty$ , set  $XLOW(j) \leq -infbnd$ , where *infbnd* is the optional parameter Infinite Bound Size. To specify a nonexistent upper bound  $[u_x]_j = \infty$ , set  $XUPP(j) \geq infbnd$ .

To fix the  $j$ th variable at  $x_j = \beta$ , where  $|\beta| < infbnd$ , set  $XLOW(j) = XUPP(j) = \beta$ .

*Constraint:*  $XLOW(i) \leq XUPP(i)$ , for  $i = 1, 2, \dots, N$ .

21: XNAMES(NXNAME) – CHARACTER\*8 array *Input*

*On entry:* the optional names for the variables.

If NXNAME = 1, XNAMES is not referenced and default names will be used for output.

If NXNAME = N, XNAMES( $j$ ) should contain the 8-character name of the  $j$ th variable.

22: FLOW(NF) – **double precision** array *Input*

23: FUPP(NF) – **double precision** array *Input*

*On entry:* contain the lower and upper bounds  $l_F$  and  $u_F$  on  $F(x)$ .

To specify a nonexistent lower bound  $[l_F]_i = -\infty$ , set  $FLOW(i) \leq -infbnd$ . For a nonexistent upper bound  $[u_F]_i = \infty$ , set  $FUPP(i) \geq infbnd$ .

To make the  $i$ th constraint an *equality* at  $F_i = \beta$ , where  $|\beta| < infbnd$ , set  $FLOW(i) = FUPP(i) = \beta$ .

*Constraint:*  $FLOW(i) \leq FUPP(i)$ , for  $i = 1, 2, \dots, N$ .

24: FNAMES(NFNAME) – CHARACTER\*8 array *Input*

*On entry:* the optional names for the problem functions.

If NFNAME = 1, FNAMES is not referenced and default names will be used for output.

If NFNAME = NF, FNAMES( $i$ ) should contain the 8-character name of the  $i$ th row of  $F$ .

25: X(N) – **double precision** array *Input/Output*

*On entry:* an initial estimate of the variables  $x$ . See the following description of XSTATE.

*On exit:* the final values of the variable  $x$ .

26: XSTATE(N) – INTEGER array *Input/Output*

*On entry:* the initial state for each variable  $x$ .

If START = 0 or 1 and no basis information is provided (the optional parameters Old Basis File, Insert File and Load File are all set to 0; the default) X and XSTATE must be defined.

If nothing special is known about the problem, or if there is no wish to provide special information, you may set  $X(j) = 0.0$ ,  $XSTATE(j) = 0$ , for all  $j = 1, 2, \dots, N$ . If you set  $X(j) = XLOW(j)$  set  $XSTATE(j) = 4$ ; if you set  $X(j) = XUPP(j)$  then set  $XSTATE(j) = 5$ . In this case a Crash procedure is used to select an initial basis.

If START = 0 or 1 and basis information is provided (at least one of the optional parameters Old Basis File, Insert File and Load File is nonzero) X and XSTATE need not be set.

If START = 2 (Warm Start), X and XSTATE must be set (probably from a previous call). In this case  $XSTATE(j)$  must be 0, 1, 2 or 3, for  $j = 1, 2, \dots, N$ .

*On exit:* the final state of the variables.

| $XSTATE(j)$ | State of variable $j$ | Usual value of $X(j)$           |
|-------------|-----------------------|---------------------------------|
| 0           | nonbasic              | $XLOW(j)$                       |
| 1           | nonbasic              | $XUPP(j)$                       |
| 2           | superbasic            | Between $XLOW(j)$ and $XUPP(j)$ |
| 3           | basic                 | Between $XLOW(j)$ and $XUPP(j)$ |

Basic and superbasic variables may be outside their bounds by as much as the optional parameter Minor Feasibility Tolerance. Note that if scaling is specified, the feasibility tolerance applies to the variables of the *scaled* problem. In this case, the variables of the original problem may be as much as 0.1 outside their bounds, but this is unlikely unless the problem is very badly scaled. Check the value of Primal infeasibility output to the unit number associated with the optional parameter Print File.

Very occasionally some nonbasic variables may be outside their bounds by as much as the optional parameter Minor Feasibility Tolerance, and there may be some nonbasics for which  $X(j)$  lies strictly between its bounds.

If  $NINF > 0$ , some basic and superbasic variables may be outside their bounds by an arbitrary amount (bounded by  $SINF$  if scaling was not used).

*Constraint:*  $0 \leq XSTATE(j) \leq 5$ , for  $j = 1, 2, \dots, N$ .

27:  $XMUL(N)$  – **double precision** array *Output*

*On exit:* the vector of the dual variables (Lagrange multipliers) for the simple bounds  $l_x \leq x \leq u_x$ .

28:  $F(NF)$  – **double precision** array *Input/Output*

*On entry:* an initial value for the problem functions  $F$ . See the following description of  $FSTATE$ .

*On exit:* the final values for the problem functions  $F$  (the values  $F$  at the final point  $X$ ).

29:  $FSTATE(NF)$  – **INTEGER** array *Input/Output*

*On entry:* the initial state for the problem functions  $F$ .

If  $START = 0$  or  $1$  and no basis information is provided (the optional parameters Old Basis File, Insert File and Load File are all set to 0; the default,  $F$  and  $FSTATE$  must be defined.

If nothing special is known about the problem, or if there is no wish to provide special information, you may set  $F(i) = 0.0$ ,  $FSTATE(i) = 0$ , for all  $i = 1, 2, \dots, NF$ . Less trivially, to say that the optimal value of function  $F(i)$  will probably be equal to one of its bounds, set  $F(i) = FLOW(i)$  and  $FSTATE(i) = 4$  or  $F(i) = FUPP(i)$  and  $FSTATE(i) = 5$  as appropriate. In this case a Crash procedure is used to select an initial basis.

If  $START = 0$  or  $1$  and basis information is provided (at least one of the optional parameters Old Basis File, Insert File and Load File is nonzero),  $F$  and  $FSTATE$  need not be set.

If  $START = 2$  (Warm Start),  $F$  and  $FSTATE$  must be set (probably from a previous call). In this case  $FSTATE(i)$  must be 0, 1, 2 or 3, for  $i = 1, 2, \dots, NF$ .

*On exit:* the final state of the variables. The elements of  $FSTATE$  have the following meaning:

| $FSTATE(i)$ | State of the corresponding slack variable | Usual value of $F(i)$           |
|-------------|-------------------------------------------|---------------------------------|
| 0           | nonbasic                                  | $FLOW(i)$                       |
| 1           | nonbasic                                  | $FUPP(i)$                       |
| 2           | superbasic                                | Between $FLOW(i)$ and $FUPP(i)$ |
| 3           | basic                                     | Between $FLOW(i)$ and $FUPP(i)$ |

Basic and superbasic slack variables may lead to the corresponding functions being outside their bounds by as much as the optional parameter Minor Feasibility Tolerance.

Very occasionally some functions may be outside their bounds by as much as the optional parameter Minor Feasibility Tolerance, and there may be some nonbasics for which  $F(i)$  lies strictly between its bounds.

If  $NINF > 0$ , some basic and superbasic variables may be outside their bounds by an arbitrary amount (bounded by  $SINF$  if scaling was not used).

*Constraint:*  $0 \leq FSTATE(i) \leq 5$ , for  $i = 1, 2, \dots, NF$ .

- 30: FMUL(NF) – **double precision** array Input/Output
- On entry:* an estimate of  $\gamma$ , the vector of Lagrange multipliers (shadow prices) for the constraints  $l_F \leq F(x) \leq u_F$ . All NF components must be defined. If nothing is known about  $\gamma$ , set  $\text{FMUL}(i) = 0.0$ , for  $i = 1, 2, \dots, \text{NF}$ . For warm start use the values from a previous call.
- On exit:* the vector of the dual variables (Lagrange multipliers) for the general constraints  $l_F \leq F(x) \leq u_F$
- 31: NS – INTEGER Input/Output
- On entry:* the number of superbasic variables. NS need not be specified for cold starts, but should retain its value from a previous call when warm start is used.
- On exit:* the final number of superbasic variables.
- 32: NINF – INTEGER Output
- 33: SINP – **double precision** Output
- On exit:* are the number and the sum of the infeasibilities of constraints that lie outside one of their bounds by more than the optional parameter Minor Feasibility Tolerance *before the solution is unscaled*.
- If any *linear* constraints are infeasible,  $x$  minimizes the sum of the infeasibilities of the linear constraints subject to the upper and lower bounds being satisfied. In this case NINF gives the number of variables and linear constraints lying outside their upper or lower bounds. The nonlinear constraints are not evaluated.
- Otherwise,  $x$  minimizes the sum of infeasibilities of the *nonlinear* constraints subject to the linear constraints and upper and lower bounds being satisfied. In this case NINF gives the number of components of  $F(x)$  lying outside their bounds by more than the optional parameter Minor Feasibility Tolerance. Again this is *before the solution is unscaled*.
- 34: CW(LENCW) – CHARACTER\*8 array Communication Array
- 35: LENCW – INTEGER Input
- On entry:* the dimension of the array CW as declared in the (sub)program from which E04VHF is called.
- Constraint:* LENCW  $\geq 600$ .
- 36: IW(LENIW) – INTEGER array Communication Array
- 37: LENIW – INTEGER Input
- On entry:* the dimension of the array IW as declared in the (sub)program from which E04VHF is called.
- Constraint:* LENIW  $\geq 600$ .
- 38: RW(LENRW) – **double precision** array Communication Array
- 39: LENRW – INTEGER Input
- On entry:* the dimension of the array RW as declared in the (sub)program from which E04VHF is called.
- Constraint:* LENRW  $\geq 600$ .
- 40: CUSER(\*) – CHARACTER\*8 array User Workspace
- 41: IUSER(\*) – INTEGER array User Workspace
- 42: RUSER(\*) – **double precision** array User Workspace

**Note:** the dimension of the arrays CUSER, IUSER and RUSER must be at least 1.

CUSER, IUSER and RUSER are not used by E04VHF, but are passed directly to USRFUN and may be used to communicate with E04VHF.

## 43: IFAIL – INTEGER

Input/Output

*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

*On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, because for this routine the values of the output parameters may be useful even if IFAIL  $\neq$  0 on exit, the recommended value is -1. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

E04VHF returns with IFAIL = 0 if the iterates have converged to a point  $x$  that satisfies the first-order Kuhn–Tucker (see Section 12.2) conditions to the accuracy requested by the optional parameter Major Optimality Tolerance, i.e., the projected gradient and active constraint residuals are negligible at  $x$ .

You should check whether the following four conditions are satisfied:

- (i) the final value of rgNorm (see Section 12.2) is significantly less than that at the starting point;
- (ii) during the final major iterations, the values of Step and Minors (see Section 12.1) are both one;
- (iii) the last few values of both rgNorm and SumInf (see Section 12.2) become small at a fast linear rate; and
- (iv) condHz (see Section 12.1) is small.

If all these conditions hold,  $x$  is almost certainly a local minimum of (1).

One caution about ‘Optimal solutions’. Some of the variables or slacks may lie outside their bounds more than desired, especially if scaling was requested. Max Primal infeas in the Print file (see Section 12) refers to the largest bound infeasibility and which variable is involved. If it is too large, consider restarting with a smaller Minor Feasibility Tolerance (say 10 times smaller) and perhaps Scale Option = 0.

Similarly, Max Dual infeas in the Print file indicates which variable is most likely to be at a nonoptimal value. Broadly speaking, if

$$\text{Max Dual infeas}/\text{Max pi} = 10^{-d},$$

then the objective function would probably change in the  $d$ th significant digit if optimization could be continued. If  $d$  seems too large, consider restarting with a smaller Major Optimality Tolerance.

Finally, Nonlinear constraint violn in the Print file shows the maximum infeasibility for nonlinear rows. If it seems too large, consider restarting with a smaller Major Feasibility Tolerance.

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

**Note:** E04VHF may return useful information for one or more of the following detected errors or warnings.

Errors or warnings detected by the routine:

IFAIL = 1

The initialization routine E04VGF has not been called or at least one of LENCW, LENIW and LENRW is less than 600.

IFAIL = 2

An input parameter is invalid. The output message provides more details of the invalid argument.

IFAIL = 3

Requested accuracy could not be achieved.

A feasible solution has been found, but the requested accuracy in the dual infeasibilities could not be achieved. An abnormal termination has occurred, but E04VHF is within  $10^{-2}$  of satisfying the Major Optimality Tolerance. Check that the Major Optimality Tolerance is not too small.

IFAIL = 4

The problem appears to be infeasible.

When the constraints are linear, this message is based on a relatively reliable indicator of infeasibility. Feasibility is measured with respect to the upper and lower bounds on the variables and slacks. Among all the points satisfying the general constraints  $Ax - s = 0$  (see (6) and (7) in Section 10.2), there is apparently no point that satisfies the bounds on  $x$  and  $s$ . Violations as small as the Minor Feasibility Tolerance are ignored, but at least one component of  $x$  or  $s$  violates a bound by more than the tolerance.

When nonlinear constraints are present, infeasibility is *much* harder to recognize correctly. Even if a feasible solution exists, the current linearization of the constraints may not contain a feasible point. In an attempt to deal with this situation, when solving each QP subproblem, E04VHF is prepared to relax the bounds on the slacks associated with nonlinear rows.

If a QP subproblem proves to be infeasible or unbounded (or if the Lagrange multiplier estimates for the nonlinear constraints become large), E04VHF enters so-called ‘nonlinear elastic’ mode. The subproblem includes the original QP objective and the sum of the infeasibilities – suitably weighted using the optional parameter Elastic Weight. In elastic mode, some of the bounds on the nonlinear rows are ‘elastic’ – i.e., they are allowed to violate their specific bounds. Variables subject to elastic bounds are known as *elastic variables*. An elastic variable is free to violate one or both of its original upper or lower bounds. If the original problem has a feasible solution and the elastic weight is sufficiently large, a feasible point eventually will be obtained for the perturbed constraints, and optimization can continue on the subproblem. If the nonlinear problem has no feasible solution, E04VHF will tend to determine a ‘good’ infeasible point if the elastic weight is sufficiently large. (If the elastic weight were infinite, E04VHF would locally minimize the nonlinear constraint violations subject to the linear constraints and bounds.)

Unfortunately, even though E04VHF locally minimizes the nonlinear constraint violations, there may still exist other regions in which the nonlinear constraints are satisfied. Wherever possible, nonlinear constraints should be defined in such a way that feasible points are known to exist when the constraints are linearized.

IFAIL = 5

The problem appears to be unbounded (or badly scaled).

For linear problems, unboundedness is detected by the simplex method when a nonbasic variable can be increased or decreased by an arbitrary amount without causing a basic variable to violate a bound. Consider adding an upper or lower bound to the variable. Also, examine the constraints that have nonzeros in the associated column, to see if they have been formulated as intended.

Very rarely, the scaling of the problem could be so poor that numerical error will give an erroneous indication of unboundedness. Consider using the optional parameter Scale Option.

For nonlinear problems, E04VHF monitors both the size of the current objective function and the size of the change in the variables at each step. If either of these is very large (as judged by the unbounded parameters (see Section 12.1)), the problem is terminated and declared unbounded. To avoid large function values, it may be necessary to impose bounds on some of the variables in order to keep them away from singularities in the nonlinear functions.

The message may indicate an abnormal termination while enforcing the limit on the constraint violations. This exit implies that the objective is not bounded below in the feasible region defined by expanding the bounds by the value of the Violation Limit.

IFAIL = 6

Iteration limit reached.

Either the Iterations Limit or the Major Iterations Limit was exceeded before the required solution could be found. Check the iteration log to be sure that progress was being made. If so, and if you caused a basis file to be saved by using the optional parameter New Basis File, consider restarting the run using the optional parameter Old Basis File to see whether further progress can be made. If you have no basis file available, you might rerun the problem after increasing the optional parameters Minor Iterations Limit and/or Major Iterations Limit.

If none of the above limits have been reached, this error may mean that the problem appears to be more nonlinear than anticipated. The current set of basic and superbasic variables have been optimized as much as possible and a pricing operation (where a nonbasic variable is selected to become superbasic) is necessary to continue, but it can't continue as the number of superbasic variables has already reached the limit specified by the optional parameter Superbasics Limit. In general, raise the Superbasics Limit  $s$  by a reasonable amount, bearing in mind the storage needed for the reduced Hessian.

IFAIL = 7

Numerical difficulties have been encountered and no further progress can be made.

Several circumstances could lead to this exit.

1. USRFUN could be returning accurate function values but inaccurate gradients (or vice versa). This is the most likely cause. Study the comments given for IFAIL = 8, and do your best to ensure that the coding is correct.
2. The function and gradient values could be consistent, but their precision could be too low. For example, accidental use of a *real* data type when *double precision* was intended would lead to a relative function precision of about  $10^{-6}$  instead of something like  $10^{-15}$ . The default Major Optimality Tolerance of  $2 \times 10^{-6}$  would need to be raised to about  $10^{-3}$  for optimality to be declared (at a rather suboptimal point). Of course, it is better to revise the function coding to obtain as much precision as economically possible.
3. If function values are obtained from an expensive iterative process, they may be accurate to rather few significant figures, and gradients will probably not be available. One should specify

Function Precision  $t$

Major Optimality Tolerance  $\sqrt{t}$

but even then, if  $t$  is as large as  $10^{-5}$  or  $10^{-6}$  (only 5 or 6 significant figures), the same exit condition may occur. At present the only remedy is to increase the accuracy of the function calculation.

4. An  $LU$  factorization of the basis has just been obtained and used to recompute the basic variables  $x_B$ , given the present values of the superbasic and nonbasic variables. A step of 'iterative refinement' has also been applied to increase the accuracy of  $x_B$ . However, a row check has revealed that the resulting solution does not satisfy the current constraints  $Ax - s = 0$  sufficiently well.

This probably means that the current basis is very ill-conditioned. If there are some linear constraints and variables, try Scale Option = 1 if scaling has not yet been used.

For certain highly structured basis matrices (notably those with band structure), a systematic growth may occur in the factor  $U$ . Consult the description of Umax and Growth in Section 12.4 and set the LU Factor Tolerance to 2.0 (or possibly even smaller, but not less than 1.0).

5. The first factorization attempt will have found the basis to be structurally or numerically singular. (Some diagonals of the triangular matrix  $U$  were respectively zero or smaller than a certain tolerance.) The associated variables are replaced by slacks and the modified basis is refactorized, but singularity persists. This must mean that the problem is badly scaled, or the LU Factor Tolerance is too much larger than 1.0. This is highly unlikely to occur.

IFAIL = 8

Derivative appears to be incorrect.

A check has been made on some elements of the Jacobian as returned in the parameter G of USRFUN. At least one value disagrees remarkably with its associated forward difference estimate (the relative difference between the computed and estimated values is 1.0 or more). This exit is a safeguard, since E04VHF will usually fail to make progress when the computed gradients are seriously inaccurate. In the process it may expend considerable effort before terminating with IFAIL = 7.

Check the function and Jacobian computation *very carefully* in USRFUN. A simple omission could explain everything. If a component is very large, then give serious thought to scaling the function or the nonlinear variables.

If you feel *certain* that the computed Jacobian is correct (and that the forward-difference estimate is therefore wrong), you can specify Verify Level = 0 to prevent individual elements from being checked. However, the optimization procedure may have difficulty.

IFAIL = 9

Undefined user-supplied function.

You have indicated that the problem functions are undefined by assigning the value STATUS = -1 on exit from USRFUN. E04VHF attempts to evaluate the problem functions closer to a point at which the functions are already known to be defined. This exit occurs if E04VHF is unable to find a point at which the functions are defined. This will occur in the case of:

- undefined functions with no recovery possible;
- undefined functions at the first point;
- undefined functions at the first feasible point; or
- undefined functions when checking derivatives.

IFAIL = 10

User requested termination.

You have indicated the wish to terminate solution of the current problem by setting STATUS to a value < -1 on exit from USRFUN.

IFAIL = 11

Internal memory allocation failed when attempting to obtain the required workspace. Please contact NAG.

IFAIL = 12

Internal memory allocation was insufficient. Please contact NAG.

IFAIL = 13

An error has occurred in the basis package, perhaps indicating incorrect setup of arrays. Set the optional parameter Print File and examine the output carefully for further information.

IFAIL = 14

An unexpected error has occurred. Set the optional parameter Print File and examine the output carefully for further information.

## 7 Accuracy

If the value of the optional parameter Major Optimality Tolerance is set to  $10^{-d}$  (default value =  $\sqrt{\epsilon}$ ) and IFAIL = 0 on exit, then the final value of  $f(x)$  should have approximately  $d$  correct significant digits.

## 8 Further Comments

This section describes the final output produced by E04VHF. Intermediate and other output are given in Section 12.

### 8.1 The Final Output

If Print File  $> 0$ , the final output, including a listing of the status of every variable and constraint will be sent to the channel numbers associated with Print File. The following describes the output for each constraint (row) and variable (column).

#### 8.1.1 The ROWS section

General linear constraints take the form  $l \leq A_L x \leq u$ . The  $i$ th constraint is therefore of the form

$$\alpha \leq \nu_i x \leq \beta,$$

where  $\nu_i$  is the  $i$ th row of  $A_L$ .

Internally, the constraints take the form  $A_L x - s = 0$ , where  $s$  is the set of slack variables (which satisfy the bounds  $l \leq s \leq u$ ). For the  $i$ th row it is the slack variable  $s_i$  that is directly available and it is sometimes convenient to refer to its state. Nonlinear constraints  $\alpha \leq f_i(x) + \nu_i x \leq \beta$  are treated similarly, except that the row activity and degree of infeasibility are computed directly from  $f_i(x) + \nu_i x$ , rather than  $s_i$ .

A full stop (.) is printed for any numerical value that is exactly zero.

| Label                                                                                                                                                                                             | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number                                                                                                                                                                                            | is the value of $n + i$ . (This is used internally to refer to $s_i$ in the intermediate output.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Row                                                                                                                                                                                               | gives the name of the $i$ th row.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| State                                                                                                                                                                                             | the state of the $i$ th row relative to the bounds $\alpha$ and $\beta$ . The various states possible are as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| LL                                                                                                                                                                                                | the row is at its lower limit, $\alpha$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| UL                                                                                                                                                                                                | the row is at its upper limit, $\beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| EQ                                                                                                                                                                                                | the limits are the same ( $\alpha = \beta$ ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| FR                                                                                                                                                                                                | $s_i$ is nonbasic and currently zero, even though it is free to take any value between its bounds $\alpha$ and $\beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| BS                                                                                                                                                                                                | $s_i$ is basic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| SBS                                                                                                                                                                                               | $s_i$ is superbasic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| A key is sometimes printed before State. Note that unless the optional parameter Scale Option = 0 is specified, the tests for assigning a key are applied to the variables of the scaled problem. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| A                                                                                                                                                                                                 | <i>Alternative optimum possible.</i> The variable is nonbasic, but its reduced gradient is essentially zero. This means that if the variable were allowed to start moving away from its bound, there would be no change in the value of the objective function. The values of the other free variables <i>might</i> change, giving a genuine alternative solution. However, if there are any degenerate variables (labelled D), the actual change might prove to be zero, since one of them could encounter a bound immediately. In either case, the values of the Lagrange multipliers <i>might</i> also change. |
| D                                                                                                                                                                                                 | <i>Degenerate.</i> The variable is basic or superbasic, but it is equal (or very close) to one of its bounds.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                |                                                                                                                                                                                                                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| I              | <i>Infeasible.</i> The variable is basic or superbasic and is currently violating one of its bounds by more than the value of the Feasibility Tolerance.                                                                                                                                                                         |
| N              | <i>Not precisely optimal.</i> The variable is nonbasic or superbasic. If the value of the reduced gradient for the variable exceeds the value of the optional parameter Major Optimality Tolerance, the solution would not be declared optimal because the reduced gradient for the variable would not be considered negligible. |
| Activity       | is the value of $\nu_i x$ (or $f_i(x) + \nu_i x$ for nonlinear rows) at the final iterate.                                                                                                                                                                                                                                       |
| Slack Activity | is the value by which the row differs from its nearest bound. (For the free row (if any), it is set to Activity.)                                                                                                                                                                                                                |
| Lower Limit    | is $\alpha$ , the lower bound on the row.                                                                                                                                                                                                                                                                                        |
| Upper Limit    | is $\beta$ , the upper bound on the row.                                                                                                                                                                                                                                                                                         |
| Dual Activity  | is the value of the dual variable $\pi_i$ (the Lagrange multiplier for the $i$ th constraint). The full vector $\pi$ always satisfies $B^T \pi = g_B$ , where $B$ is the current basis matrix and $g_B$ contains the associated gradients for the current objective function. For FP problems, $\pi_i$ is set to zero.           |
| i              | gives the index $i$ of the $i$ th row.                                                                                                                                                                                                                                                                                           |

### 8.1.2 The COLUMNS section

Let the  $j$ th component of  $x$  be the variable  $x_j$  and assume that it satisfies the bounds  $\alpha \leq x_j \leq \beta$ . A fullstop (.) is printed for any numerical value that is exactly zero.

| Label                                                                                                                                                                                             | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number                                                                                                                                                                                            | is the column number $j$ . (This is used internally to refer to $x_j$ in the intermediate output.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Column                                                                                                                                                                                            | gives the name of $x_j$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| State                                                                                                                                                                                             | the state of $x_j$ relative to the bounds $\alpha$ and $\beta$ . The various states possible are as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| LL                                                                                                                                                                                                | $x_j$ is nonbasic at its lower limit, $\alpha$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| UL                                                                                                                                                                                                | $x_j$ is nonbasic at its upper limit, $\beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| EQ                                                                                                                                                                                                | $x_j$ is nonbasic and fixed at the value $\alpha = \beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| FR                                                                                                                                                                                                | $x_j$ is nonbasic at some value strictly between its bounds: $\alpha < x_j < \beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| BS                                                                                                                                                                                                | $x_j$ is basic. Usually $\alpha < x_j < \beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| SBS                                                                                                                                                                                               | $x_j$ is superbasic. Usually $\alpha < x_j < \beta$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| A key is sometimes printed before State. Note that unless the optional parameter Scale Option = 0 is specified, the tests for assigning a key are applied to the variables of the scaled problem. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| A                                                                                                                                                                                                 | <i>Alternative optimum possible.</i> The variable is nonbasic, but its reduced gradient is essentially zero. This means that if the variable were allowed to start moving away from its bound, there would be no change in the value of the objective function. The values of the other free variables <i>might</i> change, giving a genuine alternative solution. However, if there are any degenerate variables (labelled D), the actual change might prove to be zero, since one of them could encounter a bound immediately. In either case, the values of the Lagrange multipliers <i>might</i> also change. |
| D                                                                                                                                                                                                 | <i>Degenerate.</i> The variable is basic or superbasic, but it is equal (or very close) to one of its bounds.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

- I *Infeasible.* The variable is basic or superbasic and is currently violating one of its bounds by more than the value of the Feasibility Tolerance.
- N *Not precisely optimal.* The variable is nonbasic or superbasic. If the value of the reduced gradient for the variable exceeds the value of the optional parameter Major Optimality Tolerance, the solution would not be declared optimal because the reduced gradient for the variable would not be considered negligible.

|                |                                                                                                                                                                |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Activity       | is the value of $x_j$ at the final iterate.                                                                                                                    |
| Obj Gradient   | is the value of $g_j$ at the final iterate. For FP problems, $g_j$ is set to zero.                                                                             |
| Lower Limit    | is the lower bound specified for the variable. None indicates that $XLOW(j) \leq -infbnd$ .                                                                    |
| Upper Limit    | is the upper bound specified for the variable. None indicates that $XUPP(j) \geq infbnd$ .                                                                     |
| Reduced Gradnt | is the value of the reduced gradient $d_j = g_j - \pi^T a_j$ where $a_j$ is the $j$ th column of the constraint matrix. For FP problems, $d_j$ is set to zero. |
| $m + j$        | is the value of $m + j$ .                                                                                                                                      |

Note that movement off a constraint (as opposed to a variable moving away from its bound) can be interpreted as allowing the entry in the Slack Activity column to become positive.

Numerical values are output with a fixed number of digits; they are not guaranteed to be accurate to this precision.

## 9 Example

This example is a reformulation of Problem 74 from Hock and Schittkowski (1981) and involves the minimization of the nonlinear function

$$f(x) = 10^{-6}x_3^3 + \frac{2}{3} \times 10^{-6}x_4^3 + 3x_3 + 2x_4$$

subject to the bounds

$$\begin{aligned} -0.55 &\leq x_1 \leq 0.55, \\ -0.55 &\leq x_2 \leq 0.55, \\ 0 &\leq x_3 \leq 1200, \\ 0 &\leq x_4 \leq 1200, \end{aligned}$$

to the nonlinear constraints

$$\begin{aligned} 1000 \sin(-x_1 - 0.25) + 1000 \sin(-x_2 - 0.25) - x_3 &= -894.8, \\ 1000 \sin(x_1 - 0.25) + 1000 \sin(x_1 - x_2 - 0.25) - x_4 &= -894.8, \\ 1000 \sin(x_2 - 0.25) + 1000 \sin(x_2 - x_1 - 0.25) &= -1294.8, \end{aligned}$$

and to the linear constraints

$$\begin{aligned} -x_1 + x_2 &\geq -0.55, \\ x_1 - x_2 &\geq -0.55. \end{aligned}$$

The initial point, which is infeasible, is

$$x_0 = (0, 0, 0, 0)^T,$$

and  $f(x_0) = 0$ .

The optimal solution (to five figures) is

$$x^* = (0.11887, -0.39623, 679.94, 1026.0)^T,$$

and  $f(x^*) = 5126.4$ . All the nonlinear constraints are active at the solution.

The example in the document for E04VJF solves the above problem. It first calls E04VJF to determine the sparsity pattern before calling E04VHF.

The example in the document for E04VKF solves the above problem using some of the optional parameters described in Section 11.

The formulation of the problem combines the constraints and the objective into a single vector ( $F$ ) which is split into linear part ( $A_L x$ ) and a nonlinear part ( $f$ ). For example we could write

$$F = \begin{pmatrix} 1000 \sin(-x_1 - 0.25) + 1000 \sin(-x_2 - 0.25) - x_3 \\ 1000 \sin(x_1 - 0.25) + 1000 \sin(x_1 - x_2 - 0.25) - x_4 \\ 1000 \sin(x_2 - 0.25) + 1000 \sin(x_2 - x_1 - 0.25) \\ -x_1 + x_2 \\ x_1 - x_2 \\ 10^{-6} x_3^3 + \frac{2}{3} \times 10^{-6} x_4^3 + 3x_3 + 2x_4 \end{pmatrix} = f + A_L x$$

where

$$f = \begin{pmatrix} 1000 \sin(-x_1 - 0.25) + 1000 \sin(-x_2 - 0.25) \\ 1000 \sin(x_1 - 0.25) + 1000 \sin(x_1 - x_2 - 0.25) \\ 1000 \sin(x_2 - 0.25) + 1000 \sin(x_2 - x_1 - 0.25) \\ 0 \\ 0 \\ 10^{-6} x_3^3 + \frac{2}{3} \times 10^{-6} x_4^3 \end{pmatrix}$$

and

$$A_L = \begin{pmatrix} 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & -1 \\ 0 & 0 & 0 & 0 \\ -1 & 1 & 0 & 0 \\ 1 & -1 & 0 & 0 \\ 0 & 0 & 3 & 2 \end{pmatrix}.$$

The nonzero elements of  $A_L$  need to be stored in the triples (IAFUN( $k$ ), JAVAR( $k$ ), A( $k$ )) in any order. For example

| $k$          | 1  | 2  | 3  | 4 | 5 | 6  | 7 | 8 |
|--------------|----|----|----|---|---|----|---|---|
| IAFUN( $k$ ) | 1  | 2  | 4  | 4 | 5 | 5  | 6 | 6 |
| JAVAR( $k$ ) | 3  | 4  | 1  | 2 | 1 | 2  | 3 | 4 |
| A( $k$ )     | -1 | -1 | -1 | 1 | 1 | -1 | 3 | 2 |

The nonlinear functions  $f$  and the Jacobian need to be supplied in USRFUN. Please note that there is no need to assign any value to  $f_4$  or  $f_5$  as there is no nonlinear part in  $F_4$  or  $F_5$ .

The nonzero entries of the Jacobian of  $f$  are

$$\begin{aligned}\frac{\partial f_1}{\partial x_1} &= -1000 \cos(-x_1 - 0.25) \\ \frac{\partial f_1}{\partial x_2} &= -1000 \cos(-x_2 - 0.25) \\ \frac{\partial f_2}{\partial x_1} &= 1000 \cos(x_1 - 0.25) + 1000 \cos(x_1 - x_2 - 0.25) \\ \frac{\partial f_2}{\partial x_2} &= -1000 \cos(x_1 - x_2 - 0.25) \\ \frac{\partial f_3}{\partial x_1} &= -1000 \cos(x_2 - x_1 - 0.25) \\ \frac{\partial f_3}{\partial x_2} &= 1000 \cos(x_2 - 0.25) + 1000 \cos(x_2 - x_1 - 0.25) \\ \frac{\partial f_6}{\partial x_3} &= 3 \times 10^{-6} x_3^2 \\ \frac{\partial f_6}{\partial x_4} &= 2 \times 10^{-6} x_4^2\end{aligned}$$

So the arrays IGFUN and JGVAR must contain:

| $k$          | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|--------------|---|---|---|---|---|---|---|---|
| IGFUN( $k$ ) | 1 | 1 | 2 | 2 | 3 | 3 | 6 | 6 |
| JGVAR( $k$ ) | 1 | 2 | 1 | 2 | 1 | 2 | 3 | 4 |

and USRFUN must return in  $G(k)$  the value of  $\frac{\partial f_i}{\partial x_j}$ , where  $i = \text{IGFUN}(k)$  and  $j = \text{JGVAR}(k)$ .

## 9.1 Program Text

```
*      E04VHF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Implicit None Statement ..
      IMPLICIT      NONE
*      .. Parameters ..
      INTEGER
      PARAMETER
      (NIN=5,NOUT=6)
      INTEGER
      PARAMETER
      (NMAX=100,NFMAX=100,LENAMX=300,LENGMX=300)
      INTEGER
      PARAMETER
      (LENCW=600,LENIW=600,LENRW=600)
*      .. Local Scalars ..
      DOUBLE PRECISION OBJADD, SINF
      INTEGER
      I, IFAIL, LENA, LENG, N, NEA, NEG, NF, NFNAME,
+      NINF, NS, NXNAME, OBJROW, START
      CHARACTER*8
      PROB
*      .. Local Arrays ..
      DOUBLE PRECISION A(LENAMX), F(NFMAX), FLOW(NFMAX), FMUL(NFMAX),
+      FUPP(NFMAX), RUSER(1), RW(LENRW), X(NMAX),
+      XLOW(NMAX), XMUL(NMAX), XUPP(NMAX)
      INTEGER
      FSTATE(NFMAX), IAFUN(LENAMX), IGFUN(LENGMX),
+      IUSER(1), IW(LENIW), JAVAR(LENAMX),
+      JGVAR(LENGMX), XSTATE(NMAX)
      CHARACTER*8
      CUSER(1), CW(LENCW), FNAMES(NFMAX), XNAMES(NMAX)
*      .. External Subroutines ..
      EXTERNAL      E04VGF, E04VHF, E04VMF, USRFUN
*      .. Intrinsic Functions ..
      INTRINSIC      MAX
*      .. Executable Statements ..
      WRITE (NOUT,*) 'E04VHF Example Program Results'
*      Skip heading in data file
```

```

      READ (NIN,*)
      READ (NIN,*) N, NF
      READ (NIN,*) NEA, NEG, OBJROW, START
*
      IF (N.LE.NMAX .AND. NF.LE.NFMAX .AND. NEA.LE.LENAMX .AND. NEG.LE.
+      LENGMX) THEN
          LENA = MAX(1,NEA)
          LENG = MAX(1,NEG)
          NXNAME = N
          NFNAME = NF
          OBJADD = 0.0D0
          PROB = ' '
*
*      Read the variable names XNAMES
      READ (NIN,*) (XNAMES(I),I=1,NXNAME)
*      Read the function names FNAMES
      READ (NIN,*) (FNAMES(I),I=1,NFNAME)
*
*      Read the sparse matrix A, the linear part of F
      DO 20 I = 1, NEA
*          For each element read row, column, A(row,column)
          READ (NIN,*) IAFUN(I), JAVAR(I), A(I)
20      CONTINUE
*
*      Read the structure of sparse matrix G, the nonlinear part of F
      DO 40 I = 1, NEG
*          For each element read row, column
          READ (NIN,*) IGFUN(I), JGVAR(I)
40      CONTINUE
*
*      Read the lower and upper bounds on the variables
      DO 60 I = 1, N
          READ (NIN,*) XLOW(I), XUPP(I)
60      CONTINUE
*
*      Read the lower and upper bounds on the functions
      DO 80 I = 1, NF
          READ (NIN,*) FLOW(I), FUPP(I)
80      CONTINUE
*
*      Initialise X, XSTATE, XMUL, F, FSTATE, FMUL
      READ (NIN,*) (X(I),I=1,N)
      READ (NIN,*) (XSTATE(I),I=1,N)
      READ (NIN,*) (XMUL(I),I=1,N)
      READ (NIN,*) (F(I),I=1,NF)
      READ (NIN,*) (FSTATE(I),I=1,NF)
      READ (NIN,*) (FMUL(I),I=1,NF)
*
*      Call E04VGF to initialise E04VHF.
      IFAIL = 1
      CALL E04VGF(CW,LENCW,IW,LENIW,RW,LENRW,IFAIL)
*
      IF (IFAIL.NE.0) THEN
          WRITE (NOUT,99999) IFAIL
          GO TO 100
      END IF
*
*      By default E04VHF does not print monitoring
*      information. Set the print file unit or the summary
*      file unit to get information.
      IFAIL = 0
      CALL E04VMF('Print file',NOUT,CW,IW,RW,IFAIL)
*
*      Solve the problem.
      IFAIL = 1
      CALL E04VHF(START,NF,N,NXNAME,NFNAME,OBJADD,OBJROW,PROB,USRFUN,
+      IAFUN,JAVAR,A,LENA,NEA,IGFUN,JGVAR,LENG,NEG,XLOW,
+      XUPP,XNAMES,FLOW,FUPP,FNAMES,X,XSTATE,XMUL,F,
+      FSTATE,FMUL,NS,NINF,SINF,CW,LENCW,IW,LENIW,RW,
+      LENRW,CUSER,IUSER,RUSER,IFAIL)
*

```

```

        WRITE (NOUT,*)
        IF (IFAIL.GE.0) THEN
            WRITE (NOUT,99998) IFAIL
            IF (IFAIL.EQ.0) THEN
                WRITE (NOUT,99997) F(OBJROW)
                WRITE (NOUT,99996) (X(I),I=1,N)
            END IF
        ELSE
            WRITE (NOUT,99995) IFAIL
        END IF
*
        ELSE
            WRITE (NOUT,99994)
        END IF
100 CONTINUE
*
99999 FORMAT (1X,/1X,' ** E04VGF returned with IFAIL = ',I5)
99998 FORMAT (1X,'On exit from E04VHF, IFAIL = ',I5)
99997 FORMAT (1X,'Final objective value = ',F11.1)
99996 FORMAT (1X,'Optimal X = ',7F9.2)
99995 FORMAT (1X,' ** E04VHF returned with IFAIL = ',I5)
99994 FORMAT (1X,'At least one of N, NF, NEA or NEG is too large')
END
*
SUBROUTINE USRFUN(STATUS,N,X,NEEDF,NF,F,NEEDG,LENG,G,CUSER,IUSER,
+                RUSER)
* .. Implicit None Statement ..
IMPLICIT NONE
* .. Scalar Arguments ..
INTEGER LENG, N, NEEDF, NEEDG, NF, STATUS
* .. Array Arguments ..
DOUBLE PRECISION F(NF), G(LENG), RUSER(*), X(N)
INTEGER IUSER(*)
CHARACTER*8 CUSER(*)
* .. Intrinsic Functions ..
INTRINSIC COS, SIN
* .. Executable Statements ..
IF (NEEDF.GT.0) THEN
* The nonlinear components of f_i(x) need to be assigned,
* for i = 1 to NF
F(1) = 1000.0D+0*SIN(-X(1)-0.25D+0) + 1000.0D+0*SIN(-X(2)
+ -0.25D+0)
F(2) = 1000.0D+0*SIN(X(1)-0.25D+0) + 1000.0D+0*SIN(X(1)-X(2)
+ -0.25D+0)
F(3) = 1000.0D+0*SIN(X(2)-X(1)-0.25D+0) + 1000.0D+0*SIN(X(2)
+ -0.25D+0)
* N.B. in this example there is no need to assign for the wholly
* linear components f_4(x) and f_5(x).
F(6) = 1.0D-6*X(3)**3 + 2.0D-6*X(4)**3/3.0D+0
END IF
*
IF (NEEDG.GT.0) THEN
* The derivatives of the function f_i(x) need to be assigned.
* G(k) should be set to partial derivative df_i(x)/dx_j where
* i = IGFUN(k) and j = IGVAR(k), for k = 1 to LENG.
G(1) = -1000.0D+0*COS(-X(1)-0.25D+0)
G(2) = -1000.0D+0*COS(-X(2)-0.25D+0)
G(3) = 1000.0D+0*COS(X(1)-0.25D+0) + 1000.0D+0*COS(X(1)-X(2)
+ -0.25D+0)
G(4) = -1000.0D+0*COS(X(1)-X(2)-0.25D+0)
G(5) = -1000.0D+0*COS(X(2)-X(1)-0.25D+0)
G(6) = 1000.0D+0*COS(X(2)-X(1)-0.25D+0) + 1000.0D+0*COS(X(2)
+ -0.25D+0)
G(7) = 3.0D-6*X(3)**2
G(8) = 2.0D-6*X(4)**2
END IF
*
RETURN
END

```

## 9.2 Program Data

E04VHF Example Program Data

```

4      6      : Values of N and NF
8      8      6      0 : Values of NEA, NEG, OBJROW and START

'X1'  'X2'  'X3'  'X4'  : XNAMES
'NlnCon 1'  'NlnCon 2'  'NlnCon 3'  'LinCon 1'  'LinCon 2'  'Objectiv' : FNAMES

1  3 -1.0D0 : Nonzero elements of sparse matrix A, the linear part of F.
2  4 -1.0D0 : Each row IAFUN(i), JAVAR(i), A(IAFUN(i),JAVAR(i)), i = 1 to NEA
4  1 -1.0D0
4  2  1.0D0
5  1  1.0D0
5  2 -1.0D0
6  3  3.0D0
6  4  2.0D0

1  1      : Nonzero row/column structure of G, IGFUN(i), JGVAR(i), i = 1 to NEG
1  2
2  1
2  2
3  1
3  2
6  3
6  4

-0.55D0    0.55D0 : Bounds on the variables, XLOW(i), XUPP(i), for i = 1 to N
-0.55D0    0.55D0
0.0D0     1200.0D0
0.0D0     1200.0D0

-894.8D0 -894.8D0 : Bounds on the functions, FLOW(i), FUPP(i), for i = 1 to NF
-894.8D0 -894.8D0
-1294.8D0 -1294.8D0
-0.55D0    1.0D25
-0.55D0    1.0D25
-1.0D25    1.0D25

0.0  0.0  0.0  0.0 : Initial values of X(i), for i = 1 to N
0    0    0    0    : Initial values of XSTATE(i), for i = 1 to N
0.0  0.0  0.0  0.0 : Initial values of XMUL(i), for i = 1 to N

0.0  0.0  0.0  0.0  0.0  0.0 : Initial values of F(i), for i = 1 to NF
0    0    0    0    0    0    : Initial values of FSTATE(i), for i = 1 to NF
0.0  0.0  0.0  0.0  0.0  0.0 : Initial values of FMUL(i), for i = 1 to NF

```

## 9.3 Program Results

E04VHF Example Program Results

Parameters

=====

Files

-----

|                    |   |                        |   |                     |   |
|--------------------|---|------------------------|---|---------------------|---|
| Solution file..... | 0 | Old basis file .....   | 0 | (Print file).....   | 6 |
| Insert file.....   | 0 | New basis file .....   | 0 | (Summary file)..... | 0 |
| Punch file.....    | 0 | Backup basis file..... | 0 |                     |   |
| Load file.....     | 0 | Dump file.....         | 0 |                     |   |

Frequencies

-----

|                        |     |                         |    |                         |       |
|------------------------|-----|-------------------------|----|-------------------------|-------|
| Print frequency.....   | 100 | Check frequency.....    | 60 | Save new basis map..... | 100   |
| Summary frequency..... | 100 | Factorization frequency | 50 | Expand frequency.....   | 10000 |

QP subproblems

-----

QPsolver Cholesky.....

|                      |       |                         |          |                      |       |
|----------------------|-------|-------------------------|----------|----------------------|-------|
| Scale tolerance..... | 0.900 | Minor feasibility tol.. | 1.00E-06 | Iteration limit..... | 10000 |
|----------------------|-------|-------------------------|----------|----------------------|-------|

|                      |       |                        |          |                         |   |
|----------------------|-------|------------------------|----------|-------------------------|---|
| Scale option.....    | 0     | Minor optimality tol.. | 1.00E-06 | Minor print level.....  | 1 |
| Crash tolerance..... | 0.100 | Pivot tolerance.....   | 2.04E-11 | Partial price.....      | 1 |
| Crash option.....    | 3     | Elastic weight.....    | 1.00E+04 | Prtl price section ( A) | 4 |
|                      |       | New superbasics.....   | 99       | Prtl price section (-I) | 6 |

## The SQP Method

-----

|                         |          |                         |          |                         |          |
|-------------------------|----------|-------------------------|----------|-------------------------|----------|
| Minimize.....           |          | Cold start.....         |          | Proximal Point method.. | 1        |
| Nonlinear objectiv vars | 4        | Objective Row.....      | 6        | Function precision..... | 1.72E-13 |
| Unbounded step size.... | 1.00E+20 | Superbasics limit.....  | 4        | Difference interval.... | 4.15E-07 |
| Unbounded objective.... | 1.00E+15 | Reduced Hessian dim.... | 4        | Central difference int. | 5.57E-05 |
| Major step limit.....   | 2.00E+00 | Derivative linesearch.. |          | Derivative option.....  | 1        |
| Major iterations limit. | 1000     | Linesearch tolerance... | 0.90000  | Verify level.....       | 0        |
| Minor iterations limit. | 500      | Penalty parameter.....  | 0.00E+00 | Major Print Level.....  | 1        |
|                         |          | Major optimality tol... | 2.00E-06 |                         |          |

## Hessian Approximation

-----

|                         |  |                      |          |                        |          |
|-------------------------|--|----------------------|----------|------------------------|----------|
| Full-Memory Hessian.... |  | Hessian updates..... | 99999999 | Hessian frequency..... | 99999999 |
|                         |  |                      |          | Hessian flush.....     | 99999999 |

## Nonlinear constraints

-----

|                         |   |                         |          |                      |          |
|-------------------------|---|-------------------------|----------|----------------------|----------|
| Nonlinear constraints.. | 3 | Major feasibility tol.. | 1.00E-06 | Violation limit..... | 1.00E+06 |
| Nonlinear Jacobian vars | 2 |                         |          |                      |          |

## Miscellaneous

-----

|                         |      |                         |          |                        |    |
|-------------------------|------|-------------------------|----------|------------------------|----|
| LU factor tolerance.... | 3.99 | LU singularity tol..... | 2.04E-11 | Timing level.....      | 0  |
| LU update tolerance.... | 3.99 | LU swap tolerance.....  | 1.03E-04 | Debug level.....       | 0  |
| LU partial pivoting...  |      | eps (machine precision) | 1.11E-16 | System information.... | No |

## Matrix statistics

-----

|                               | Total | Normal              | Free                      | Fixed   | Bounded |
|-------------------------------|-------|---------------------|---------------------------|---------|---------|
| Rows                          | 6     | 2                   | 1                         | 3       | 0       |
| Columns                       | 4     | 0                   | 0                         | 0       | 4       |
| No. of matrix elements        |       |                     | 14                        | Density | 58.333  |
| Biggest                       |       | 1.0000E+00          | (excluding fixed columns, |         |         |
| Smallest                      |       | 0.0000E+00          | free rows, and RHS)       |         |         |
| No. of objective coefficients |       | 2                   |                           |         |         |
| Biggest                       |       | 3.0000E+00          | (excluding fixed columns) |         |         |
| Smallest                      |       | 2.0000E+00          |                           |         |         |
| Nonlinear constraints         | 3     | Linear constraints  |                           | 3       |         |
| Nonlinear variables           | 4     | Linear variables    |                           | 0       |         |
| Jacobian variables            | 2     | Objective variables |                           | 4       |         |
| Total constraints             | 6     | Total variables     |                           | 4       |         |

The user has defined 8 out of 8 first derivatives

Cheap test of user-supplied problem derivatives...

The constraint gradients seem to be OK.

--> The largest discrepancy was 2.20E-08 in constraint 6

The objective gradients seem to be OK.

Gradient projected in one direction 0.0000000000E+00  
 Difference approximation 4.48709939860E-21

| Itns | Major | Minors | Step    | nCon | Feasible  | Optimal   | MeritFunction | L+U | BSwap | nS | condHz  | Penalty |       |
|------|-------|--------|---------|------|-----------|-----------|---------------|-----|-------|----|---------|---------|-------|
| 3    | 0     | 3      |         | 1    | 8.0E+02   | 1.0E+00   | 0.0000000E+00 | 17  |       | 1  | 1.7E+07 |         | _ r   |
| 5    | 1     | 2      | 1.2E-03 | 2    | 4.0E+02   | 9.9E-01   | 9.6317131E+05 | 16  |       | 1  | 4.8E+06 | 2.8E+00 | _n r1 |
| 6    | 2     | 1      | 1.3E-03 | 3    | 2.7E+02   | 5.5E-01   | 9.6122945E+05 | 16  |       |    |         | 2.8E+00 | _s 1  |
| 6    | 3     | 0      | 7.5E-03 | 4    | 8.8E+01   | 5.4E-01   | 9.4691061E+05 | 16  |       |    |         | 2.8E+00 | _ 1   |
| 6    | 4     | 0      | 2.3E-02 | 5    | 2.9E+01   | 5.3E-01   | 9.0468403E+05 | 16  |       |    |         | 2.8E+00 | _ 1   |
| 6    | 5     | 0      | 6.9E-02 | 6    | 8.9E+00   | 5.0E-01   | 7.8452897E+05 | 16  |       |    |         | 2.8E+00 | _ 1   |
| 7    | 6     | 1      | 2.2E-01 | 7    | 2.3E+00   | 5.5E+01   | 4.8112339E+05 | 16  |       | 1  | 8.7E+03 | 2.8E+00 | _ 1   |
| 8    | 7     | 1      | 8.3E-01 | 8    | 1.7E-01   | 4.2E+00   | 2.6898257E+04 | 16  |       | 1  | 7.6E+03 | 2.8E+00 | _ 1   |
| 9    | 8     | 1      | 1.0E+00 | 9    | 1.8E-02   | 8.7E+01   | 6.2192920E+03 | 15  | 1     | 1  | 1.2E+02 | 2.8E+00 | _     |
| 10   | 9     | 1      | 1.0E+00 | 10   | 1.7E-02   | 7.9E+00   | 5.4526185E+03 | 15  |       | 1  | 9.4E+01 | 2.8E+00 | _     |
| 11   | 10    | 1      | 1.0E+00 | 11   | 1.7E-04   | 9.6E-01   | 5.1266089E+03 | 15  |       | 1  | 1.0E+02 | 2.8E+00 | _     |
| 12   | 11    | 1      | 1.0E+00 | 12   | 1.7E-06   | 5.8E-02   | 5.1264988E+03 | 15  |       | 1  | 9.5E+01 | 2.8E+00 | _     |
| 13   | 12    | 1      | 1.0E+00 | 13   | (1.2E-08) | 6.9E-05   | 5.1264981E+03 | 15  |       | 1  | 9.5E+01 | 2.8E+00 | _     |
| 14   | 13    | 1      | 1.0E+00 | 14   | (6.7E-15) | (3.0E-09) | 5.1264981E+03 | 15  |       | 1  | 9.5E+01 | 6.0E+00 | _     |

E04VHU EXIT 0 -- finished successfully

E04VHU INFO 1 -- optimality conditions satisfied

Problem name

|                            |           |                        |                  |
|----------------------------|-----------|------------------------|------------------|
| No. of iterations          | 14        | Objective value        | 5.1264981096E+03 |
| No. of major iterations    | 13        | Linear objective       | 4.0919702248E+03 |
| Penalty parameter          | 6.038E+00 | Nonlinear objective    | 1.0345278848E+03 |
| No. of calls to funobj     | 15        | No. of calls to funcon | 15               |
| No. of superbasics         | 1         | No. of basic nonlinear | 3                |
| No. of degenerate steps    | 0         | Percentage             | 0.00             |
| Max x                      | 4 1.0E+03 | Max pi                 | 3 5.5E+00        |
| Max Primal infeas          | 0 0.0E+00 | Max Dual infeas        | 1 4.6E-08        |
| Nonlinear constraint violn | 5.7E-12   |                        |                  |

Name Objective Value 5.1264981096E+03

Status Optimal Soln Iteration 14 Superbasics 1

Objective (Min)

RHS

Ranges

Bounds

Section 1 - Rows

| Number | ...Row.. | State | ...Activity... | Slack Activity | ..Lower Limit. | ..Upper Limit. | ..Dual Activity | ..i |
|--------|----------|-------|----------------|----------------|----------------|----------------|-----------------|-----|
| 5      | NlnCon 1 | EQ    | -894.80000     | 0.00000        | -894.80000     | -894.80000     | -4.38698        | 1   |
| 6      | NlnCon 2 | EQ    | -894.80000     | 0.00000        | -894.80000     | -894.80000     | -4.10563        | 2   |
| 7      | NlnCon 3 | EQ    | -1294.80000    | 0.00000        | -1294.80000    | -1294.80000    | -5.46328        | 3   |
| 8      | LinCon 1 | BS    | -0.51511       | 0.03489        | -0.55000       | None           | .               | 4   |
| 9      | LinCon 2 | BS    | 0.51511        | 1.06511        | -0.55000       | None           | .               | 5   |
| 10     | Objectiv | BS    | 4091.97022     | 4091.97022     | None           | None           | -1.0            | 6   |

Section 2 - Columns

| Number | .Column. | State | ...Activity... | .Obj Gradient. | ..Lower Limit. | ..Upper Limit. | Reduced Gradnt | m+j |
|--------|----------|-------|----------------|----------------|----------------|----------------|----------------|-----|
| 1      | X1       | BS    | 0.11888        | .              | -0.55000       | 0.55000        | 0.00000        | 7   |
| 2      | X2       | BS    | -0.39623       | .              | -0.55000       | 0.55000        | 0.00000        | 8   |
| 3      | X3       | SBS   | 679.94532      | 4.38698        | .              | 1200.00000     | 0.00000        | 9   |
| 4      | X4       | BS    | 1026.06713     | 4.10563        | .              | 1200.00000     | 0.00000        | 10  |

On exit from E04VHF, IFAIL = 0

Final objective value = 5126.5

Optimal X = 0.12 -0.40 679.95 1026.07

**Note:** the remainder of this document is intended for more advanced users. Section 10 contains a detailed description of the algorithm which may be needed in order to understand Sections 11 and 12. Section 11 describes the optional parameters which may be set by calls to E04VKF, E04VLF, E04VMF and/or E04VNF. Section 12 describes the quantities which can be requested to monitor the course of the computation.

## 10 Algorithmic Details

Here we summarize the main features of the SQP algorithm used in E04VHF and introduce some terminology used in the description of the subroutine and its arguments. The SQP algorithm is fully described in Gill *et al.* (2002).

### 10.1 Constraints and Slack Variables

Problem (1) contains  $n$  variables in  $x$ . Let  $m$  be the number of components of  $f(x)$  and  $A_L x$  combined. The upper and lower bounds on those terms define the *general constraints* of the problem. E04VHF converts the general constraints to equalities by introducing a set of *slack variables*  $s = (s_1, s_2, \dots, s_m)^T$ . For example, the linear constraint  $5 \leq 2x_1 + 3x_2 \leq \infty$  is replaced by  $2x_1 + 3x_2 - s_1 = 0$  together with the bounded slack  $5 \leq s_1 \leq \infty$ . The minimization problem (1) can therefore be written in the equivalent form

$$\underset{x,s}{\text{minimize}} f_0(x) \quad \text{subject to} \quad \begin{pmatrix} f(x) \\ A_L x \end{pmatrix} - s = 0, \quad l \leq \begin{pmatrix} x \\ s \end{pmatrix} \leq u. \quad (3)$$

The general constraints become the equalities  $f(x) - s_N = 0$  and  $A_L x - s_L = 0$ , where  $s_L$  and  $s_N$  are the *linear* and *nonlinear* slacks.

### 10.2 Major Iterations

The basic structure of the SQP algorithm involves *major* and *minor* iterations. The major iterations generate a sequence of iterates  $\{x_k\}$  that satisfy the linear constraints and converge to a point that satisfies the nonlinear constraints and the first-order conditions for optimality. At each iterate  $x_k$  a QP subproblem is used to generate a search direction towards the next iterate  $x_{k+1}$ . The constraints of the subproblem are formed from the linear constraints  $A_L x - s_L = 0$  and the linearized constraint

$$f(x_k) + f'(x_k)(x - x_k) - s_N = 0, \quad (4)$$

where  $f'(x_k)$  denotes the *Jacobian matrix*, whose elements are the first derivatives of  $f(x)$  evaluated at  $x_k$ . The QP constraints therefore comprise the  $m$  linear constraints

$$\begin{aligned} f'(x_k)x - s_N &= -f(x_k) + f'(x_k)x_k, \\ A_L x - s_L &= 0, \end{aligned} \quad (5)$$

where  $x$  and  $s$  are bounded above and below by  $u$  and  $l$  as before. If the  $m$  by  $n$  matrix  $A$  and  $m$ -vector  $b$  are defined as

$$A = \begin{pmatrix} f'(x_k) \\ A_L \end{pmatrix} \quad \text{and} \quad b = \begin{pmatrix} -f(x_k) + f'(x_k)x_k \\ 0 \end{pmatrix}, \quad (6)$$

then the QP subproblem can be written as

$$\underset{x,s}{\text{minimize}} q(x, x_k) = g_k^T(x - x_k) + \frac{1}{2}(x - x_k)^T H_k(x - x_k) \quad \text{subject to} \quad Ax - s = b, \quad l \leq \begin{pmatrix} x \\ s \end{pmatrix} \leq u, \quad (7)$$

where  $q(x, x_k)$  is a quadratic approximation to a modified Lagrangian function (see Gill *et al.* (2002)). The matrix  $H_k$  is a quasi-Newton approximation to the Hessian of the Lagrangian. A BFGS update is applied after each major iteration. If some of the variables enter the Lagrangian linearly the Hessian will have some zero rows and columns. If the nonlinear variables appear first, then only the  $n_1$  rows and columns of the Hessian need to be approximated, where  $n_1$  is the number of nonlinear variables. This quantity is determined by the implicit values of the number of nonlinear objective and Jacobian variables determined after the constraints and variables are reordered.

### 10.3 Minor Iterations

Solving the QP subproblem is itself an iterative procedure. Here, the iterations of the QP solver E04NQF form the *minor* iterations of the SQP method. E04NQF uses a reduced-Hessian active-set method implemented as a reduced-gradient method. At each minor iteration, the constraints  $Ax - s = b$  are partitioned into the form

$$Bx_B + Sx_S + Nx_N = b, \quad (8)$$

where the *basis matrix*  $B$  is square and nonsingular, and the matrices  $S$  and  $N$  are the remaining columns of  $(A \ -I)$ . The vectors  $x_B$ ,  $x_S$  and  $x_N$  are the associated *basic*, *superbasic* and *nonbasic* variables respectively; they are a permutation of the elements of  $x$  and  $s$ . At a QP subproblem, the basic and superbasic variables will lie somewhere between their bounds, while the nonbasic variables will normally be equal to one of their bounds. At each iteration,  $x_S$  is regarded as a set of independent variables that are free to move in any desired direction, namely one that will improve the value of the QP objective (or the sum of infeasibilities). The basic variables are then adjusted in order to ensure that  $(x, s)$  continues to satisfy  $Ax - s = b$ . The number of superbasic variables ( $n_S$ , say) therefore indicates the number of degrees of freedom remaining after the constraints have been satisfied. In broad terms,  $n_S$  is a measure of *how nonlinear* the problem is. In particular,  $n_S$  will always be zero for LP problems.

If it appears that no improvement can be made with the current definition of  $B$ ,  $S$  and  $N$ , a nonbasic variable is selected to be added to  $S$ , and the process is repeated with the value of  $n_S$  increased by one. At all stages, if a basic or superbasic variable encounters one of its bounds, the variable is made nonbasic and the value of  $n_S$  is decreased by one.

Associated with each of the  $m$  equality constraints  $Ax - s = b$  are the *dual variables*  $\pi$ . Similarly, each variable in  $(x, s)$  has an associated *reduced gradient*  $d_j$ . The reduced gradients for the variables  $x$  are the quantities  $g - A^T \pi$ , where  $g$  is the gradient of the QP objective, and the reduced gradients for the slacks are the dual variables  $\pi$ . The QP subproblem is optimal if  $d_j \geq 0$  for all nonbasic variables at their lower bounds,  $d_j \leq 0$  for all nonbasic variables at their upper bounds, and  $d_j = 0$  for other variables, including superbasics. In practice, an *approximate* QP solution  $(\hat{x}_k, \hat{s}_k, \hat{\pi}_k)$  is found by relaxing these conditions.

### 10.4 The Merit Function

After a QP subproblem has been solved, new estimates of the solution are computed using a linesearch on the augmented Lagrangian merit function

$$\mathcal{M}(x, s, \pi) = f_0(x) - \pi^T(f(x) - s_N) + \frac{1}{2}(f(x) - s_N)^T D(f(x) - s_N), \quad (9)$$

where  $D$  is a diagonal matrix of penalty parameters ( $D_{ii} \geq 0$ ), and  $\pi$  now refers to dual variables for the nonlinear constraints in (1). If  $(x_k, s_k, \pi_k)$  denotes the current solution estimate and  $(\hat{x}_k, \hat{s}_k, \hat{\pi}_k)$  denotes the QP solution, the linesearch determines a step  $\alpha_k$  ( $0 < \alpha_k \leq 1$ ) such that the new point

$$\begin{pmatrix} x_{k+1} \\ s_{k+1} \\ \pi_{k+1} \end{pmatrix} = \begin{pmatrix} x_k \\ s_k \\ \pi_k \end{pmatrix} + \alpha_k \begin{pmatrix} \hat{x}_k - x_k \\ \hat{s}_k - s_k \\ \hat{\pi}_k - \pi_k \end{pmatrix} \quad (10)$$

gives a *sufficient decrease* in the merit function  $\mathcal{M}$ . When necessary, the penalties in  $D$  are increased by the minimum-norm perturbation that ensures descent for  $\mathcal{M}$  (see Gill *et al.* (1992)). The value of  $s_N$  is adjusted to minimize the merit function as a function of  $s$  before the solution of the QP subproblem (see Gill *et al.* (1986) and Eldersveld (1991)).

### 10.5 Treatment of Constraint Infeasibilities

E04VHF makes explicit allowance for infeasible constraints. First, infeasible *linear* constraints are detected by solving the linear program

$$\underset{x, v, w}{\text{minimize}} \ e^T(v + w) \quad \text{subject to} \ l \leq \begin{pmatrix} x \\ A_L x - v + w \end{pmatrix} \leq u, \quad v \geq 0, \quad w \geq 0, \quad (11)$$

where  $e$  is a vector of ones, and the nonlinear constraint bounds are temporarily excluded from  $l$  and  $u$ . This is equivalent to minimizing the sum of the general linear constraint violations subject to the bounds

on  $x$ . (The sum is the  $\ell_1$ -norm of the linear constraint violations. In the linear programming literature, the approach is called *elastic programming*.)

The linear constraints are infeasible if the optimal solution of (11) has  $v \neq 0$  or  $w \neq 0$ . E04VHF then terminates without computing the nonlinear functions.

Otherwise, all subsequent iterates satisfy the linear constraints. (Such a strategy allows linear constraints to be used to define a region in which the functions can be safely evaluated.) E04VHF proceeds to solve nonlinear problems as given, using search directions obtained from the sequence of QP subproblems (see (7)).

If a QP subproblem proves to be infeasible or unbounded (or if the dual variables  $\pi$  for the nonlinear constraints become large), E04VHF enters ‘elastic’ mode and thereafter solves the problem

$$\underset{x,v,w}{\text{minimize}} f_0(x) + \gamma e^T(v+w) \quad \text{subject to } l \leq \begin{pmatrix} x \\ f(x) - v + w \\ A_L x \end{pmatrix} \leq u, \quad v \geq 0, \quad w \geq 0, \quad (12)$$

where  $\gamma$  is a non-negative parameter (the *elastic weight*), and  $f_0(x) + \gamma e^T(v+w)$  is called a *composite objective* (the  $\ell_1$  penalty function for the nonlinear constraints).

The value of  $\gamma$  may increase automatically by multiples of 10 if the optimal  $v$  and  $w$  continue to be nonzero. If  $\gamma$  is sufficiently large, this is equivalent to minimizing the sum of the nonlinear constraint violations subject to the linear constraints and bounds.

The initial value of  $\gamma$  is controlled by the optional parameter Elastic Weight.

## 11 Optional Parameters

Several optional parameters in E04VHF define choices in the problem specification or the algorithm logic. In order to reduce the number of formal parameters of E04VHF these optional parameters have associated *default values* that are appropriate for most problems. Therefore, you need only specify those optional parameters whose values are to be different from their default values.

The remainder of this section can be skipped if you wish to use the default values for all optional parameters. A complete list of optional parameters and their default values is given in Section 11.1.

Optional parameters may be specified by calling one, or more, of the routines E04VKF, E04VLF, E04VMF and E04VNF before a call to E04VHF.

E04VKF reads options from an external options file, with `Begin` and `End` as the first and last lines respectively and each intermediate line defining a single optional parameter. For example,

```
Begin
  Print Level = 5
End
```

The call

```
CALL E04VKF (ISPECS, CW, IW, RW, IFAIL)
```

can then be used to read the file on unit ISPECS. IFAIL = 0 on successful exit. E04VKF should be consulted for a full description of this method of supplying optional parameters.

E04VLF, E04VMF and E04VNF can be called to supply options directly, one call being necessary for each optional parameter. For example,

```
CALL E04VLF ('Print Level = 5', CW, IW, RW, IFAIL)
```

E04VLF, E04VMF and E04VNF should be consulted for a full description of this method of supplying optional parameters.

All optional parameters you do not specify are set to their default values. Optional parameters you specify are unaltered by E04VHF (unless they define invalid values) and so remain in effect for subsequent calls to E04VHF, unless you alter them.

## 11.1 Optional Parameter Checklist and Default Values

The following list gives the valid options. For each option, we give the keyword, any essential optional qualifiers and the default value. A definition for each option can be found in Section 11.2, where the minimum abbreviation of each keyword is underlined (if no characters of an optional qualifier are underlined, the qualifier may be omitted), the letter *a* denotes a phrase (character string) that qualifies an option, the letters *i* and *r* denote INTEGER and *double precision* values required with certain options, the number  $\epsilon$  is a generic notation for *machine precision* (see X02AJF), and  $\epsilon_r$  denotes the relative precision of the objective function (see optional parameter Function Precision), and the variable *infband* holds the value of Infinite Bound Size.

| Optional Parameter          | Default Value                                                                   |
|-----------------------------|---------------------------------------------------------------------------------|
| Backup Basis File           | Default = 0. See New Basis File.                                                |
| Central Difference Interval | Default = $\epsilon_r^{\frac{1}{3}}$                                            |
| Check Frequency             | Default = 60                                                                    |
| Crash Option                | Default = 3                                                                     |
| Crash Tolerance             | Default = 0.1. See Crash Option.                                                |
| Defaults                    |                                                                                 |
| Derivative Linesearch       | Default                                                                         |
| Derivative Option           | Default = 1                                                                     |
| Difference Interval         | Default = $\sqrt{\epsilon_r}$                                                   |
| Dump File                   | Default = 0                                                                     |
| Elastic Weight              | Default = $10^4$                                                                |
| Expand Frequency            | Default = 10000                                                                 |
| Factorization Frequency     | Default = 50                                                                    |
| Feasibility Tolerance       | Default = $\max\{10^{-6}, \sqrt{\epsilon}\}$ . See Minor Feasibility Tolerance. |
| Feasible Point              | See Minimize                                                                    |
| Function Precision          | Default = $\epsilon^{0.8}$                                                      |
| Hessian Frequency           | Default = 99999999                                                              |
| Hessian Full Memory         | Default if $n_1 \leq 75$                                                        |
| Hessian Limited Memory      | Default if $n_1 > 75$ . See Hessian Full Memory.                                |
| Hessian Updates             | Default = Hessian Frequency if Hessian Full Memory,<br>10 otherwise             |
| Infinite Bound Size         | Default = $10^{20}$                                                             |
| Insert File                 | Default = 0. See Punch File.                                                    |
| Iterations Limit            | Default = $\max(10000, 10 \max(N, NF))$                                         |
| Linesearch Tolerance        | Default = 0.9                                                                   |
| List                        | See Nolist                                                                      |
| Load File                   | Default = 0. See Dump File.                                                     |
| LU Complete Pivoting        | See LU Partial Pivoting                                                         |
| LU Density Tolerance        | Default = 0.6                                                                   |
| LU Factor Tolerance         | Default = 3.99                                                                  |
| LU Partial Pivoting         | Default                                                                         |
| LU Rook Pivoting            | See LU Partial Pivoting                                                         |
| LU Singularity Tolerance    | Default = $\epsilon^{\frac{2}{3}}$ . See LU Density Tolerance.                  |
| LU Update Tolerance         | Default = 3.99. See LU Factor Tolerance.                                        |
| Major Feasibility Tolerance | Default = $\max(10^{-6}, \sqrt{\epsilon})$                                      |
| Major Iterations Limit      | Default = $\max(1000, 3 \max(n, nf))$                                           |
| Major Optimality Tolerance  | Default = $2 \max(10^{-6}, \sqrt{\epsilon})$                                    |
| Major Print Level           | Default = 000001                                                                |
| Major Step Limit            | Default = 2.0                                                                   |
| Maximize                    | See Minimize                                                                    |
| Minimize                    | Default                                                                         |
| Minor Feasibility Tolerance | Default = $\max(10^{-6}, \sqrt{\epsilon})$                                      |
| Minor Iterations Limit      | Default = 500                                                                   |
| Minor Print Level           | Default = 1                                                                     |
| New Basis File              | Default = 0                                                                     |

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| New Superbasics Limit    | Default = 99                                       |
| Nolist                   | Default                                            |
| Nonderivative Linesearch | See Derivative Linesearch                          |
| Old Basis File           | Default = 0                                        |
| Partial Price            | Default = 1                                        |
| Pivot Tolerance          | Default = $\epsilon^{\frac{2}{3}}$                 |
| Print File               | Default = 0                                        |
| Print Frequency          | Default = 100                                      |
| Proximal Point Method    | Default = 1                                        |
| Punch File               | Default = 0                                        |
| Save Frequency           | Default = 100. See New Basis File.                 |
| Scale Option             | Default = 0                                        |
| Scale Print              | See Scale Option                                   |
| Scale Tolerance          | Default = 0.9. See Scale Option.                   |
| Solution File            | Default = 0                                        |
| Summary File             | Default = 0                                        |
| Summary Frequency        | Default = 100. See Summary File.                   |
| Superbasics Limit        | Default = $n_1$                                    |
| Suppress Parameters      |                                                    |
| System Information No    | Default                                            |
| System Information Yes   | See System Information No                          |
| Timing Level             | Default = 0                                        |
| Unbounded Objective      | Default = 1.0D+15                                  |
| Unbounded Step Size      | Default = <i>infbnd</i> . See Unbounded Objective. |
| Verify Level             | Default = 0                                        |
| Violation Limit          | Default = 1.0D+6                                   |

## 11.2 Description of the Optional Parameters

**Central Difference Interval**  $r$  Default =  $\epsilon_r^{\frac{1}{3}}$

When Derivative Option = 0, the central-difference interval  $r$  is used near an optimal solution to obtain more accurate (but more expensive) estimates of gradients. Twice as many function evaluations are required compared to forward differencing. The interval used for the  $j$ th variable is  $h_j = r(1 + |x_j|)$ . The resulting derivative estimates should be accurate to  $O(r^2)$ , unless the functions are badly scaled.

**Check Frequency**  $i$  Default = 60

Every  $i$ th minor iteration after the most recent basis factorization, a numerical test is made to see if the current solution  $x$  satisfies the general linear constraints (the linear constraints and the linearized nonlinear constraints, if any). The constraints are of the form  $Ax - s = b$ , where  $s$  is the set of slack variables. To perform the numerical test, the residual vector  $r = b - Ax + s$  is computed. If the largest component of  $r$  is judged to be too large, the current basis is refactorized and the basic variables are recomputed to satisfy the general constraints more accurately. If  $i \leq 0$ , the value of  $i = 99999999$  is used and effectively no checks are made.

Check Frequency = 1 is useful for debugging purposes, but otherwise this option should not be needed.

**Crash Option**  $i$  Default = 3  
**Crash Tolerance**  $r$  Default = 0.1

Except on restarts, an internal Crash procedure is used to select an initial basis from certain rows and columns of the constraint matrix  $(A \ -I)$ . The Crash Option  $i$  determines which rows and columns of  $A$  are eligible initially, and how many times the Crash procedure is called. Columns of  $-I$  are used to pad the basis where necessary.

$i$  **Meaning**

0 The initial basis contains only slack variables:  $B = I$ .

1 The Crash procedure is called once, looking for a triangular basis in all rows and columns of  $A$ .

- 2 The Crash procedure is called twice (if there are nonlinear constraints). The first call looks for a triangular basis in linear rows, and the iteration proceeds with simplex iterations until the linear constraints are satisfied. The Jacobian is then evaluated for the first major iteration and the Crash procedure is called again to find a triangular basis in the nonlinear rows (retaining the current basis for linear rows).
- 3 The Crash procedure is called up to three times (if there are nonlinear constraints). The first two calls treat *linear equalities* and *linear inequalities* separately. As before, the last call treats nonlinear rows before the first major iteration.

If  $i \geq 1$ , certain slacks on inequality rows are selected for the basis first. (If  $i \geq 2$ , numerical values are used to exclude slacks that are close to a bound). The Crash procedure then makes several passes through the columns of  $A$ , searching for a basis matrix that is essentially triangular. A column is assigned to ‘pivot’ on a particular row if the column contains a suitably large element in a row that has not yet been assigned. (The pivot elements ultimately form the diagonals of the triangular basis.) For remaining unassigned rows, slack variables are inserted to complete the basis.

The Crash Tolerance  $r$  allows the starting Crash procedure to ignore certain ‘small’ nonzeros in each column of  $A$ . If  $a_{\max}$  is the largest element in column  $j$ , other nonzeros of  $a_{ij}$  in the columns are ignored if  $|a_{ij}| \leq a_{\max} \times r$ . (To be meaningful,  $r$  should be in the range  $0 \leq r < 1$ .)

When  $r > 0.0$ , the basis obtained by the Crash procedure may not be strictly triangular, but it is likely to be nonsingular and almost triangular. The intention is to obtain a starting basis containing more columns of  $A$  and fewer (arbitrary) slacks. A feasible solution may be reached sooner on some problems.

For example, suppose the first  $m$  columns of  $A$  form the matrix shown under LU Factor Tolerance; i.e., a tridiagonal matrix with entries  $-1, 4, -1$ . To help the Crash procedure choose all  $m$  columns for the initial basis, we would specify a Crash Tolerance of  $r$  for some value of  $r > 0.5$ .

### Defaults

This special keyword may be used to reset all optional parameters to their default values.

### Derivative Option

$i$

Default = 1

Optional parameter Derivative Option specifies which nonlinear function gradients are known analytically and will be supplied to E04VHF by USRFUN.

$i$

### **Meaning**

0 Some problem derivatives are unknown.

1 All problem derivatives are known.

The value  $i = 1$  should be used whenever possible. It is the most reliable and will usually be the most efficient.

If  $i = 0$ , E04VHF will *estimate* the missing components of  $G(x)$  using finite differences. This may simplify the coding of USRFUN. However, it could increase the total run-time substantially (since a special call to USRFUN is required for each column of the Jacobian that has a missing element), and there is less assurance that an acceptable solution will be located. If the nonlinear variables are not well scaled, it may be necessary to specify a nonstandard optional parameter Difference Interval.

For each column of the Jacobian, one call to USRFUN is needed to estimate all missing elements in that column, if any.

At times, central differences are used rather than forward differences. Twice as many calls to USRFUN are needed. (This is not under your control.)

### Derivative Linesearch

Default

### Nonderivative Linesearch

At each major iteration a linesearch is used to improve the merit function. Optional parameter Derivative Linesearch uses safeguarded cubic interpolation and requires both function and gradient values to compute estimates of the step  $\alpha_k$ . If some analytic derivatives are not provided, or optional parameter

Nonderivative Linesearch is specified, E04VHF employs a linesearch based upon safeguarded quadratic interpolation, which does not require gradient evaluations.

A nonderivative linesearch can be slightly less robust on difficult problems, and it is recommended that the default be used if the functions and derivatives can be computed at approximately the same cost. If the gradients are very expensive relative to the functions, a nonderivative linesearch may give a significant decrease in computation time.

If Nonderivative Linesearch is selected, E04VHF signals the evaluation of the linesearch by calling USRFUN with NEEDG = 0. Once the linesearch is completed, the problem functions are called again with NEEDF = 0 and NEEDG = 0. If the potential saving provided by a nonderivative linesearch is to be realised, it is essential that USRFUN be coded so that derivatives are not computed when NEEDG = 0.

**Difference Interval**  $r$  Default =  $\sqrt{\epsilon_r}$

This alters the interval  $r$  used to estimate gradients by forward differences. It does so in the following circumstances:

- in the interval ('cheap') phase of verifying the problem derivatives;
- for verifying the problem derivatives;
- for estimating missing derivatives.

In all cases, a derivative with respect to  $x_j$  is estimated by perturbing that component of  $x$  to the value  $x_j + r(1 + |x_j|)$ , and then evaluating  $F_{\text{obj}}(x)$  or  $f(x)$  at the perturbed point. The resulting gradient estimates should be accurate to  $O(r)$  unless the functions are badly scaled. Judicious alteration of  $r$  may sometimes lead to greater accuracy.

**Dump File**  $i_1$  Default = 0  
**Load File**  $i_2$  Default = 0

Optional parameters Dump File and Load File are similar to optional parameters Punch File and Insert File, but they record solution information in a manner that is more direct and more easily modified. A full description of information recorded in optional parameters Dump File and Load File is given in Gill *et al.* (2005a).

If  $i_1 > 0$ , the last solution obtained will be output to the file with unit number  $i_1$ .

If  $i_2 > 0$ , the Load File, containing basis information, will be read. The file will usually have been output previously as a Dump File. The file will not be accessed if optional parameters Old Basis File or Insert File are specified.

**Elastic Weight**  $r$  Default =  $10^4$

This keyword determines the initial weight  $\gamma$  associated with the problem (12) (see Section 10.5).

At major iteration  $k$ , if elastic mode has not yet started, a scale factor  $\sigma_k = 1 + \|g(x_k)\|_\infty$  is defined from the current objective gradient. Elastic mode is then started if the QP subproblem is infeasible, or the QP dual variables are larger in magnitude than  $\sigma_k r$ . The QP is resolved in elastic mode with  $\gamma = \sigma_k r$ .

Thereafter, major iterations continue in elastic mode until they converge to a point that is optimal for (12) (see Section 10.5). If the point is feasible for (1) ( $v = w = 0$ ), it is declared locally optimal. Otherwise,  $\gamma$  is increased by a factor of 10 and major iterations continue. If  $\gamma$  has already reached a maximum allowable value, (1) is declared locally infeasible.

**Expand Frequency**  $i$  Default = 10000

This option is part of the anti-cycling procedure designed to make progress even on highly degenerate problems.

For linear models, the strategy is to force a positive step at every iteration, at the expense of violating the bounds on the variables by a small amount. Suppose that the optional parameter Minor Feasibility Tolerance is  $\delta$ . Over a period of  $i$  iterations, the tolerance actually used by E04VHF increases from  $0.5\delta$  to  $\delta$  (in steps of  $0.5\delta/i$ ).

For nonlinear models, the same procedure is used for iterations in which there is only one superbasic variable. (Cycling can occur only when the current solution is at a vertex of the feasible region.) Thus, zero steps are allowed if there is more than one superbasic variable, but otherwise positive steps are enforced.

Increasing  $i$  helps reduce the number of slightly infeasible nonbasic variables (most of which are eliminated during a resetting procedure). However, it also diminishes the freedom to choose a large pivot element (see optional parameter Pivot Tolerance).

### **Factorization Frequency**

 $i$ 

Default = 50

At most  $i$  basis changes will occur between factorizations of the basis matrix.

With linear programs, the basis factors are usually updated every iteration. The default  $i$  is reasonable for typical problems. Higher values up to  $i = 100$  (say) may be more efficient on well-scaled problems.

When the objective function is nonlinear, fewer basis updates will occur as an optimum is approached. The number of iterations between basis factorizations will therefore increase. During these iterations a test is made regularly (according to the optional parameter Check Frequency) to ensure that the general constraints are satisfied. If necessary the basis will be refactorized before the limit of  $i$  updates is reached.

### **Function Precision**

 $r$ Default =  $\epsilon^{0.8}$ 

The *relative function precision*  $\epsilon_r$  is intended to be a measure of the relative accuracy with which the nonlinear functions can be computed. For example, if  $f(x)$  is computed as 1000.56789 for some relevant  $x$  and if the first 6 significant digits are known to be correct, the appropriate value for  $\epsilon_r$  would be 1.0D-6.

Ideally the functions  $f_i(x)$  should have magnitude of order 1. If all functions are substantially *less* than 1 in magnitude,  $\epsilon_r$  should be the *absolute* precision. For example, if  $f(x) = 1.23456789\text{D}-4$  at some point and if the first 6 significant digits are known to be correct, the appropriate value for  $\epsilon_r$  would be 1.0D-10.)

The default value of  $\epsilon_r$  is appropriate for simple analytic functions.

In some cases the function values will be the result of extensive computation, possibly involving a costly iterative procedure that can provide few digits of precision. Specifying an appropriate Function Precision may lead to savings, by allowing the linesearch procedure to terminate when the difference between function values along the search direction becomes as small as the absolute error in the values.

### **Hessian Full Memory**

Default if  $n_1 \leq 75$ 

### **Hessian Limited Memory**

Default if  $n_1 > 75$ 

These options select the method for storing and updating the approximate Hessian. (E04VHF uses a quasi-Newton approximation to the Hessian of the Lagrangian. A BFGS update is applied after each major iteration.)

If Hessian Full Memory is specified, the approximate Hessian is treated as a dense matrix and the BFGS updates are applied explicitly. This option is most efficient when the number of variables  $n$  is not too large (say, less than 75). In this case, the storage requirement is fixed and one can expect 1-step Q-superlinear convergence to the solution.

Hessian Limited Memory should be used on problems where  $n$  is very large. In this case a limited-memory procedure is used to update a diagonal Hessian approximation  $H_r$  a limited number of times. (Updates are accumulated as a list of vector pairs. They are discarded at regular intervals after  $H_r$  has been reset to their diagonal.)

### **Hessian Frequency**

 $i$ 

Default = 99999999

If optional parameter Hessian Full Memory is selected and  $i$  BFGS updates have already been carried out, the Hessian approximation is reset to the identity matrix. (For certain problems, occasional resets may improve convergence, but in general they should not be necessary.)

Hessian Full Memory and Hessian Frequency = 10 have a similar effect to Hessian Limited Memory and Hessian Updates = 10 (except that the latter retains the current diagonal during resets).

**Hessian Updates** $i$ Default = Hessian Frequency if  
Hessian Full Memory, 10 otherwise

If optional parameter Hessian Limited Memory is selected and  $i$  BFGS updates have already been carried out, all but the diagonal elements of the accumulated updates are discarded and the updating process starts again.

Broadly speaking, the more updates stored, the better the quality of the approximate Hessian. However, the more vectors stored, the greater the cost of each QP iteration. The default value is likely to give a robust algorithm without significant expense, but faster convergence can sometimes be obtained with significantly fewer updates (e.g.,  $i = 5$ ).

**Infinite Bound Size** $r$ Default =  $10^{20}$ 

If  $r \geq 0$ ,  $r$  defines the ‘infinite’ bound  $infbnd$  in the definition of the problem constraints. Any upper bound greater than or equal to  $infbnd$  will be regarded as  $+\infty$  (and similarly any lower bound less than or equal to  $-infbnd$  will be regarded as  $-\infty$ ). If  $r < 0$ , the default value is used.

**Iterations Limit** $i$ Default =  $\max(10000, 10 \max(N, NF))$ 

The value of  $i$  specifies the maximum number of minor iterations allowed (i.e., iterations of the simplex method or the QP algorithm), summed over all major iterations. (See also the description of the optional parameter Minor Iterations Limit.)

**Linesearch Tolerance** $r$ 

Default = 0.9

This tolerance,  $r$ , controls the accuracy with which a step length will be located along the direction of search each iteration. At the start of each linesearch a target directional derivative for the merit function is identified. This parameter determines the accuracy to which this target value is approximated, and it must be a value in the range  $0.0 \leq r \leq 1.0$ .

The default value  $r = 0.9$  requests just moderate accuracy in the linesearch.

If the nonlinear functions are cheap to evaluate, a more accurate search may be appropriate; try  $r = 0.1$ , 0.01 or 0.001.

If the nonlinear functions are expensive to evaluate, a less accurate search may be appropriate. *If all gradients are known*, try  $r = 0.99$ . (The number of major iterations might increase, but the total number of function evaluations may decrease enough to compensate.)

If not all gradients are known, a moderately accurate search remains appropriate. Each search will require only 1–5 function values (typically), but many function calls will then be needed to estimate missing gradients for the next iteration.

**LU Density Tolerance** $r_1$ 

Default = 0.6

**LU Singularity Tolerance** $r_2$ Default =  $\epsilon^2$ 

The density tolerance,  $r_1$ , is used during  $LU$  factorization of the basis matrix. Columns of  $L$  and rows of  $U$  are formed one at a time, and the remaining rows and columns of the basis are altered appropriately. At any stage, if the density of the remaining matrix exceeds  $r_1$ , the Markowitz strategy for choosing pivots is terminated, and the remaining matrix is factored by a dense  $LU$  procedure. Raising the density tolerance towards 1.0 may give slightly sparser  $LU$  factors, with a slight increase in factorization time.

The singularity tolerance,  $r_2$ , helps guard against ill-conditioned basis matrices. After  $B$  is refactorized, the diagonal elements of  $U$  are tested as follows: if  $|u_{jj}| \leq r_2$  or  $|u_{jj}| < r_2 \max_i |u_{ij}|$ , the  $j$ th column of the basis is replaced by the corresponding slack variable. (This is most likely to occur after a restart.)

**LU Factor Tolerance** $r_1$ 

Default = 3.99

**LU Update Tolerance** $r_2$ 

Default = 3.99

The values of  $r_1$  and  $r_2$  affect the stability of the basis factorization  $B = LU$ , during refactorization and updates respectively. The lower triangular matrix  $L$  is a product of matrices of the form

$$\begin{pmatrix} 1 & \\ \mu & 1 \end{pmatrix}$$

where the multipliers  $\mu$  will satisfy  $|\mu| \leq r_i$ . The default values of  $r_1$  and  $r_2$  usually strike a good compromise between stability and sparsity. They must satisfy  $r_1, r_2 \geq 1.0$ .

For large and relatively dense problems,  $r_1 = 10.0$  or  $5.0$  (say) may give a useful improvement in stability without impairing sparsity to a serious degree.

For certain very regular structures (e.g., band matrices) it may be necessary to reduce  $r_1$  and/or  $r_2$  in order to achieve stability. For example, if the columns of  $A$  include a sub-matrix of the form

$$\begin{pmatrix} 4 & -1 & & & \\ -1 & 4 & -1 & & \\ & -1 & 4 & -1 & \\ & & \cdots & \cdots & \cdots \\ & & & -1 & 4 & -1 \\ & & & & -1 & 4 \end{pmatrix},$$

one should set both  $r_1$  and  $r_2$  to values in the range  $1.0 \leq r_i < 4.0$ .

#### **LU Partial Pivoting**

Default

#### **LU Complete Pivoting**

#### **LU Rook Pivoting**

The  $LU$  factorization implements a Markowitz-type search for pivots that locally minimize the fill-in subject to a threshold pivoting stability criterion. The default option is to use threshold partial pivoting. The optional parameters LU Rook Pivoting and LU Complete Pivoting are more expensive than partial pivoting but are more stable and better at revealing rank, as long as LU Factor Tolerance is not too large (say  $< 2.0$ ). When numerical difficulties are encountered, E04VHF automatically reduces the  $LU$  tolerance towards 1.0 and switches (if necessary) to rook or complete pivoting, before reverting to the default or specified options at the next refactorization (with System Information Yes, relevant messages are output to the Print File).

#### **Major Feasibility Tolerance**

 $r$ Default =  $\max(10^{-6}, \sqrt{\epsilon})$ 

This tolerance,  $r$ , specifies how accurately the nonlinear constraints should be satisfied. The default value is appropriate when the linear and nonlinear constraints contain data to about that accuracy.

Let  $v_{\max}$  be the maximum nonlinear constraint violation, normalized by the size of the solution, which is required to satisfy

$$v_{\max} = \max_i v_i / \|x\| \leq r, \quad (13)$$

where  $v_i$  is the violation of the  $i$ th nonlinear constraint, for  $i = 1, 2, \dots, \text{NF}$ .

In the major iteration log (see Section 12.2),  $v_{\max}$  appears as the quantity labelled ‘Feasible’. If some of the problem functions are known to be of low accuracy, a larger Major Feasibility Tolerance may be appropriate.

#### **Major Optimality Tolerance**

 $r$ Default =  $2 \max(10^{-6}, \sqrt{\epsilon})$ 

This tolerance,  $r$ , specifies the final accuracy of the dual variables. On successful termination, E04VHF will have computed a solution  $(x, s, \pi)$  such that

$$c_{\max} = \max_j c_j / \|\pi\| \leq r, \quad (14)$$

where  $c_j$  is an estimate of the complementarity slackness for variable  $j$ , for  $j = 1, 2, \dots, n + \text{nf}$ . The values  $c_i$  are computed from the final QP solution using the reduced gradients  $d_j = g_j - \pi^T a_j$  (where  $g_j$  is the  $j$ th component of the objective gradient,  $a_j$  is the associated column of the constraint matrix  $(A \ -I)$ , and  $\pi$  is the set of QP dual variables):

$$c_j = \begin{cases} d_j \min(x_j - l_j, 1) & \text{if } d_j \geq 0; \\ -d_j \min(u_j - x_j, 1) & \text{if } d_j < 0. \end{cases} \quad (15)$$

In the Print File,  $c_{\max}$  appears as the quantity labelled ‘Optimal’.

**Major Iterations Limit**  $i$  Default =  $\max(1000, 3 \max(n, nf))$

This is the maximum number of major iterations allowed. It is intended to guard against an excessive number of linearizations of the constraints. If  $i = 0$ , optimality and feasibility are checked.

**Major Print Level**  $i$  Default = 000001

This controls the amount of output to the optional parameters Print File and Summary File at each major iteration. Major Print Level = 0 suppresses most output, except for error messages. Major Print Level = 1 gives normal output for linear and nonlinear problems, and Major Print Level = 11 gives additional details of the Jacobian factorization that commences each major iteration.

In general, the value being specified may be thought of as a binary number of the form

Major Print Level  $JFDXbs$

where each letter stands for a digit that is either 0 or 1 as follows:

- $s$  a single line that gives a summary of each major iteration. (This entry in  $JFDXbs$  is not strictly binary since the summary line is printed whenever  $JFDXbs \geq 1$ );
- $b$  basis statistics, i.e., information relating to the basis matrix whenever it is refactorized. (This output is always provided if  $JFDXbs \geq 10$ );
- $X$   $x_k$ , the nonlinear variables involved in the objective function or the constraints. These appear under the heading ‘Jacobian variables’;
- $D$   $\pi_k$ , the dual variables for the nonlinear constraints. These appear under the heading ‘Multiplier estimates’;
- $F$   $f(x_k)$ , the values of the nonlinear constraint functions;
- $J$   $J(x_k)$ , the Jacobian matrix. This appears under the heading ‘ $x$  and Jacobian’.

To obtain output of any items  $JFDXbs$ , set the corresponding digit to 1, otherwise to 0.

If  $J = 1$ , the Jacobian matrix will be output column-wise at the start of each major iteration. Column  $j$  will be preceded by the value of the corresponding variable  $x_j$  and a key to indicate whether the variable is basic, superbasic or nonbasic. (Hence if  $J = 1$ , there is no reason to specify  $X = 1$  unless the objective contains more nonlinear variables than the Jacobian.) A typical line of output is

3 1.250000D+01 BS 1 1.000000D+00 4 2.000000D+00

which would mean that  $x_3$  is basic at value 12.5, and the third column of the Jacobian has elements of 1.0 and 2.0 in rows 1 and 4.

**Major Step Limit**  $r$  Default = 2.0

This parameter limits the change in  $x$  during a linesearch. It applies to all nonlinear problems, once a ‘feasible solution’ or ‘feasible subproblem’ has been found.

1. A linesearch determines a step  $\alpha$  over the range  $0 < \alpha \leq \beta$ , where  $\beta$  is 1 if there are nonlinear constraints or is the step to the nearest upper or lower bound on  $x$  if all the constraints are linear. Normally, the first step length tried is  $\alpha_1 = \min(1, \beta)$ .
2. In some cases, such as  $f(x) = ae^{bx}$  or  $f(x) = ax^b$ , even a moderate change in the components of  $x$  can lead to floating-point overflow. The parameter  $r$  is therefore used to define a limit  $\bar{\beta} = r(1 + \|x\|)/\|p\|$  (where  $p$  is the search direction), and the first evaluation of  $f(x)$  is at the potentially smaller step length  $\alpha_1 = \min(1, \bar{\beta}, \beta)$ .

3. Wherever possible, upper and lower bounds on  $x$  should be used to prevent evaluation of nonlinear functions at meaningless points. The optional parameter Major Step Limit provides an additional safeguard. The default value  $r = 2.0$  should not affect progress on well behaved problems, but setting  $r = 0.1$  or  $0.01$  may be helpful when rapidly varying functions are present. A ‘good’ starting point may be required. An important application is to the class of nonlinear least-squares problems.
4. In cases where several local optima exist, specifying a small value for  $r$  may help locate an optimum near the starting point.

**Minimize**

Default

**Maximize****Feasible Point**

The keywords Minimize and Maximize specify the required direction of optimization. It applies to both linear and nonlinear terms in the objective.

The keyword Feasible Point means ‘Ignore the objective function, while finding a feasible point for the linear and nonlinear constraints’. It can be used to check that the nonlinear constraints are feasible without altering the call to E04VHF.

**Minor Feasibility Tolerance** $r$ Default =  $\max(10^{-6}, \sqrt{\epsilon})$ **Feasibility Tolerance** $r$ Default =  $\max\{10^{-6}, \sqrt{\epsilon}\}$ 

E04VHF tries to ensure that all variables eventually satisfy their upper and lower bounds to within this tolerance,  $r$ . This includes slack variables. Hence, general linear constraints should also be satisfied to within  $r$ .

Feasibility with respect to nonlinear constraints is judged by the optional parameter Major Feasibility Tolerance (not by  $r$ ).

If the bounds and linear constraints cannot be satisfied to within  $r$ , the problem is declared *infeasible*. If SINF is quite small, it may be appropriate to raise  $r$  by a factor of 10 or 100. Otherwise, some error in the data should be suspected.

Nonlinear functions will be evaluated only at points that satisfy the bounds and linear constraints. If there are regions where a function is undefined, every attempt should be made to eliminate these regions from the problem.

For example, if  $f(x) = \sqrt{x_1} + \log(x_2)$ , it is essential to place lower bounds on both variables. If  $r = 1.0D-6$ , the bounds  $x_1 \geq 10^{-5}$  and  $x_2 \geq 10^{-4}$  might be appropriate. (The log singularity is more serious. In general, keep  $x$  as far away from singularities as possible.)

If Scale Option  $\geq 1$ , feasibility is defined in terms of the *scaled* problem (since it is then more likely to be meaningful).

In reality, E04VHF uses  $r$  as a feasibility tolerance for satisfying the bounds on  $x$  and  $s$  in each QP subproblem. If the sum of infeasibilities cannot be reduced to zero, the QP subproblem is declared infeasible. E04VHF is then in *elastic mode* thereafter (with only the linearized nonlinear constraints defined to be elastic). See the description of the optional parameter Elastic Weight.

**Minor Iterations Limit** $i$ 

Default = 500

If the number of minor iterations for the optimality phase of the QP subproblem exceeds  $i$ , then all nonbasic QP variables that have not yet moved are frozen at their current values and the reduced QP is solved to optimality.

Note that more than  $i$  minor iterations may be necessary to solve the reduced QP to optimality. These extra iterations are necessary to ensure that the terminated point gives a suitable direction for the linesearch.

In the major iteration log (see Section 12.2) a  $\tau$  at the end of a line indicates that the corresponding QP was artificially terminated using the limit  $i$ .

Compare with the optional parameter Iterations Limit, which defines an independent *absolute* limit on the *total* number of minor iterations (summed over all QP subproblems).

**Minor Print Level** $i$ 

Default = 1

This controls the amount of output to the Print File and Summary File during solution of the QP subproblems. The value of  $i$  has the following effect:

| $i$       | Meaning                                                                                                                                                                                                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0         | No minor iteration output except error messages.                                                                                                                                                                                                                               |
| $\geq 1$  | A single line of output at each minor iteration (controlled by optional parameters Print Frequency and Summary Frequency).                                                                                                                                                     |
| $\geq 10$ | Basis factorization statistics generated during the periodic refactorization of the basis (see the optional parameter Factorization Frequency). Statistics for the <i>first factorization</i> each major iteration are controlled by the optional parameter Major Print Level. |

**New Basis File** $i_1$ 

Default = 0

**Backup Basis File** $i_2$ 

Default = 0

**Save Frequency** $i_3$ 

Default = 100

New Basis File and Backup Basis File are sometimes referred to as basis maps. They contain the most compact representation of the state of each variable. They are intended for restarting the solution of a problem at a point that was reached by an earlier run. For nontrivial problems, it is advisable to save basis maps at the end of a run, in order to restart the run if necessary.

If  $i_1 > 0$ , a basis map will be saved in the file associated with unit  $i_1$  every  $i_3$ th iteration. The first record of the file will contain the word PROCEEDING if the run is still in progress. A basis map will also be saved at the end of a run, with some other word indicating the final solution status.

Use of  $i_2 > 0$  is intended as a safeguard against losing the results of a long run. Suppose that a New Basis File is being saved every 100 (Save Frequency) iterations, and that E04VHF is about to save such a basis at iteration 2000. It is conceivable that the run may be interrupted during the next few milliseconds (in the middle of the save). In this case the Basis file will be corrupted and the run will have been essentially wasted.

To eliminate this risk, both a New Basis File and a Backup Basis File may be specified. The following would be suitable for the above example:

```
Backup Basis File 11
New Basis File 12
```

The current basis will then be saved every 100 iterations, first in the file associated with unit 12 and then immediately in the file associated with unit 11. If the run is interrupted at iteration 2000 during the save in the file associated with unit 12, there will still be a usable basis in the file associated with unit 11 (corresponding to iteration 1900).

Note that a new basis will be saved in New Basis File at the end of a run if it terminates normally, but it will not be saved in Backup Basis File. In the above example, if an optimum solution is found at iteration 2050 (or if the iteration limit is 2050), the final basis in the file associated with unit 12 will correspond to iteration 2050, but the last basis saved in the file associated with unit 11 will be the one for iteration 2000.

A full description of information recorded in New Basis File and Backup Basis File is given in Gill *et al.* (2005a).

**New Superbasics Limit** $i$ 

Default = 99

This option causes early termination of the QP subproblems if the number of free variables has increased significantly since the first feasible point. If the number of new superbasics is greater than  $i$ , the nonbasic variables that have not yet moved are frozen and the resulting smaller QP is solved to optimality.

In the major iteration log (see Section 12.1), a  $\tau$  at the end of a line indicates that the QP was terminated early in this way.

**Nolist**  
**List**

Default

For E04VHF, normally each optional parameter specification is printed as it is supplied. Optional parameter Nolist may be used to suppress the printing and optional parameter List may be used to turn on printing.

**Old Basis File** $i$ 

Default = 0

If  $i > 0$ , the basis maps information will be obtained from this file. The file will usually have been output previously as a New Basis File or Backup Basis File. A full description of information recorded in New Basis File and Backup Basis File is given in Gill *et al.* (2005a).

The file will not be acceptable if the number of rows or columns in the problem has been altered.

**Partial Price** $i$ 

Default = 1

This parameter is recommended for large problems that have significantly more variables than constraints. It reduces the work required for each ‘pricing’ operation (where a nonbasic variable is selected to become superbasic). When  $i = 1$ , all columns of the constraint matrix ( $A \ -I$ ) are searched. Otherwise,  $A$  and  $I$  are partitioned to give  $i$  roughly equal segments  $A_j$  and  $I_j$ , for  $j = 1, 2, \dots, i$ . If the previous pricing search was successful on  $A_{j-1}$  and  $I_{j-1}$ , the next search begins on the segments  $A_j$  and  $I_j$ . (All subscripts here are modulo  $i$ .) If a reduced gradient is found that is larger than some dynamic tolerance, the variable with the largest such reduced gradient (of appropriate sign) is selected to become superbasic. If nothing is found, the search continues on the next segments  $A_{j+1}$  and  $I_{j+1}$ , and so on.

For time-stage models having  $r$  time periods, Partial Price  $r$  (or  $r/2$  or  $r/3$ ) may be appropriate.

**Pivot Tolerance** $r$ Default =  $\epsilon^{\frac{2}{3}}$ 

During the solution of QP subproblems, the pivot tolerance is used to prevent columns entering the basis if they would cause the basis to become almost singular.

When  $x$  changes to  $x + \alpha p$  for some search direction  $p$ , a ‘ratio test’ determines which component of  $x$  reaches an upper or lower bound first. The corresponding element of  $p$  is called the pivot element. Elements of  $p$  are ignored (and therefore cannot be pivot elements) if they are smaller than the pivot tolerance  $r$ .

It is common for two or more variables to reach a bound at essentially the same time. In such cases, the Minor Feasibility Tolerance (say,  $t$ ) provides some freedom to maximize the pivot element and thereby improve numerical stability. Excessively small values of  $t$  should therefore not be specified. To a lesser extent, the Expand Frequency (say,  $f$ ) also provides some freedom to maximize the pivot element. Excessively large values of  $f$  should therefore not be specified.

**Print File** $i$ 

Default = 0

If  $i > 0$ , the following information is output to a file associated with unit  $i$  during the solution of each problem:

- a listing of the optional parameters;
- some statistics about the problem;
- the amount of storage available for the  $LU$  factorization of the basis matrix;
- notes about the initial basis resulting from a Crash procedure or a Basis file;
- the iteration log;
- basis factorization statistics;
- the exit IFAIL condition and some statistics about the solution obtained;
- the printed solution, if requested.

These items are described in Sections 8 and 12. Further brief output may be directed to the Summary File.

**Print Frequency**  $i$  Default = 100

If  $i > 0$ , one line of the iteration log will be printed every  $i$ th iteration. A value such as  $i = 10$  is suggested for those interested only in the final solution. If  $i \leq 0$ , the value of  $i = 99999999$  is used and effectively no checks are made.

**Proximal Point Method**  $i$  Default = 1

$i = 1$  or  $2$  specifies minimization of  $\|x - x_0\|_1$  or  $\frac{1}{2}\|x - x_0\|_2^2$  when the starting point  $x_0$  is changed to satisfy the linear constraints (where  $x_0$  refers to nonlinear variables).

**Punch File**  $i_1$  Default = 0  
**Insert File**  $i_2$  Default = 0

The Punch File from a previous run may be used as an Insert File for a later run on the same problem. A full description of information recorded in Insert File and Punch File is given in Gill *et al.* (2005a).

If  $i_1 > 0$ , the final solution obtained will be output to the file. For linear programs, this format is compatible with various commercial systems.

If  $i_2 > 0$  the Insert File containing basis information will be read from unit  $i_2$ . The file will usually have been output previously as a Punch File. The file will not be accessed if Old Basis File is specified.

**Scale Option**  $i$  Default = 0  
**Scale Tolerance**  $r$  Default = 0.9  
**Scale Print**

Three scale options are available as follows:

- | $i$ | Meaning                                                                                                                                                                                                                                                                                                                |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0   | No scaling. This is recommended if it is known that $x$ and the constraint matrix never have very large elements (say, larger than 100).                                                                                                                                                                               |
| 1   | The constraints and variables are scaled by an iterative procedure that attempts to make the matrix coefficients as close as possible to 1.0 (see Fourer (1982)). This will sometimes improve the performance of the solution procedures.                                                                              |
| 2   | The constraints and variables are scaled by the iterative procedure. Also, a certain additional scaling is performed that may be helpful if the right-hand side $b$ or the solution $x$ is large. This takes into account columns of $(A \ -I)$ that are fixed or have positive lower bounds or negative upper bounds. |

Optional parameter Scale Tolerance affects how many passes might be needed through the constraint matrix. On each pass, the scaling procedure computes the ratio of the largest and smallest nonzero coefficients in each column:

$$\rho_j = \max_j |a_{ij}| / \min_i |a_{ij}| \quad (a_{ij} \neq 0).$$

If  $\max_j \rho_j$  is less than  $r$  times its previous value, another scaling pass is performed to adjust the row and column scales. Raising  $r$  from 0.9 to 0.99 (say) usually increases the number of scaling passes through  $A$ . At most 10 passes are made. The value of  $r$  should lie in the range  $0 < r < 1$ .

Scale Print causes the row scales  $r(i)$  and column scales  $c(j)$  to be printed to Print File, if System Information Yes has been specified. The scaled matrix coefficients are  $\bar{a}_{ij} = a_{ij}c(j)/r(i)$ , and the scaled bounds on the variables and slacks are  $\bar{l}_j = l_j/c(j)$ ,  $\bar{u}_j = u_j/c(j)$ , where  $c(j) = r(j - n)$  if  $j > n$ .

**Solution File**  $i$  Default = 0

If  $i > 0$ , the final solution will be output to file  $i$  (whether optimal or not). All numbers are printed in 1pe16.6 format.

To see more significant digits in the printed solution, it will sometimes be useful to make  $i$  refer to Print File.

**Summary File** $i_1$ 

Default = 0

**Summary Frequency** $i_2$ 

Default = 100

If  $i_1 > 0$ , a brief log will be output to the file associated with unit  $i_1$ , including one line of information every  $i_2$ th iteration. In an interactive environment, it is useful to direct this output to the terminal, to allow a run to be monitored online. (If something looks wrong, the run can be manually terminated.) Further details are given in Section 12.6.

**Superbasics Limit** $i$ Default =  $n_1$ 

This option places a limit on the storage allocated for superbasic variables. Ideally,  $i$  should be set slightly larger than the ‘number of degrees of freedom’ expected at an optimal solution.

For nonlinear problems, the number of degrees of freedom is often called the ‘number of independent variables’. Normally,  $i$  need not be greater than  $n + 1$ , where  $n_1$  is the number of nonlinear variables. For many problems,  $i$  may be considerably smaller than  $n$ . This will save storage if  $n$  is very large.

**Suppress Parameters**

Normally E04VHF prints the options file as it is being read, and then prints a complete list of the available keywords and their final values. The optional parameter Suppress Parameters tells E04VHF not to print the full list.

**System Information No**

Default

**System Information Yes**

This option prints additional information on the progress of major and minor iterations, and Crash statistics. See Section 12.

**Timing Level** $i$ 

Default = 0

If  $i > 0$ , some timing information will be output to the Print file, if Print File  $> 0$ .

**Unbounded Objective** $r_1$ 

Default = 1.0D+15

**Unbounded Step Size** $r_2$ Default = *inf*bnd

These parameters are intended to detect unboundedness in nonlinear problems. During a linesearch,  $F_{\text{obj}}$  is evaluated at points of the form  $x + \alpha p$ , where  $x$  and  $p$  are fixed and  $\alpha$  varies. If  $|F_{\text{obj}}|$  exceeds  $r_1$  or  $\alpha$  exceeds  $r_2$ , iterations are terminated with the exit message IFAIL = 5.

If singularities are present, unboundedness in  $F_{\text{obj}}(x)$  may be manifested by a floating-point overflow (during the evaluation of  $F_{\text{obj}}(x + \alpha p)$ ), before the test against  $r_1$  can be made.

Unboundedness in  $x$  is best avoided by placing finite upper and lower bounds on the variables.

**Verify Level** $i$ 

Default = 0

This option refers to finite-difference checks on the derivatives computed by the user-supplied routines. Derivatives are checked at the first point that satisfies all bounds and linear constraints.

 $i$ **Meaning**

- 0 Only a ‘cheap’ test will be performed, requiring two calls to USRFUN.
- 1 Individual gradients will be checked (with a more reliable test). A key of the form OK or Bad? indicates whether or not each component appears to be correct.
- 2 Individual columns of the problem Jacobian will be checked.
- 3 Options 2 and 1 will both occur (in that order).
- −1 Derivative checking is disabled.

Verify Level = 3 should be specified whenever a new USRFUN is being developed.

**Violation Limit** $r$ 

Default = 1.0D+6

This keyword defines an absolute limit on the magnitude of the maximum constraint violation,  $r$ , after the linesearch. On completion of the linesearch, the new iterate  $x_{k+1}$  satisfies the condition

$$v_i(x_{k+1}) \leq r \max(1, v_i(x_0)),$$

where  $x_0$  is the point at which the nonlinear constraints are first evaluated and  $v_i(x)$  is the  $i$ th nonlinear constraint violation  $v_i(x) = \max(0, l_i - f_i(x), f_i(x) - u_i)$ .

The effect of this violation limit is to restrict the iterates to lie in an *expanded* feasible region whose size depends on the magnitude of  $r$ . This makes it possible to keep the iterates within a region where the objective is expected to be well-defined and bounded below. If the objective is bounded below for all values of the variables, then  $r$  may be any large positive value.

## 12 Description of Monitoring Information

E04VHF produces monitoring information, statistical information and information about the solution. Section 8.1 contains details of the final output information sent to the unit specified by the optional parameter Print File. This section contains other details of output information.

### 12.1 Major Iteration Log

This section describes the output to unit Print File if Major Print Level > 0. One line of information is output every  $k$ th major iteration, where  $k$  is Print Frequency.

| Label         | Description                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Itns          | is the cumulative number of minor iterations.                                                                                                                                                                                                                                                                                                                                                                                                    |
| Major         | is the current major iteration number.                                                                                                                                                                                                                                                                                                                                                                                                           |
| Minors        | is the number of iterations required by both the feasibility and optimality phases of the QP subproblem. Generally, Minors will be 1 in the later iterations, since theoretical analysis predicts that the correct active set will be identified near the solution (see Section 10).                                                                                                                                                             |
| Step          | is the step length $\alpha$ taken along the current search direction $p$ . The variables $x$ have just been changed to $x + \alpha p$ . On reasonably well-behaved problems, the unit step will be taken as the solution is approached.                                                                                                                                                                                                          |
| nCon          | the number of times USRFUN has been called to evaluate the nonlinear problem functions. Evaluations needed for the estimation of the derivatives by finite differences are not included. nCon is printed as a guide to the amount of work required for the linesearch.                                                                                                                                                                           |
| Feasible      | is the value of $v_{\max}$ (see (13)), the maximum component of the scaled nonlinear constraint residual (see optional parameter Major Feasibility Tolerance). The solution is regarded as acceptably feasible if Feasible is less than the Major Feasibility Tolerance. In this case, the entry is contained in parentheses.<br><br>If the constraints are linear, all iterates are feasible and this entry is not printed.                     |
| Optimal       | is the value of $c_{\max}$ (see (14)), the maximum complementary gap (see optional parameter Major Optimality Tolerance). It is an estimate of the degree of nonoptimality of the reduced costs. Both Feasible and Optimal are small in the neighbourhood of a solution.                                                                                                                                                                         |
| MeritFunction | is the value of the augmented Lagrangian merit function (see (8)). This function will decrease at each iteration unless it was necessary to increase the penalty parameters (see Section 10.4). As the solution is approached, MeritFunction will converge to the value of the objective at the solution.<br><br>In elastic mode, the merit function is a composite function involving the constraint violations weighted by the elastic weight. |

|         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|         | <p>If the constraints are linear, this item is labelled <b>Objective</b>, the value of the objective function. It will decrease monotonically to its optimal value.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| L+U     | <p>is the number of nonzeros representing the basis factors <math>L</math> and <math>U</math> on completion of the QP subproblem.</p> <p>If nonlinear constraints are present, the basis factorization <math>B = LU</math> is computed at the start of the first minor iteration. At this stage, <math>L+U = \text{lenL} + \text{lenU}</math>, where <math>\text{lenL}</math> (see Section 12.4) is the number of subdiagonal elements in the columns of a lower triangular matrix and <math>\text{lenU}</math> (see Section 12.4) is the number of diagonal and superdiagonal elements in the rows of an upper-triangular matrix.</p> <p>As columns of <math>B</math> are replaced during the minor iterations, <math>L+U</math> may fluctuate up or down but, in general, will tend to increase. As the solution is approached and the minor iterations decrease towards zero, <math>L+U</math> will reflect the number of nonzeros in the <math>LU</math> factors at the start of the QP subproblem.</p> <p>If the constraints are linear, refactorization is subject only to the Factorization Frequency, and <math>L+U</math> will tend to increase between factorizations.</p>               |
| BSwap   | <p>is the number of columns of the basis matrix <math>B</math> that were swapped with columns of <math>S</math> to improve the condition of <math>B</math>. The swaps are determined by an <math>LU</math> factorization of the rectangular matrix <math>B_S = (B \ S)^T</math> with stability being favoured more than sparsity.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| nS      | <p>is the current number of superbasic variables.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| condHz  | <p>is an estimate of the condition number of <math>R^T R</math>, itself an estimate of <math>Z^T H Z</math>, the reduced Hessian of the Lagrangian. The condition number is the square of the ratio of the largest and smallest diagonals of the upper triangular matrix <math>R</math>, this being a lower bound on the condition number of <math>R^T R</math>. <math>\text{condHz}</math> gives a rough indication of whether or not the optimization procedure is having difficulty. If <math>\epsilon</math> is the relative <b>machine precision</b> being used, the SQP algorithm will make slow progress if <math>\text{condHz}</math> becomes as large as <math>\epsilon^{-1/2} \approx 10^8</math>, and will probably fail to find a better solution if <math>\text{condHz}</math> reaches <math>\epsilon^{-3/4} \approx 10^{12}</math>.</p> <p>To guard against high values of <math>\text{condHz}</math>, attention should be given to the scaling of the variables and the constraints. In some cases it may be necessary to add upper or lower bounds to certain variables to keep them a reasonable distance from singularities in the nonlinear functions or their derivatives.</p> |
| Penalty | <p>is the Euclidean norm of the vector of penalty parameters used in the augmented Lagrangian merit function (not printed if there are no nonlinear constraints).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

The summary line may include additional code characters that indicate what happened during the course of the major iteration. These will follow the separator ‘\_’ in the output

| Label | Description                                                                                                                                                                                                                                                                                                                                                |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| c     | central differences have been used to compute the unknown components of the objective and constraint gradients. A switch to central differences is made if either the linesearch gives a small step, or $x$ is close to being optimal. In some cases, it may be necessary to re-solve the QP subproblem with the central difference gradient and Jacobian. |
| d     | during the linesearch it was necessary to decrease the step in order to obtain a maximum constraint violation conforming to the value of the optional parameter Violation Limit.                                                                                                                                                                           |
| D     | you set $\text{STATUS} = -1$ on exit from USRFUN, indicating that the linesearch needed to be done with a smaller value of the step length $\alpha$ .                                                                                                                                                                                                      |
| l     | the norm wise change in the variables was limited by the value of the the optional parameter Major Step Limit. If this output occurs repeatedly during later iterations,                                                                                                                                                                                   |

it may be worthwhile increasing the value of the optional parameter Major Step Limit.

|   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| i | if E04VHF is not in elastic mode, an i signifies that the QP subproblem is infeasible. This event triggers the start of nonlinear elastic mode, which remains in effect for all subsequent iterations. Once in elastic mode, the QP subproblems are associated with the elastic problem (12) (see Section 10.5).<br><br>If E04VHF is already in elastic mode, an i indicates that the minimizer of the elastic subproblem does not satisfy the linearized constraints. (In this case, a feasible point for the usual QP subproblem may or may not exist.) |
| M | an extra evaluation of the problem functions was needed to define an acceptable positive-definite quasi-Newton update to the Lagrangian Hessian. This modification is only done when there are nonlinear constraints.                                                                                                                                                                                                                                                                                                                                     |
| m | this is the same as M except that it was also necessary to modify the update to include an augmented Lagrangian term.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| n | no positive-definite BFGS update could be found. The approximate Hessian is unchanged from the previous iteration.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| R | the approximate Hessian has been reset by discarding all but the diagonal elements. This reset will be forced periodically by the Hessian Frequency and Hessian Updates keywords. However, it may also be necessary to reset an ill-conditioned Hessian from time to time.                                                                                                                                                                                                                                                                                |
| r | the approximate Hessian was reset after ten consecutive major iterations in which no BFGS update could be made. The diagonals of the approximate Hessian are retained if at least one update has been done since the last reset. Otherwise, the approximate Hessian is reset to the identity matrix.                                                                                                                                                                                                                                                      |
| s | a self-scaled BFGS update was performed. This update is used when the Hessian approximation is diagonal, and hence always follows a Hessian reset.                                                                                                                                                                                                                                                                                                                                                                                                        |
| t | the minor iterations were terminated because of the Minor Iterations Limit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| T | the minor iterations were terminated because of the New Superbasics Limit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| u | the QP subproblem was unbounded.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| w | a weak solution of the QP subproblem was found.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| z | the Superbasics Limit was reached.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## 12.2 Minor Iteration Log

If Minor Print Level > 0, one line of information is output to the Print file every  $k$ th minor iteration, where  $k$  is the specified Print Frequency. A heading is printed before the first such line following a basis factorization. The heading contains the items described below. In this description, a pricing operation is the process by which a nonbasic variable is selected to become superbasic (in addition to those already in the superbasic set). The selected variable is denoted by jq. Variable jq often becomes basic immediately. Otherwise it remains superbasic, unless it reaches its opposite bound and returns to the nonbasic set.

If Partial Price is in effect, variable jq is selected from  $A_{pp}$  or  $I_{pp}$ , the ppth segments of the constraint matrix  $(A \ -I)$ .

| Label            | Description                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Itn              | the current iteration number.                                                                                                                                                                                                                                                                                                                                                                  |
| LPmult or QPmult | is the reduced cost (or reduced gradient) of the variable jq selected by the pricing procedure at the start of the present iteration. Algebraically, the reduced gradient is $d_j = g_j - \pi^T a_j$ for $j = jq$ , where $g_j$ is the gradient of the current objective function, $\pi$ is the vector of dual variables for the QP subproblem, and $a_j$ is the $j$ th column of $(A \ -I)$ . |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                            | Note that the reduced cost is the 1-norm of the reduced-gradient vector at the start of the iteration, just after the pricing procedure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| LPstep or QPstep           | is the step length $\alpha$ taken along the current search direction $p$ . The variables $x$ have just been changed to $x + \alpha p$ . Write Step to stand for LPStep or QPStep, depending on the problem. If a variable is made superbasic during the current iteration ( $+SBS > 0$ ), Step will be the step to the nearest bound. During Phase 2, the step can be greater than one only if the reduced Hessian is not positive definite.                                                                                                                                                                                                                                                                      |
| nInf                       | is the number of infeasibilities <i>after</i> the present iteration. This number will not increase unless the iterations are in elastic mode.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| SumInf                     | is the sum of infeasibilities after the present iteration, if $nInf > 0$ . The value usually decreases at each nonzero Step, but if it decreases by 2 or more, SumInf may occasionally increase.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| rgNorm                     | is the norm of the reduced-gradient vector at the start of the iteration. (It is the norm of the vector with elements $d_j$ for variables $j$ in the superbasic set.) During Phase 2 this norm will be approximately zero after a unit step. (The heading is not printed if the problem is linear.)                                                                                                                                                                                                                                                                                                                                                                                                               |
| LPobjective or QPobjective | the QP objective function after the present iteration. In elastic mode, the heading is changed to Elastic QPobj. In either case, the value printed decreases monotonically.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| +SBS                       | is the variable $j_q$ selected by the pricing operation to be added to the superbasic set.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| -SBS                       | is the superbasic variable chosen to become nonbasic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| -BS                        | is the basis variable removed (if any) to become nonbasic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Pivot                      | if column $a_q$ replaces the $r$ th column of the basis $B$ , Pivot is the $r$ th element of a vector $y$ satisfying $By = a_q$ . Wherever possible, Step is chosen to avoid extremely small values of Pivot (since they cause the basis to be nearly singular). In rare cases, it may be necessary to increase the Pivot Tolerance to exclude very small elements of $y$ from consideration during the computation of Step.                                                                                                                                                                                                                                                                                      |
| L+U                        | is the number of nonzeros representing the basis factors $L$ and $U$ . Immediately after a basis factorization $B = LU$ , $L+U$ is $\text{len}L + \text{len}U$ , the number of subdiagonal elements in the columns of a lower triangular matrix and the number of diagonal and superdiagonal elements in the rows of an upper-triangular matrix. Further nonzeros are added to $L$ when various columns of $B$ are later replaced. As columns of $B$ are replaced, the matrix $U$ is maintained explicitly (in sparse form). The value of $L$ will steadily increase, whereas the value of $U$ may fluctuate up or down. Thus the value of $L+U$ may fluctuate up or down (in general, it will tend to increase). |
| ncp                        | is the number of compressions required to recover storage in the data structure for $U$ . This includes the number of compressions needed during the previous basis factorization.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| nS                         | is the current number of superbasic variables. (The heading is not printed if the problem is linear.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| condHz                     | see Section 12.1. (The heading is not printed if the problem is linear.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 12.3 Crash Statistics

If Major Print Level  $\geq 10$  and System Information Yes has been specified, the following items are output to the Print file when START = 0 and no Basis file is loaded. They refer to the number of columns that the Crash procedure selects during selected passes through  $A$  while searching for a triangular basis matrix.

| Label     | Description                                 |
|-----------|---------------------------------------------|
| Slacks    | is the number of slacks selected initially. |
| Free cols | is the number of free columns in the basis. |

|           |                                                                                                 |
|-----------|-------------------------------------------------------------------------------------------------|
| Preferred | is the number of ‘preferred’ columns in the basis (i.e., $XSTATE(j) = 3$ for some $j \leq n$ ). |
| Unit      | is the number of unit columns in the basis.                                                     |
| Double    | is the number of columns in the basis containing 2 nonzeros.                                    |
| Triangle  | is the number of triangular columns in the basis.                                               |
| Pad       | is the number of slacks used to pad the basis (to make it a nonsingular triangle).              |

## 12.4 Basis Factorization Statistics

If Major Print Level  $\geq 10$ , the first seven items listed below are output to the Print file whenever the basis  $B$  or the rectangular matrix  $B_S = (B \ S)^T$  is factorized before solution of the next QP subproblem (see Section 11.2).

Note that  $B_S$  may be factorized at the start of just some of the major iterations. It is immediately followed by a factorization of  $B$  itself.

Gaussian elimination is used to compute a sparse  $LU$  factorization of  $B$  or  $B_S$ , where  $PLP^T$  and  $PUQ$  are lower and upper triangular matrices, for some permutation matrices  $P$  and  $Q$ . Stability is ensured as described under optional parameter LU Factor Tolerance.

If Minor Print Level  $\geq 10$ , the same items are printed during the QP solution whenever the current  $B$  is factorized. In addition, if System Information Yes has been specified, the entries from Elms onwards are also printed.

| Label                     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------------------------------------------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------------------------------------------------------------------------------------------------|----|-------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------------------|----|----------------------------------------------------------------------------------------------|----|---------------------------------------------------|
| Factor                    | the number of factorizations since the start of the run.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| Demand                    | a code giving the reason for the present factorization, as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
|                           | <table> <tr> <th>Code</th><th>Meaning</th></tr> <tr> <td>0</td><td>First <math>LU</math> factorization.</td></tr> <tr> <td>1</td><td>The number of updates reached the Factorization Frequency.</td></tr> <tr> <td>2</td><td>The nonzeros in the updated factors have increased significantly.</td></tr> <tr> <td>7</td><td>Not enough storage to update factors.</td></tr> <tr> <td>10</td><td>Row residuals are too large (see the description of the optional parameter Check Frequency).</td></tr> <tr> <td>11</td><td>Ill-conditioning has caused inconsistent results.</td></tr> </table>                                                                                                                                             | Code | Meaning                                   | 0  | First $LU$ factorization.                                                                                                                                                                                       | 1  | The number of updates reached the Factorization Frequency.                                                          | 2  | The nonzeros in the updated factors have increased significantly.                                                                                     | 7 | Not enough storage to update factors. | 10 | Row residuals are too large (see the description of the optional parameter Check Frequency). | 11 | Ill-conditioning has caused inconsistent results. |
| Code                      | Meaning                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 0                         | First $LU$ factorization.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 1                         | The number of updates reached the Factorization Frequency.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 2                         | The nonzeros in the updated factors have increased significantly.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 7                         | Not enough storage to update factors.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 10                        | Row residuals are too large (see the description of the optional parameter Check Frequency).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| 11                        | Ill-conditioning has caused inconsistent results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| Itn                       | is the current minor iteration number.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| Nonlin                    | is the number of nonlinear variables in the current basis $B$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| Linear                    | is the number of linear variables in $B$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| Slacks                    | is the number of slack variables in $B$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| B, BR, BS or BT factorize | is the type of $LU$ factorization.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
|                           | <table> <tr> <td>B</td><td>periodic factorization of the basis <math>B</math>.</td></tr> <tr> <td>BR</td><td>more careful rank-revealing factorization of <math>B</math> using threshold rook pivoting. This occurs mainly at the start, if the first basis factors seem singular or ill-conditioned. Followed by a normal B factorize.</td></tr> <tr> <td>BS</td><td><math>B_S</math> is factorized to choose a well-conditioned <math>B</math> from the current <math>(B \ S)</math>. Followed by a normal B factorize.</td></tr> <tr> <td>BT</td><td>same as BS except the current <math>B</math> is tried first and accepted if it appears to be not much more ill-conditioned than after the previous BS factorize.</td></tr> </table> | B    | periodic factorization of the basis $B$ . | BR | more careful rank-revealing factorization of $B$ using threshold rook pivoting. This occurs mainly at the start, if the first basis factors seem singular or ill-conditioned. Followed by a normal B factorize. | BS | $B_S$ is factorized to choose a well-conditioned $B$ from the current $(B \ S)$ . Followed by a normal B factorize. | BT | same as BS except the current $B$ is tried first and accepted if it appears to be not much more ill-conditioned than after the previous BS factorize. |   |                                       |    |                                                                                              |    |                                                   |
| B                         | periodic factorization of the basis $B$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| BR                        | more careful rank-revealing factorization of $B$ using threshold rook pivoting. This occurs mainly at the start, if the first basis factors seem singular or ill-conditioned. Followed by a normal B factorize.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| BS                        | $B_S$ is factorized to choose a well-conditioned $B$ from the current $(B \ S)$ . Followed by a normal B factorize.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| BT                        | same as BS except the current $B$ is tried first and accepted if it appears to be not much more ill-conditioned than after the previous BS factorize.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| m                         | is the number of rows in $B$ or $B_S$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |
| n                         | is the number of columns in $B$ or $B_S$ . Preceded by ‘=’ or ‘>’ respectively.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |      |                                           |    |                                                                                                                                                                                                                 |    |                                                                                                                     |    |                                                                                                                                                       |   |                                       |    |                                                                                              |    |                                                   |

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Elems             | is the number of nonzero elements in $B$ or $B_S$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Amax              | is the largest nonzero in $B$ or $B_S$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Density           | is the percentage nonzero density of $B$ or $B_S$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Merit/MerRP/MerCP | Merit is the average Markowitz merit count for the elements chosen to be the diagonals of $PUQ$ . Each merit count is defined to be $(c-1)(r-1)$ where $c$ and $r$ are the number of nonzeros in the column and row containing the element at the time it is selected to be the next diagonal. Merit is the average of $n$ such quantities. It gives an indication of how much work was required to preserve sparsity during the factorization. If LU Complete Pivoting or LU Rook Pivoting has been selected, this heading is changed to MerCP, respectively MerRP.                                                                                                                                             |
| lenL              | is the number of nonzeros in $L$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| L+U               | is the number of nonzeros representing the basis factors $L$ and $U$ . Immediately after a basis factorization $B = LU$ , this is $\text{lenL} + \text{lenU}$ , the number of subdiagonal elements in the columns of a lower triangular matrix and the number of diagonal and superdiagonal elements in the rows of an upper-triangular matrix. Further nonzeros are added to $L$ when various columns of $B$ are later replaced. As columns of $B$ are replaced, the matrix $U$ is maintained explicitly (in sparse form). The value of $L$ will steadily increase, whereas the value of $U$ may fluctuate up or down. Thus the value of $L+U$ may fluctuate up or down (in general, it will tend to increase). |
| Cmpressns         | is the number of times the data structure holding the partially factored matrix needed to be compressed to recover unused storage. Ideally this number should be zero. If it is more than 3 or 4, the amount of workspace available to E04VHF should be increased for efficiency.                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Inces             | is the percentage increase in the number of nonzeros in $L$ and $U$ relative to the number of nonzeros in $B$ or $B_S$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Utri              | is the number of triangular rows of $B$ or $B_S$ at the top of $U$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| lenU              | the number of nonzeros in $U$ , including its diagonals.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Ltol              | is the largest subdiagonal element allowed in $L$ . This is the specified LU Factor Tolerance or a smaller value that is currently being used for greater stability.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Umax              | the maximum nonzero element in $U$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Ugrwth            | is the ratio $U_{\max}/A_{\max}$ , which ideally should not be substantially larger than 10.0 or 100.0. If it is orders of magnitude larger, it may be advisable to reduce the LU Factor Tolerance to 5.0, 4.0, 3.0 or 2.0, say (but bigger than 1.0).<br><br>As long as $L_{\max}$ is not large (say 5.0 or less), $\max(A_{\max}, U_{\max})/D_{\min}$ gives an estimate of the condition number $B$ . If this is extremely large, the basis is nearly singular. Slacks are used to replace suspect columns of $B$ and the modified basis is refactored.                                                                                                                                                        |
| Ltri              | is the number of triangular columns of $B$ or $B_S$ at the left of $L$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| dense1            | is the number of columns remaining when the density of the basis matrix being factorized reached 0.3.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Lmax              | is the actual maximum subdiagonal element in $L$ (bounded by $L_{\text{tol}}$ ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Akmax             | is the largest nonzero generated at any stage of the $LU$ factorization. (Values much larger than $A_{\max}$ indicate instability.) $A_{\text{kmax}}$ is not printed if LU Partial Pivoting is selected.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

|        |                                                                                                                                                                            |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Agrwth | is the ratio $A_{kmax}/A_{max}$ . Values much larger than 100 (say) indicate instability. Agrwth is not printed if LU Partial Pivoting is selected.                        |
| bump   | is the size of the block to be factorized nontrivially after the triangular rows and columns of $B$ or $B_S$ have been removed.                                            |
| dense2 | is the number of columns remaining when the density of the basis matrix being factorized reached 0.6. (The Markowitz pivot strategy searches fewer columns at that stage.) |
| DUmax  | is the largest diagonal of $PUQ$ .                                                                                                                                         |
| DUmin  | is the smallest diagonal of $PUQ$ .                                                                                                                                        |
| condU  | the ratio $DU_{max}/DU_{min}$ , which estimates the condition number of $U$ (and of $B$ if Ltol is less than 5.0, say).                                                    |

## 12.5 The Solution File

At the end of a run, the final solution may be output as a Solution file, according to Solution File. Some header information appears first to identify the problem and the final state of the optimization procedure. A ROWS section and a COLUMNS section then follow, giving one line of information for each row and column. The format used is similar to certain commercial systems, though there is no industry standard.

In general, numerical values are output with format f16.5. The maximum record length is 111 characters, including the first (carriage-control) character.

To reduce clutter, a full stop (.) is printed for any numerical value that is exactly zero. The values  $\pm 1$  are also printed specially as 1.0 and  $-1.0$ . Infinite bounds ( $\pm 10^{20}$  or larger) are printed as None.

A Solution file is intended to be read from disk by a self-contained program that extracts and saves certain values as required for possible further computation. Typically, the first 14 records would be ignored. Each subsequent record may be read using

```
format(i8, 2x, 2a4, 1x, a1, 1x, a3, 5e16.6, i7)
```

adapted to suit the occasion. The end of the ROWS section is marked by a record that starts with a 1 and is otherwise blank. If this and the next 4 records are skipped, the COLUMNS section can then be read under the same format. (There should be no need for backspace statements.)

A full description of the ROWS section and the COLUMNS section is given in Sections 8.1.1 and 8.1.2.

## 12.6 The Summary File

If Summary File > 0, the following information is output to the unit number associated with Summary File. (It is a brief summary of the output directed to unit Print File):

- the optional parameters supplied via the option setting routines, if any;
  - the Basis file loaded, if any;
  - a brief major iteration log (see Section 12.1);
  - a brief minor iteration log (see Section 12.2);
  - the exit condition, IFAIL;
  - a summary of the final iterate.
-