

NAG Library Routine Document

F06GUF (ZGTHR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06GUF (ZGTHR) gathers specified (usually nonzero) elements of a complex vector y in full storage form into a sparse complex vector x in compressed form.

2 Specification

```
SUBROUTINE F06GUF(NZ, Y, X, INDX)
  INTEGER          NZ, INDX(*)
  complex*16      Y(*), X(*)
```

The routine may be called by its BLAS name *zgthr*.

3 Description

None.

4 References

None.

5 Parameters

- | | | |
|----|--|---------------|
| 1: | NZ – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the number of elements in the compressed vector x . | |
| 2: | Y(*) – complex*16 array | <i>Input</i> |
| | Note: the dimension of the array Y must be at least $\max_k(\text{INDX}(k))$. | |
| | <i>On entry:</i> the vector y . Only elements corresponding to indices in INDX are accessed. | |
| 3: | X(*) – complex*16 array | <i>Output</i> |
| | Note: the dimension of the array X must be at least $\max(1, \text{NZ})$. | |
| | <i>On exit:</i> the compressed vector x . | |
| 4: | INDX(*) – INTEGER array | <i>Input</i> |
| | Note: the dimension of the array INDX must be at least $\max(1, \text{NZ})$. | |
| | <i>On entry:</i> the indices of the elements in the compressed vector x . | |

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
