

NAG Library Routine Document

F06GVF (ZGTHRZ)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06GVF (ZGTHRZ) gathers specified (usually nonzero) elements of a complex vector y in full storage form into a sparse complex vector x in compressed form. The specified elements of y are set to zero.

2 Specification

```
SUBROUTINE F06GVF(NZ, Y, X, INDX)
  INTEGER          NZ, INDX(*)
  complex*16      Y(*), X(*)
```

The routine may be called by its BLAS name *zgthrz*.

3 Description

None.

4 References

None.

5 Parameters

- 1: NZ – INTEGER *Input*
On entry: the number of elements in the compressed vector x .
- 2: Y(*) – **complex*16** array *Input/Output*
Note: the dimension of the array Y must be at least $\max_k(\text{INDX}(k))$.
On entry: the vector y . Only elements corresponding to indices in INDX are accessed.
On exit: the elements of y corresponding to indices in INDX are set to zero.
- 3: X(*) – **complex*16** array *Output*
Note: the dimension of the array X must be at least $\max(1, \text{NZ})$.
On exit: the compressed vector x .
- 4: INDX(*) – INTEGER array *Input*
Note: the dimension of the array INDX must be at least $\max(1, \text{NZ})$.
On entry: the indices of the elements in the compressed vector x .

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
