

NAG Library Routine Document

F06PGF (DTBMV)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06PGF (DTBMV) performs one of the matrix-vector operations

$$x \leftarrow Ax \quad \text{or} \quad x \leftarrow A^T x,$$

where A is an n by n real triangular band matrix with k subdiagonals or superdiagonals, and x is an n element real vector.

2 Specification

```
SUBROUTINE F06PGF(UPLO, TRANS, DIAG, N, K, A, LDA, X, INCX)
  INTEGER          N, K, LDA, INCX
  double precision A(LDA,*), X(*)
  CHARACTER*1      UPLO, TRANS, DIAG
```

The routine may be called by its BLAS name ***dtbm*****v**.

3 Description

None.

4 References

None.

5 Parameters

- 1: UPLO – CHARACTER*1 *Input*
On entry: specifies whether A is upper or lower triangular.
UPLO = 'U'
 A is upper triangular.
UPLO = 'L'
 A is lower triangular.
Constraint: UPLO = 'U' or 'L'.
- 2: TRANS – CHARACTER*1 *Input*
On entry: specifies the operation to be performed.
TRANS = 'N'
 $x \leftarrow Ax$.
TRANS = 'T' or 'C'
 $x \leftarrow A^T x$.
Constraint: TRANS = 'N', 'T' or 'C'.

- 3: DIAG – CHARACTER*1 *Input*
On entry: specifies whether A has nonunit or unit diagonal elements.
DIAG = 'N'
The diagonal elements are stored explicitly.
DIAG = 'U'
The diagonal elements are assumed to be 1, and are not referenced.
Constraint: DIAG = 'N' or 'U'.
- 4: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 5: K – INTEGER *Input*
On entry: k , the number of subdiagonals or superdiagonals of the matrix A .
Constraint: $K \geq 0$.
- 6: A(LDA,*) – **double precision** array *Input*
Note: the second dimension of the array A must be at least N .
On entry: the n by n triangular band matrix A
The matrix is stored in rows 1 to $k + 1$, more precisely,
if UPLO = 'U', the elements of the upper triangle of A within the band must be stored with element A_{ij} in $A(k + 1 + i - j, j)$ for $\max(1, j - k) \leq i \leq j$;
if UPLO = 'L', the elements of the lower triangle of A within the band must be stored with element A_{ij} in $A(1 + i - j, j)$ for $j \leq i \leq \min(n, j + k)$.
If DIAG = 'U', the diagonal elements of A are assumed to be 1, and are not referenced.
- 7: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06PGF (DTBMV) is called.
Constraint: $LDA \geq K + 1$.
- 8: X(*) – **double precision** array *Input/Output*
Note: the dimension of the array X must be at least $1 + (N - 1)|INCX|$.
On entry: the incremented array X must contain the n element vector x .
On exit: the updated vector x .
- 9: INCX – INTEGER *Input*
On entry: the increment in the subscripts of X between successive elements of x .
Constraint: $INCX \neq 0$.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
