

NAG Library Routine Document

F06TBF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06TBF performs the symmetric rank-1 update operation

$$A \leftarrow \alpha x x^T + A,$$

where A is an n by n complex symmetric matrix, x is an n element complex vector, and α is a complex scalar.

2 Specification

```
SUBROUTINE F06TBF(UPLO, N, ALPHA, X, INCX, A, LDA)
  INTEGER          N, INCX, LDA
  complex*16      ALPHA, X(*), A(LDA,*)
  CHARACTER*1      UPLO
```

3 Description

None.

4 References

None.

5 Parameters

- | | | |
|----|---|--------------|
| 1: | UPLO – CHARACTER*1 | <i>Input</i> |
| | <i>On entry:</i> specifies whether the upper or lower triangular part of A is stored. | |
| | UPLO = 'U'
The upper triangular part of A is stored. | |
| | UPLO = 'L'
The lower triangular part of A is stored. | |
| | <i>Constraint:</i> UPLO = 'U' or 'L'. | |
| 2: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the order of the matrix A . | |
| | <i>Constraint:</i> $N \geq 0$. | |
| 3: | ALPHA – complex*16 | <i>Input</i> |
| | <i>On entry:</i> the scalar α . | |
| 4: | X(*) – complex*16 array | <i>Input</i> |
| | Note: the dimension of the array X must be at least $1 + (N - 1) \text{INCX} $. | |
| | <i>On entry:</i> the incremented array X must contain the n element vector x . | |

- 5: INCX – INTEGER *Input*
On entry: the increment in the subscripts of X between successive elements of x .
Constraint: $\text{INCX} \neq 0$.
- 6: A(LDA,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n symmetric matrix A .
If UPLO = 'U', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.
If UPLO = 'L', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: the updated matrix A .
- 7: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06TBF is called.
Constraint: $\text{LDA} \geq \max(1, N)$.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
