

NAG Library Routine Document

F06TRF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06TRF performs a QR or RQ factorization (as a sequence of plane rotations) of a complex upper Hessenberg matrix.

2 Specification

```
SUBROUTINE F06TRF(SIDE, N, K1, K2, C, S, A, LDA)
INTEGER          N, K1, K2, LDA
double precision S(*)
complex*16      C(K2), A(LDA,*)
CHARACTER*1      SIDE
```

3 Description

F06TRF transforms an n by n complex upper Hessenberg matrix H to upper triangular form R by applying a unitary matrix P from the left or the right. H is assumed to have real nonzero subdiagonal elements $h_{k+1,k}$, for $k = k_1, k_1 + 1, \dots, k_2 - 1$, only; R has real diagonal elements. P is formed as a sequence of plane rotations in planes k_1 to k_2 .

If $SIDE = 'L'$, the rotations are applied from the left:

$$PH = R,$$

where $P = DP_{k_2-1} \cdots P_{k_1+1}P_{k_1}$ and $D = \text{diag}(1, \dots, 1, d_{k_2}, 1, \dots, 1)$ with $|d_{k_2}| = 1$.

If $SIDE = 'R'$, the rotations are applied from the right:

$$HP^H = R,$$

where $P = DP_{k_1}P_{k_1+1} \cdots P_{k_2-1}$ and $D = \text{diag}(1, \dots, 1, d_{k_1}, 1, \dots, 1)$ with $|d_{k_1}| = 1$.

In either case, P_k is a rotation in the $(k, k+1)$ plane, chosen to annihilate $h_{k+1,k}$.

The 2 by 2 plane rotation part of P_k has the form

$$\begin{pmatrix} \bar{c}_k & s_k \\ -s_k & c_k \end{pmatrix}$$

with s_k real.

4 References

None.

5 Parameters

1: SIDE – CHARACTER*1

Input

On entry: specifies whether H is operated on from the left or the right.

SIDE = 'L'

H is pre-multiplied from the left.

SIDE = 'R'

H is post-multiplied from the right.

Constraint: SIDE = 'L' or 'R'.

2: N – INTEGER Input

On entry: n , the order of the matrix H .

Constraint: $N \geq 0$.

3: K1 – INTEGER Input

4: K2 – INTEGER Input

On entry: the dimension of the array C as declared in the (sub)program from which F06TRF is called. the values k_1 and k_2 .

If $K1 < 1$ or $K2 \leq K1$ or $K2 > N$, an immediate return is effected.

5: C(K2) – **complex*16** array Output

On exit: $C(k)$ holds c_k , the cosine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$; $C(k_2)$ holds d_{k_2} , the k_2 th diagonal element of D , if SIDE = 'L', or d_{k_1} , the k_1 th diagonal element of D , if SIDE = 'R'.

6: S(*) – **double precision** array Input/Output

Note: the dimension of the array S must be at least $K2 - K1$.

On entry: the nonzero subdiagonal elements of H : $S(k)$ must hold $h_{k+1,k}$, for $k = k_1, k_1 + 1, \dots, k_2 - 1$.

On exit: $S(k)$ holds s_k , the sine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$.

7: A(LDA,*) – **complex*16** array Input/Output

Note: the second dimension of the array A must be at least N.

On entry: the upper triangular part of the n by n upper Hessenberg matrix H .

On exit: the upper triangular matrix R . The imaginary parts of the diagonal elements are set to zero.

8: LDA – INTEGER Input

On entry: the first dimension of the array A as declared in the (sub)program from which F06TRF is called.

Constraint: $LDA \geq \max(1, N)$.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.