

NAG Library Routine Document

F06ZUF (ZSYRK)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06ZUF (ZSYRK) performs one of the symmetric rank- k update operations

$$C \leftarrow \alpha AA^T + \beta C \quad \text{or} \quad C \leftarrow \alpha A^T A + \beta C,$$

where A is a complex matrix, C is an n by n complex symmetric matrix, and α and β are complex scalars.

2 Specification

```
SUBROUTINE F06ZUF(UPLO, TRANS, N, K, ALPHA, A, LDA, BETA, C, LDC)
  INTEGER          N, K, LDA, LDC
  complex*16      ALPHA, A(LDA,*), BETA, C(LDC,*)
  CHARACTER*1      UPLO, TRANS
```

The routine may be called by its BLAS name ***zsyrk***.

3 Description

None.

4 References

None.

5 Parameters

- 1: UPLO – CHARACTER*1 *Input*
On entry: specifies whether the upper or lower triangular part of C is stored.
 UPLO = 'U'
 The upper triangular part of C is stored.
 UPLO = 'L'
 The lower triangular part of C is stored.
Constraint: UPLO = 'U' or 'L'.
- 2: TRANS – CHARACTER*1 *Input*
On entry: specifies the operation to be performed.
 TRANS = 'N'
 $C \leftarrow \alpha AA^T + \beta C$.
 TRANS = 'T'
 $C \leftarrow \alpha A^T A + \beta C$.
Constraint: TRANS = 'N' or 'T'.

- 3: N – INTEGER *Input*
On entry: n , the order of the matrix C ; the number of rows of A if TRANS = 'N', or the number of columns of A if TRANS = 'T' or 'C'.
Constraint: $N \geq 0$.
- 4: K – INTEGER *Input*
On entry: k , the number of columns of A if TRANS = 'N', or the number of rows of A if TRANS = 'T' or 'C'.
Constraint: $K \geq 0$.
- 5: ALPHA – **complex*16** *Input*
On entry: the scalar α .
- 6: A(LDA,*) – **complex*16** array *Input*
Note: the second dimension of the array A must be at least $\max(1, K)$ if TRANS = 'N' and at least $\max(1, N)$ if TRANS = 'T' or 'C'.
On entry: the matrix A ; A is n by k if TRANS = 'N', or k by n if TRANS = 'T' or 'C'.
- 7: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06ZUF (ZSYRK) is called.
Constraints:
 if TRANS = 'N', $LDA \geq \max(1, N)$;
 if TRANS = 'T' or 'C', $LDA \geq \max(1, K)$.
- 8: BETA – **complex*16** *Input*
On entry: the scalar β .
- 9: C(LDC,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array C must be at least $\max(1, N)$.
On entry: the n by n symmetric matrix C .
 If UPLO = 'U', the upper triangular part of C must be stored and the elements of the array below the diagonal are not referenced.
 If UPLO = 'L', the lower triangular part of C must be stored and the elements of the array above the diagonal are not referenced.
On exit: the updated matrix C .
- 10: LDC – INTEGER *Input*
On entry: the first dimension of the array C as declared in the (sub)program from which F06ZUF (ZSYRK) is called.
Constraint: $LDC \geq \max(1, N)$.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
