

NAG Library Routine Document

F08AGF (DORMQR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08AGF (DORMQR) multiplies an arbitrary real matrix C by the real orthogonal matrix Q from a QR factorization computed by F08AEF (DGEQRF) or F08BEF (DGEQPF).

2 Specification

```
SUBROUTINE F08AGF(SIDE, TRANS, M, N, K, A, LDA, TAU, C, LDC, WORK,
1                LWORK, INFO)
    INTEGER          M, N, K, LDA, LDC, LWORK, INFO
    double precision A(LDA,*), TAU(*), C(LDC,*), WORK(max(1,LWORK))
    CHARACTER*1      SIDE, TRANS
```

The routine may be called by its LAPACK name ***dormqr***.

3 Description

F08AGF (DORMQR) is intended to be used after a call to F08AEF (DGEQRF) or F08BEF (DGEQPF), which perform a QR factorization of a real matrix A . The orthogonal matrix Q is represented as a product of elementary reflectors.

This routine may be used to form one of the matrix products

$$QC, Q^T C, CQ \text{ or } CQ^T,$$

overwriting the result on C (which may be any real rectangular matrix).

A common application of this routine is in solving linear least-squares problems, as described in the F08 Chapter Introduction and illustrated in Section 9 in F08AEF (DGEQRF).

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: SIDE – CHARACTER*1 *Input*
- On entry: indicates how Q or Q^T is to be applied to C .
- SIDE = 'L'
 Q or Q^T is applied to C from the left.
- SIDE = 'R'
 Q or Q^T is applied to C from the right.
- Constraint: SIDE = 'L' or 'R'.

- 2: TRANS – CHARACTER*1 *Input*
On entry: indicates whether Q or Q^T is to be applied to C .
 TRANS = 'N'
 Q is applied to C .
 TRANS = 'T'
 Q^T is applied to C .
Constraint: TRANS = 'N' or 'T'.
- 3: M – INTEGER *Input*
On entry: m , the number of rows of the matrix C .
Constraint: $M \geq 0$.
- 4: N – INTEGER *Input*
On entry: n , the number of columns of the matrix C .
Constraint: $N \geq 0$.
- 5: K – INTEGER *Input*
On entry: k , the number of elementary reflectors whose product defines the matrix Q .
Constraints:
 if SIDE = 'L', $M \geq K \geq 0$;
 if SIDE = 'R', $N \geq K \geq 0$.
- 6: A(LDA,*) – **double precision** array *Input*
Note: the second dimension of the array A must be at least $\max(1, K)$.
On entry: details of the vectors which define the elementary reflectors, as returned by F08AEF (DGEQRF) or F08BEF (DGEQPF).
- 7: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F08AGF (DORMQR) is called.
Constraints:
 if SIDE = 'L', $LDA \geq \max(1, M)$;
 if SIDE = 'R', $LDA \geq \max(1, N)$.
- 8: TAU(*) – **double precision** array *Input*
Note: the dimension of the array TAU must be at least $\max(1, K)$.
On entry: further details of the elementary reflectors as returned by F08AEF (DGEQRF) or F08BEF (DGEQPF).
- 9: C(LDC,*) – **double precision** array *Input/Output*
Note: the second dimension of the array C must be at least $\max(1, N)$.
On entry: the m by n matrix C .
On exit: C is overwritten by QC or $Q^T C$ or CQ or CQ^T as specified by SIDE and TRANS.

- 10: LDC – INTEGER *Input*
On entry: the first dimension of the array C as declared in the (sub)program from which F08AGF (DORMQR) is called.
Constraint: $LDC \geq \max(1, M)$.
- 11: WORK(max(1, LWORK)) – **double precision** array *Workspace*
On exit: if INFO = 0, WORK(1) contains the minimum value of LWORK required for optimal performance.
- 12: LWORK – INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F08AGF (DORMQR) is called.
 If LWORK = -1, a workspace query is assumed; the routine only calculates the optimal size of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.
Suggested value: for optimal performance, $LWORK \geq N \times nb$ if SIDE = 'L' and at least $M \times nb$ if SIDE = 'R', where *nb* is the optimal **block size**.
Constraints:
 if SIDE = 'L', $LWORK \geq \max(1, N)$ or LWORK = -1;
 if SIDE = 'R', $LWORK \geq \max(1, M)$ or LWORK = -1.
- 13: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = -*i*, argument *i* had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The computed result differs from the exact result by a matrix *E* such that

$$\|E\|_2 = O(\epsilon)\|C\|_2,$$

where ϵ is the **machine precision**.

8 Further Comments

The total number of floating-point operations is approximately $2nk(2m - k)$ if SIDE = 'L' and $2mk(2n - k)$ if SIDE = 'R'.

The complex analogue of this routine is F08AUF (ZUNMQR).

9 Example

See Section 9 in F08AEF (DGEQRF).