

NAG Library Routine Document

F08FPF (ZHEEVX)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08FPF (ZHEEVX) computes selected eigenvalues and, optionally, eigenvectors of a complex n by n Hermitian matrix A . Eigenvalues and eigenvectors can be selected by specifying either a range of values or a range of indices for the desired eigenvalues.

2 Specification

```
SUBROUTINE F08FPF (JOBZ, RANGE, UPLO, N, A, LDA, VL, VU, IL, IU, ABSTOL,
1                M, W, Z, LDZ, WORK, LWORK, RWORK, IWORK, JFAIL, INFO)
    INTEGER      N, LDA, IL, IU, M, LDZ, LWORK, IWORK(*), JFAIL(*),
1                INFO
    double precision VL, VU, ABSTOL, W(*), RWORK(*)
    complex*16      A(LDA,*), Z(LDZ,*), WORK(max(1,LWORK))
    CHARACTER*1  JOBZ, RANGE, UPLO
```

The routine may be called by its LAPACK name ***zheevx***.

3 Description

The Hermitian matrix A is first reduced to real tridiagonal form, using unitary similarity transformations. The required eigenvalues and eigenvectors are then computed from the tridiagonal matrix; the method used depends upon whether all, or selected, eigenvalues and eigenvectors are required.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Demmel J W and Kahan W (1990) Accurate singular values of bidiagonal matrices *SIAM J. Sci. Statist. Comput.* **11** 873–912

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: JOBZ – CHARACTER*1 *Input*
On entry: if JOBZ = 'N', compute eigenvalues only.
 If JOBZ = 'V', compute eigenvalues and eigenvectors.
Constraint: JOBZ = 'N' or 'V'.
- 2: RANGE – CHARACTER*1 *Input*
On entry: if RANGE = 'A', all eigenvalues will be found.
 If RANGE = 'V', all eigenvalues in the half-open interval (VL, VU] will be found.

If RANGE = 'I', the ILth to IUth eigenvalues will be found.

Constraint: RANGE = 'A', 'V' or 'I'.

3: UPLO – CHARACTER*1

Input

On entry: if UPLO = 'U', the upper triangular part of A is stored.

If UPLO = 'L', the lower triangular part of A is stored.

Constraint: UPLO = 'U' or 'L'.

4: N – INTEGER

Input

On entry: n , the order of the matrix A .

Constraint: $N \geq 0$.

5: A(LDA,*) – **complex*16** array

Input/Output

Note: the second dimension of the array A must be at least $\max(1, N)$.

On entry: the n by n Hermitian matrix A .

If UPLO = 'U', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.

If UPLO = 'L', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.

On exit: the lower triangle (if UPLO = 'L') or the upper triangle (if UPLO = 'U') of A , including the diagonal, is destroyed.

6: LDA – INTEGER

Input

On entry: the first dimension of the array A as declared in the (sub)program from which F08FPF (ZHEEVX) is called.

Constraint: $LDA \geq \max(1, N)$.

7: VL – **double precision**

Input

8: VU – **double precision**

Input

On entry: if RANGE = 'V', the lower and upper bounds of the interval to be searched for eigenvalues.

If RANGE = 'A' or 'I', VL and VU are not referenced.

Constraint: if RANGE = 'V', $VL < VU$.

9: IL – INTEGER

Input

10: IU – INTEGER

Input

On entry: if RANGE = 'I', the indices (in ascending order) of the smallest and largest eigenvalues to be returned.

If RANGE = 'A' or 'V', IL and IU are not referenced.

Constraints:

if RANGE = 'I' and $N = 0$, $IL = 1$ and $IU = 0$;

if RANGE = 'I' and $N > 0$, $1 \leq IL \leq IU \leq N$.

11: ABSTOL – **double precision**

Input

On entry: the absolute error tolerance for the eigenvalues. An approximate eigenvalue is accepted as converged when it is determined to lie in an interval $[a, b]$ of width less than or equal to

$$ABSTOL + \epsilon \max(|a|, |b|),$$

where ϵ is the **machine precision**. If ABSTOL is less than or equal to zero, then $\epsilon\|T\|_1$ will be used in its place, where T is the tridiagonal matrix obtained by reducing A to tridiagonal form. Eigenvalues will be computed most accurately when ABSTOL is set to twice the underflow threshold $2 \times X02AMF()$, not zero. If this routine returns with $INFO > 0$, indicating that some eigenvectors did not converge, try setting ABSTOL to $2 \times X02AMF()$. See Demmel and Kahan (1990).

- 12: M – INTEGER *Output*
On exit: the total number of eigenvalues found. $0 \leq M \leq N$.
 If RANGE = 'A', $M = N$.
 If RANGE = 'I', $M = IU - IL + 1$.
- 13: W(*) – **double precision** array *Output*
Note: the dimension of the array W must be at least $\max(1, N)$.
On exit: the first M elements contain the selected eigenvalues in ascending order.
- 14: Z(LDZ,*) – **complex*16** array *Output*
Note: the second dimension of the array Z must be at least $\max(1, M)$ if JOBZ = 'V', and at least 1 otherwise.
On exit: if JOBZ = 'V', then if $INFO = 0$, the first M columns of Z contain the orthonormal eigenvectors of the matrix A corresponding to the selected eigenvalues, with the i th column of Z holding the eigenvector associated with $W(i)$.
 If an eigenvector fails to converge, then that column of Z contains the latest approximation to the eigenvector, and the index of the eigenvector is returned in JFAIL.
 If JOBZ = 'N', Z is not referenced.
Note: you must ensure that at least $\max(1, M)$ columns are supplied in the array Z; if RANGE = 'V', the exact value of M is not known in advance and an upper bound of at least N must be used.
- 15: LDZ – INTEGER *Input*
On entry: the first dimension of the array Z as declared in the (sub)program from which F08FPF (ZHEEVX) is called.
Constraints:
 if JOBZ = 'V', $LDZ \geq \max(1, N)$;
 otherwise $LDZ \geq 1$.
- 16: WORK($\max(1, LWORK)$) – **complex*16** array *Workspace*
On exit: if $INFO = 0$, the real part of WORK(1) contains the minimum value of LWORK required for optimal performance.
- 17: LWORK – INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F08FPF (ZHEEVX) is called.
 If LWORK = -1, a workspace query is assumed; the routine only calculates the optimal size of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.
Suggested value: for optimal performance, $LWORK \geq (nb + 1) \times N$, where nb is the largest optimal **block size** for F08FSF (ZHETRD) and for F08FUF (ZUNMTR).
Constraint: $LWORK \geq \max(1, 2 \times N)$.

- 18: RWORK(*) – *double precision* array *Workspace*
Note: the dimension of the array RWORK must be at least $\max(1, 7 \times N)$.
- 19: IWORK(*) – INTEGER array *Workspace*
Note: the dimension of the array IWORK must be at least $\max(1, 5 \times N)$.
- 20: JFAIL(*) – INTEGER array *Output*
Note: the dimension of the array JFAIL must be at least $\max(1, N)$.
On exit: if JOBZ = 'V', then if INFO = 0, the first M elements of JFAIL are zero.
 If INFO > 0, JFAIL contains the indices of the eigenvectors that failed to converge.
 If JOBZ = 'E', JFAIL is not referenced.
- 21: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

If INFO = i , then i eigenvectors failed to converge. Their indices are stored in array JFAIL. Please see ABSTOL.

7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix $(A + E)$, where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and ϵ is the *machine precision*. See Section 4.7 of Anderson *et al.* (1999) for further details.

8 Further Comments

The total number of floating-point operations is proportional to n^3 .

The real analogue of this routine is F08FBF (DSYEVX).

9 Example

This example finds the eigenvalues in the half-open interval $(-2, 2]$, and the corresponding eigenvectors, of the Hermitian matrix

$$A = \begin{pmatrix} 1 & 2-i & 3-i & 4-i \\ 2+i & 2 & 3-2i & 4-2i \\ 3+i & 3+2i & 3 & 4-3i \\ 4+i & 4+2i & 4+3i & 4 \end{pmatrix}.$$

9.1 Program Text

```

*      F08FPF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
INTEGER          NIN, NOUT
PARAMETER        (NIN=5,NOUT=6)
INTEGER          NB, NMAX, MMAX
PARAMETER        (NB=64,NMAX=10,MMAX=5)
INTEGER          LDA, LDZ, LWORK
PARAMETER        (LDA=NMAX,LDZ=NMAX,LWORK=(NB+1)*NMAX)
DOUBLE PRECISION ZERO
PARAMETER        (ZERO=0.0D+0)
*      .. Local Scalars ..
DOUBLE PRECISION ABSTOL, VL, VU
INTEGER          I, IFAIL, IL, INFO, IU, J, LWKOPT, M, N
*      .. Local Arrays ..
COMPLEX *16      A(LDA,NMAX), WORK(LWORK), Z(LDZ,MMAX)
DOUBLE PRECISION RWORK(7*NMAX), W(NMAX)
INTEGER          IWORK(5*NMAX), JFAIL(NMAX)
*      .. External Subroutines ..
EXTERNAL          X04DAF, ZHEEVX
*      .. Intrinsic Functions ..
INTRINSIC         INT
*      .. Executable Statements ..
WRITE (NOUT,*) 'F08FPF Example Program Results'
WRITE (NOUT,*)
*      Skip heading in data file
READ (NIN,*)
READ (NIN,*) N
IF (N.LE.NMAX) THEN
*
*      Read the lower and upper bounds of the interval to be searched,
*      and read the upper triangular part of the matrix A from data
*      file
*
      READ (NIN,*) VL, VU
      READ (NIN,*) ((A(I,J),J=I,N),I=1,N)
*
*      Set the absolute error tolerance for eigenvalues. With ABSTOL
*      set to zero, the default value is used instead
*
      ABSTOL = ZERO
*
*      Solve the Hermitian eigenvalue problem
*
      CALL ZHEEVX('Vectors','Values in range','Upper',N,A,LDA,VL,VU,
+              IL,IU,ABSTOL,M,W,Z,LDZ,WORK,LWORK,RWORK,IWORK,
+              JFAIL,INFO)
      LWKOPT = INT(WORK(1))
*
      IF (INFO.GE.0 .AND. M.LE.MMAX) THEN
*
*      Print solution
*
        WRITE (NOUT,99999) 'Number of eigenvalues found =', M
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Eigenvalues'
        WRITE (NOUT,99998) (W(J),J=1,M)
*
        IFAIL = 0
        CALL X04DAF('General',' ',N,M,Z,LDZ,'Selected eigenvectors',
+              IFAIL)
        IF (INFO.GT.0) THEN
          WRITE (NOUT,99999)
          'INFO eigenvectors failed to converge, INFO =', INFO
          WRITE (NOUT,*)
          'Indices of eigenvectors that did not converge'
          WRITE (NOUT,99997) (JFAIL(J),J=1,M)
        END IF
      ELSE IF (M.GT.MMAX) THEN

```

```

      WRITE (NOUT,99996) 'M greater than MMAX, M =', M,
+      ', MMAX =', MMAX
      ELSE
      WRITE (NOUT,99999) 'Failure in ZHEEVX. INFO =', INFO
      END IF
*
*      Print workspace information
*
      IF (LWORK.LT.LWKOPT) THEN
      WRITE (NOUT,*)
      WRITE (NOUT,99995) 'Optimum complex workspace required = ',
+      LWKOPT, 'Workspace provided in WORK          = ', LWORK
      END IF
      ELSE
      WRITE (NOUT,*)
      WRITE (NOUT,*) 'NMAX too small'
      END IF
*
99999 FORMAT (1X,A,I5)
99998 FORMAT (3X,(8F8.4))
99997 FORMAT (3X,(8I8))
99996 FORMAT (1X,A,I5,A,I5)
99995 FORMAT (1X,A,I5,/1X,A,I5)
      END

```

9.2 Program Data

F08FPF Example Program Data

4					:Value of N
-2.0	2.0				:Values of VL and VU
(1.0, 0.0)	(2.0, -1.0)	(3.0, -1.0)	(4.0, -1.0)		
	(2.0, 0.0)	(3.0, -2.0)	(4.0, -2.0)		
		(3.0, 0.0)	(4.0, -3.0)		
			(4.0, 0.0)	:End of matrix A	

9.3 Program Results

F08FPF Example Program Results

Number of eigenvalues found = 2

Eigenvalues

-0.6886 1.1412

Selected eigenvectors

	1	2
1	-0.3975	-0.3746
	0.5105	-0.2414

2	0.3953	0.2895
	-0.3238	-0.4917

3	-0.4309	0.3768
	0.0383	0.3994

4	0.3648	-0.4175
	0.0000	0.0000