

NAG Library Routine Document

F08JEF (DSTEQR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08JEF (DSTEQR) computes all the eigenvalues and, optionally, all the eigenvectors of a real symmetric tridiagonal matrix, or of a real symmetric matrix which has been reduced to tridiagonal form.

2 Specification

```
SUBROUTINE F08JEF( COMPZ, N, D, E, Z, LDZ, WORK, INFO)
INTEGER           N, LDZ, INFO
double precision D(*), E(*), Z(LDZ,*), WORK(*)
CHARACTER*1       COMPZ
```

The routine may be called by its LAPACK name *dsteqr*.

3 Description

F08JEF (DSTEQR) computes all the eigenvalues and, optionally, all the eigenvectors of a real symmetric tridiagonal matrix T . In other words, it can compute the spectral factorization of T as

$$T = Z\Lambda Z^T,$$

where Λ is a diagonal matrix whose diagonal elements are the eigenvalues λ_i , and Z is the orthogonal matrix whose columns are the eigenvectors z_i . Thus

$$Tz_i = \lambda_i z_i, \quad i = 1, 2, \dots, n.$$

The routine may also be used to compute all the eigenvalues and eigenvectors of a real symmetric matrix A which has been reduced to tridiagonal form T :

$$\begin{aligned} A &= QTQ^T, \text{ where } Q \text{ is orthogonal} \\ &= (QZ)\Lambda(QZ)^T. \end{aligned}$$

In this case, the matrix Q must be formed explicitly and passed to F08JEF (DSTEQR), which must be called with $\text{COMPZ} = 'V'$. The routines which must be called to perform the reduction to tridiagonal form and form Q are:

full matrix	F08FEF (DSYTRD) and F08FFF (DORGTR)
full matrix, packed storage	F08GEF (DSPTRD) and F08GFF (DOPGTR)
band matrix	F08HEF (DSBTRD) with $\text{VECT} = 'V'$.

F08JEF (DSTEQR) uses the implicitly shifted QR algorithm, switching between the QR and QL variants in order to handle graded matrices effectively (see Greenbaum and Dongarra (1980)). The eigenvectors are normalized so that $\|z_i\|_2 = 1$, but are determined only to within a factor ± 1 .

If only the eigenvalues of T are required, it is more efficient to call F08JFF (DSTERF) instead. If T is positive-definite, small eigenvalues can be computed more accurately by F08JGF (DPTEQR).

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Greenbaum A and Dongarra J J (1980) Experiments with QR/QL methods for the symmetric triangular eigenproblem *LAPACK Working Note No. 17 (Technical Report CS-89-92)* University of Tennessee, Knoxville

Parlett B N (1998) *The Symmetric Eigenvalue Problem* SIAM, Philadelphia

5 Parameters

- 1: COMPZ – CHARACTER*1 *Input*
On entry: indicates whether the eigenvectors are to be computed.
 COMPZ = 'N'
 Only the eigenvalues are computed (and the array Z is not referenced).
 COMPZ = 'I'
 The eigenvalues and eigenvectors of T are computed (and the array Z is initialized by the routine).
 COMPZ = 'V'
 The eigenvalues and eigenvectors of A are computed (and the array Z must contain the matrix Q on entry).
Constraint: COMPZ = 'N', 'V' or 'I'.
- 2: N – INTEGER *Input*
On entry: n , the order of the matrix T .
Constraint: $N \geq 0$.
- 3: D(*) – **double precision** array *Input/Output*
Note: the dimension of the array D must be at least $\max(1, N)$.
On entry: the diagonal elements of the tridiagonal matrix T .
On exit: the n eigenvalues in ascending order, unless INFO > 0 (in which case see Section 6).
- 4: E(*) – **double precision** array *Input/Output*
Note: the dimension of the array E must be at least $\max(1, N - 1)$.
On entry: the off-diagonal elements of the tridiagonal matrix T .
On exit: E is overwritten.
- 5: Z(LDZ,*) – **double precision** array *Input/Output*
Note: the second dimension of the array Z must be at least $\max(1, N)$ if COMPZ = 'V' or 'I' and at least 1 if COMPZ = 'N'.
On entry: if COMPZ = 'V', Z must contain the orthogonal matrix Q from the reduction to tridiagonal form.
 If COMPZ = 'I', Z need not be set.
On exit: if COMPZ = 'I' or 'V', the n required orthonormal eigenvectors stored as columns of Z; the i th column corresponds to the i th eigenvalue, where $i = 1, 2, \dots, n$, unless INFO > 0.
 If COMPZ = 'N', Z is not referenced.

- 6: LDZ – INTEGER *Input*
On entry: the first dimension of the array Z as declared in the (sub)program from which F08JEF (DSTEQR) is called.
Constraints:
 if COMPZ = 'V' or 'I', LDZ $\geq \max(1, N)$;
 if COMPZ = 'N', LDZ ≥ 1 .
- 7: WORK(*) – **double precision** array *Workspace*
Note: the dimension of the array WORK must be at least $\max(1, 2 \times (N - 1))$ if COMPZ = 'V' or 'I' and at least 1 if COMPZ = 'N'.
 If COMPZ = 'N', WORK is not referenced.
- 8: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

The algorithm has failed to find all the eigenvalues after a total of $30 \times N$ iterations. In this case, D and E contain on exit the diagonal and off-diagonal elements, respectively, of a tridiagonal matrix similar to T . If INFO = i , then i off-diagonal elements have not converged to zero.

7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix $(T + E)$, where

$$\|E\|_2 = O(\epsilon)\|T\|_2,$$

and ϵ is the **machine precision**.

If λ_i is an exact eigenvalue and $\tilde{\lambda}_i$ is the corresponding computed value, then

$$|\tilde{\lambda}_i - \lambda_i| \leq c(n)\epsilon\|T\|_2,$$

where $c(n)$ is a modestly increasing function of n .

If z_i is the corresponding exact eigenvector, and $\tilde{z}_i$ is the corresponding computed eigenvector, then the angle $\theta(\tilde{z}_i, z_i)$ between them is bounded as follows:

$$\theta(\tilde{z}_i, z_i) \leq \frac{c(n)\epsilon\|T\|_2}{\min_{i \neq j} |\lambda_i - \lambda_j|}.$$

Thus the accuracy of a computed eigenvector depends on the gap between its eigenvalue and all the other eigenvalues.

8 Further Comments

The total number of floating-point operations is typically about $24n^2$ if COMPZ = 'N' and about $7n^3$ if COMPZ = 'V' or 'I', but depends on how rapidly the algorithm converges. When COMPZ = 'N', the

operations are all performed in scalar mode; the additional operations to compute the eigenvectors when COMPZ = 'V' or 'I' can be vectorized and on some machines may be performed much faster.

The complex analogue of this routine is F08JSF (ZSTEQR).

9 Example

This example computes all the eigenvalues and eigenvectors of the symmetric tridiagonal matrix T , where

$$T = \begin{pmatrix} -6.99 & -0.44 & 0.00 & 0.00 \\ -0.44 & 7.92 & -2.63 & 0.00 \\ 0.00 & -2.63 & 2.34 & -1.18 \\ 0.00 & 0.00 & -1.18 & 0.32 \end{pmatrix}.$$

See also the examples for F08FFF (DORGTR), F08GFF (DOPGTR) or F08HEF (DSBTRD), which illustrate the use of this routine to compute the eigenvalues and eigenvectors of a full or band symmetric matrix.

9.1 Program Text

```
*      F08JEF Example Program Text
*      Mark 16 Release. NAG Copyright 1992.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          NMAX, LDZ
      PARAMETER        (NMAX=8,LDZ=NMAX)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, INFO, N
*      .. Local Arrays ..
      DOUBLE PRECISION D(NMAX), E(NMAX-1), WORK(2*NMAX-2), Z(LDZ,NMAX)
*      .. External Subroutines ..
      EXTERNAL         DSTEQR, X04CAF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F08JEF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN
*
*          Read T from data file
*
*          READ (NIN,*) (D(I),I=1,N)
*          READ (NIN,*) (E(I),I=1,N-1)
*
*          Calculate all the eigenvalues and eigenvectors of T
*
*          CALL DSTEQR('I',N,D,E,Z,LDZ,WORK,INFO)
*
*          WRITE (NOUT,*)
*          IF (INFO.GT.0) THEN
*              WRITE (NOUT,*) 'Failure to converge.'
*          ELSE
*
*              Print eigenvalues and eigenvectors
*
*              WRITE (NOUT,*) 'Eigenvalues'
*              WRITE (NOUT,99999) (D(I),I=1,N)
*              WRITE (NOUT,*)
*              IFAIL = 0
*
*              CALL X04CAF('General',' ',N,N,Z,LDZ,'Eigenvectors',IFAIL)
*
*          END IF
*      END IF
*
*      99999 FORMAT (3X,(8F8.4))
      END
```

9.2 Program Data

F08JEF Example Program Data

```
4                               :Value of N
-6.99    7.92    2.34    0.32
-0.44   -2.63   -1.18       :End of matrix T
```

9.3 Program Results

F08JEF Example Program Results

Eigenvalues

```
-7.0037 -0.4059  2.0028  8.9968
```

Eigenvectors

	1	2	3	4
1	0.9995	-0.0109	-0.0167	-0.0255
2	0.0310	0.1627	0.3408	0.9254
3	0.0089	0.5170	0.7696	-0.3746
4	0.0014	0.8403	-0.5397	0.0509
