

NAG Library Routine Document

F08SAF (DSYGV)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08SAF (DSYGV) computes all the eigenvalues and, optionally, the eigenvectors of a real generalized symmetric-definite eigenproblem, of the form

$$Az = \lambda Bz, \quad ABz = \lambda z \quad \text{or} \quad BAz = \lambda z,$$

where A and B are symmetric and B is also positive-definite.

2 Specification

```

SUBROUTINE F08SAF( ITYPE, JOBZ, UPLO, N, A, LDA, B, LDB, W, WORK, LWORK,
1                  INFO )
    INTEGER          ITYPE, N, LDA, LDB, LWORK, INFO
    double precision A(LDA,*), B(LDB,*), W(*), WORK(max(1,LWORK))
    CHARACTER*1      JOBZ, UPLO

```

The routine may be called by its LAPACK name ***dsygv***.

3 Description

F08SAF (DSYGV) first performs a Cholesky factorization of the matrix B as $B = U^T U$, when $UPLO = 'U'$ or $B = LL^T$, when $UPLO = 'L'$. The generalized problem is then reduced to a standard symmetric eigenvalue problem

$$Cx = \lambda x,$$

which is solved for the eigenvalues and, optionally, the eigenvectors; the eigenvectors are then backtransformed to give the eigenvectors of the original problem.

For the problem $Az = \lambda Bz$, the eigenvectors are normalized so that the matrix of eigenvectors, z , satisfies

$$Z^T A Z = \Lambda \quad \text{and} \quad Z^T B Z = I,$$

where Λ is the diagonal matrix whose diagonal elements are the eigenvalues. For the problem $ABz = \lambda z$ we correspondingly have

$$Z^{-1} A Z^{-T} = \Lambda \quad \text{and} \quad Z^T B Z = I,$$

and for $BAz = \lambda z$ we have

$$Z^T A Z = \Lambda \quad \text{and} \quad Z^T B^{-1} Z = I.$$

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: ITYPE – INTEGER *Input*
On entry: specifies the problem type to be solved.
 ITYPE = 1
 $Az = \lambda Bz.$
 ITYPE = 2
 $ABz = \lambda z.$
 ITYPE = 3
 $BAz = \lambda z.$
- 2: JOBZ – CHARACTER*1 *Input*
On entry: if JOBZ = 'N', compute eigenvalues only.
 If JOBZ = 'V', compute eigenvalues and eigenvectors.
Constraint: JOBZ = 'N' or 'V'.
- 3: UPLO – CHARACTER*1 *Input*
On entry: if UPLO = 'U', the upper triangles of A and B are stored.
 If UPLO = 'L', the lower triangles of A and B are stored.
Constraint: UPLO = 'U' or 'L'.
- 4: N – INTEGER *Input*
On entry: n , the order of the matrices A and B .
Constraint: $N \geq 0$.
- 5: A(LDA,*) – **double precision** array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n symmetric matrix A .
 If UPLO = 'U', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.
 If UPLO = 'L', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: if JOBZ = 'V', then if INFO = 0, A contains the matrix Z of eigenvectors. The eigenvectors are normalized as follows:
 if ITYPE = 1 or 2, $Z^T B Z = I$;
 if ITYPE = 3, $Z^T B^{-1} Z = I$.
 If JOBZ = 'N', the upper triangle (if UPLO = 'U') or the lower triangle (if UPLO = 'L') of A , including the diagonal, is destroyed.
- 6: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F08SAF (DSYGV) is called.
Constraint: $LDA \geq \max(1, N)$.

- 7: B(LDB,*) – **double precision** array *Input/Output*
Note: the second dimension of the array B must be at least $\max(1, N)$.
On entry: the symmetric positive-definite matrix B :
 if UPLO = 'U', the leading n by n upper triangular part of B contains the upper triangular part of the matrix B ;
 if UPLO = 'L', the leading n by n lower triangular part of B contains the lower triangular part of the matrix B .
On exit: if INFO $\leq N$, the part of B containing the matrix is overwritten by the triangular factor U or L from the Cholesky factorization $B = U^T U$ or $B = L L^T$.
- 8: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F08SAF (DSYGV) is called.
Constraint: $LDB \geq \max(1, N)$.
- 9: W(*) – **double precision** array *Output*
Note: the dimension of the array W must be at least $\max(1, N)$.
On exit: if INFO = 0, the eigenvalues in ascending order.
- 10: WORK(max(1, LWORK)) – **double precision** array *Workspace*
On exit: if INFO = 0, WORK(1) contains the minimum value of LWORK required for optimal performance.
- 11: LWORK – INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F08SAF (DSYGV) is called.
If LWORK = -1, a workspace query is assumed; the routine only calculates the optimal size of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.
Suggested value: for optimal performance, $LWORK \geq (nb + 2) \times N$, where nb is the optimal **block size** for F08FEF (DSYTRD).
Constraint: $LWORK \geq \max(1, 3 \times N - 1)$.
- 12: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

F07FDF (DPOTRF) or F08FAF (DSYEV) returned an error code:

- $\leq N$ if $\text{INFO} = i$, F08FAF (DSYEV) failed to converge; i off-diagonal elements of an intermediate tridiagonal form did not converge to zero;
- $> N$ if $\text{INFO} = N + i$, for $1 \leq i \leq N$, then the leading minor of order i of B is not positive-definite. The factorization of B could not be completed and no eigenvalues or eigenvectors were computed.

7 Accuracy

If B is ill-conditioned with respect to inversion, then the error bounds for the computed eigenvalues and vectors may be large, although when the diagonal elements of B differ widely in magnitude the eigenvalues and eigenvectors may be less sensitive than the condition of B would suggest. See Section 4.10 of Anderson *et al.* (1999) for further details.

The example program below illustrates the computation of approximate error bounds.

8 Further Comments

The total number of floating-point operations is proportional to n^3 .

The complex analogue of this routine is F08SNF (ZHEGV).

9 Example

This example finds all the eigenvalues and eigenvectors of the generalized symmetric eigenproblem $Az = \lambda Bz$, where

$$A = \begin{pmatrix} 0.24 & 0.39 & 0.42 & -0.16 \\ 0.39 & -0.11 & 0.79 & 0.63 \\ 0.42 & 0.79 & -0.25 & 0.48 \\ -0.16 & 0.63 & 0.48 & -0.03 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.09 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.09 & 0.34 & 1.18 \end{pmatrix},$$

together with an estimate of the condition number of B , and approximate error bounds for the computed eigenvalues and eigenvectors.

The example program for F08SCF (DSYGVD) illustrates solving a generalized symmetric eigenproblem of the form $ABz = \lambda z$.

9.1 Program Text

```
*      F08SAF Example Program Text
*      Mark 21 Release.  NAG Copyright 2004.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          NB, NMAX
      PARAMETER        (NB=64,NMAX=10)
      INTEGER          LDA, LDB, LWORK
      PARAMETER        (LDA=NMAX,LDB=NMAX,LWORK=(NB+2)*NMAX)
*      .. Local Scalars ..
      DOUBLE PRECISION ANORM, BNORM, EPS, RCOND, RCONDB, T1, T2, T3
      INTEGER          I, IFAIL, INFO, J, LWKOPT, N
*      .. Local Arrays ..
      DOUBLE PRECISION A(LDA,NMAX), B(LDB,NMAX), EERBND(NMAX),
+      RCONDZ(NMAX), W(NMAX), WORK(LWORK), ZERBND(NMAX)
      INTEGER          IWORK(NMAX)
*      .. External Functions ..
      DOUBLE PRECISION F06RCF, X02AJF
      EXTERNAL          F06RCF, X02AJF
*      .. External Subroutines ..
      EXTERNAL          DDISNA, DSYGV, DTRCON, X04CAF
*      .. Intrinsic Functions ..
      INTRINSIC          ABS, INT
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F08SAF Example Program Results'
```

```

      WRITE (NOUT,*)
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN
*
*          Read the upper triangular parts of the matrices A and B
*
      READ (NIN,*) ((A(I,J),J=I,N),I=1,N)
      READ (NIN,*) ((B(I,J),J=I,N),I=1,N)
*
*          Compute the one-norms of the symmetric matrices A and B
*
      ANORM = F06RCF('One norm','Upper',N,A,LDA,WORK)
      BNORM = F06RCF('One norm','Upper',N,B,LDB,WORK)
*
*          Solve the generalized symmetric eigenvalue problem
*          A*x = lambda*B*x (ITYPE = 1)
*
      CALL DSYGV(1,'Vectors','Upper',N,A,LDA,B,LDB,W,WORK,LWORK,INFO)
      LWKOPT = INT(WORK(1))
*
      IF (INFO.EQ.0) THEN
*
*          Print solution
*
      WRITE (NOUT,*) 'Eigenvalues'
      WRITE (NOUT,99999) (W(J),J=1,N)
*
      WRITE (NOUT,*)
      IFAIL = 0
      CALL X04CAF('General',' ',N,N,A,LDA,'Eigenvectors',IFAIL)
*
*          Call DTRCON (F07TGF) to estimate the reciprocal condition
*          number of the Cholesky factor of B. Note that:
*          cond(B) = 1/RCOND**2
*
      CALL DTRCON('One norm','Upper','Non-unit',N,B,LDB,RCOND,
+          WORK,IWORK,INFO)
*
*          Print the reciprocal condition number of B
*
      RCONDB = RCOND**2
      WRITE (NOUT,*)
      WRITE (NOUT,*)
+      'Estimate of reciprocal condition number for B'
      WRITE (NOUT,99998) RCONDB
*
*          Get the machine precision, EPS, and if RCONDB is not less
*          than EPS**2, compute error estimates for the eigenvalues and
*          eigenvectors
*
      EPS = X02AJF()
      IF (RCOND.GE.EPS) THEN
*
*          Call DDISNA (F08FLF) to estimate reciprocal condition
*          numbers for the eigenvectors of (A - lambda*B)
*
      CALL DDISNA('Eigenvectors',N,N,W,RCONDZ,INFO)
*
*          Compute the error estimates for the eigenvalues and
*          eigenvectors
*
      T1 = EPS/RCONDB
      T2 = ANORM/BNORM
      T3 = T2/RCOND
      DO 20 I = 1, N
          EERBND(I) = T1*(T2+ABS(W(I)))
          ZERBND(I) = T1*(T3+ABS(W(I)))/RCONDZ(I)
20      CONTINUE
*

```

```

*          Print the approximate error bounds for the eigenvalues
*          and vectors
*
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Error estimates for the eigenvalues'
          WRITE (NOUT,99998) (EERBND(I),I=1,N)
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Error estimates for the eigenvectors'
          WRITE (NOUT,99998) (ZERBND(I),I=1,N)
        ELSE
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'B is very ill-conditioned, error ',
+            'estimates have not been computed'
        END IF
      ELSE IF (INFO.GT.N .AND. INFO.LE.2*N) THEN
        I = INFO - N
        WRITE (NOUT,99997) 'The leading minor of order ', I,
+          ' of B is not positive definite'
      ELSE
        WRITE (NOUT,99996) 'Failure in DSYGV. INFO =', INFO
      END IF
*
*          Print workspace information
*
      IF (LWORK.LT.LWKOPT) THEN
        WRITE (NOUT,*)
        WRITE (NOUT,99995) 'Optimum workspace required = ', LWKOPT,
+          'Workspace provided      = ', LWORK
      END IF
      ELSE
        WRITE (NOUT,*) 'NMAX too small'
      END IF
*
99999 FORMAT (3X,(6F11.4))
99998 FORMAT (4X,1P,6E11.1)
99997 FORMAT (1X,A,I4,A)
99996 FORMAT (1X,A,I4)
99995 FORMAT (1X,A,I5,/1X,A,I5)
      END

```

9.2 Program Data

F08SAF Example Program Data

```

4                               :Value of N

0.24   0.39   0.42  -0.16
      -0.11   0.79   0.63
           -0.25   0.48
              -0.03 :End of matrix A

4.16  -3.12   0.56  -0.10
      5.03  -0.83   1.09
           0.76   0.34
              1.18 :End of matrix B

```

9.3 Program Results

F08SAF Example Program Results

```

Eigenvalues
  -2.2254   -0.4548    0.1001    1.1270

Eigenvectors
      1      2      3      4
1   -0.0690  -0.3080   0.4469   0.5528
2   -0.5740  -0.5329   0.0371   0.6766
3   -1.5428   0.3496  -0.0505   0.9276
4    1.4004   0.6211  -0.4743  -0.2510

```

```
Estimate of reciprocal condition number for B
5.8E-03

Error estimates for the eigenvalues
4.7E-14    1.2E-14    5.6E-15    2.5E-14

Error estimates for the eigenvectors
5.2E-14    1.0E-13    9.2E-14    6.9E-14
```
