

NAG Library Routine Document

F08XAF (DGGES)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08XAF (DGGES) computes the generalized eigenvalues, the generalized real Schur form (S, T) and, optionally, the left and/or right generalized Schur vectors for a pair of n by n real nonsymmetric matrices (A, B) .

2 Specification

```

SUBROUTINE F08XAF(JOBVSL, JOBVSR, SORT, SELCTG, N, A, LDA, B, LDB, SDIM,
1              ALPHAR, ALPHAI, BETA, VSL, LDVSL, VSR, LDVSR, WORK,
2              LWORK, BWORK, INFO)

    INTEGER          N, LDA, LDB, SDIM, LDVSL, LDVSR, LWORK, INFO
    double precision A(LDA,*), B(LDB,*), ALPHAR(N), ALPHAI(N), BETA(N),
1              VSL(LDVSL,*), VSR(LDVSR,*), WORK(max(1,LWORK))
    LOGICAL          SELCTG, BWORK(*)
    CHARACTER*1      JOBVSL, JOBVSR, SORT
    EXTERNAL         SELCTG

```

The routine may be called by its LAPACK name ***dgges***.

3 Description

The generalized real Schur factorization of (A, B) is given by

$$A = QSZ^T, \quad B = QTZ^T,$$

where Q and Z are orthogonal, T is upper triangular and S is upper quasi-triangular with 1 by 1 and 2 by 2 diagonal blocks. The generalized eigenvalues, λ , of (A, B) are computed from the diagonals of S and T and satisfy

$$Az = \lambda Bz,$$

where z is the corresponding generalized eigenvector. λ is actually returned as the pair (α, β) such that

$$\lambda = \alpha/\beta$$

since β , or even both α and β can be zero. The columns of Q and Z are the left and right generalized Schur vectors of (A, B) .

Optionally, F08XAF (DGGES) can order the generalized eigenvalues on the diagonals of (S, T) so that selected eigenvalues are at the top left. The leading columns of Q and Z then form an orthonormal basis for the corresponding eigenspaces, the deflating subspaces.

F08XAF (DGGES) computes T to have non-negative diagonal elements, and the 2 by 2 blocks of S correspond to complex conjugate pairs of generalized eigenvalues. The generalized Schur factorization, before reordering, is computed by the QZ algorithm.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: JOBVSL – CHARACTER*1 *Input*
On entry: if JOBVSL = 'N', do not compute the left Schur vectors.
 If JOBVSL = 'V', compute the left Schur vectors.
Constraint: JOBVSL = 'N' or 'V'.
- 2: JOBVSR – CHARACTER*1 *Input*
On entry: if JOBVSR = 'N', do not compute the right Schur vectors.
 If JOBVSR = 'V', compute the right Schur vectors.
Constraint: JOBVSR = 'N' or 'V'.
- 3: SORT – CHARACTER*1 *Input*
On entry: specifies whether or not to order the eigenvalues on the diagonal of the generalized Schur form.
 SORT = 'N'
 Eigenvalues are not ordered.
 SORT = 'S'
 Eigenvalues are ordered (see SELCTG).
Constraint: SORT = 'N' or 'S'.
- 4: SELCTG – LOGICAL FUNCTION, supplied by the user. *External Procedure*
 If SORT = 'S', SELCTG is used to select generalized eigenvalues to the top left of the generalized Schur form.
 If SORT = 'N', SELCTG is not referenced and F08XAF (DGGES) may be called with the dummy function F08XAZ.

The specification of SELCTG is:

```
LOGICAL FUNCTION SELCTG(AR, AI, B)
  double precision      AR, AI, B
```

- | | | |
|----|------------------------------|--------------|
| 1: | AR – double precision | <i>Input</i> |
| 2: | AI – double precision | <i>Input</i> |
| 3: | B – double precision | <i>Input</i> |

On entry: an eigenvalue $(AR(j) + \sqrt{-1} \times AI(j))/B(j)$ is selected if
 $SELCTG(AR(j), AI(j), B(j)) = .TRUE.$.. If either one of a complex conjugate pair is
 selected, then both complex generalized eigenvalues are selected.

Note that in the ill-conditioned case, a selected complex generalized eigenvalue may no
 longer satisfy $SELCTG(AR(j), AI(j), B(j)) = .TRUE.$ after ordering. INFO = N + 2 in
 this case.

SELCTG must be declared as EXTERNAL in the (sub)program from which F08XAF (DGGES) is
 called. Parameters denoted as *Input* must **not** be changed by this procedure.

- 5: N – INTEGER *Input*
On entry: n , the order of the matrices A and B .
Constraint: $N \geq 0$.

- 6: A(LDA,*) – **double precision** array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the first of the pair of matrices, A.
On exit: A has been overwritten by its generalized Schur form S.
- 7: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F08XAF (DGGES) is called.
Constraint: $LDA \geq \max(1, N)$.
- 8: B(LDB,*) – **double precision** array *Input/Output*
Note: the second dimension of the array B must be at least $\max(1, N)$.
On entry: the second of the pair of matrices, B.
On exit: B has been overwritten by its generalized Schur form T.
- 9: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F08XAF (DGGES) is called.
Constraint: $LDB \geq \max(1, N)$.
- 10: SDIM – INTEGER *Output*
On exit: if SORT = 'N', SDIM = 0.
 If SORT = 'S', SDIM = number of eigenvalues (after sorting) for which SELCTG is .TRUE..
 (Complex conjugate pairs for which SELCTG is .TRUE. for either eigenvalue count as 2.)
- 11: ALPHAR(N) – **double precision** array *Output*
On exit: see the description of BETA.
- 12: ALPHAI(N) – **double precision** array *Output*
On exit: see the description of BETA.
- 13: BETA(N) – **double precision** array *Output*
On exit: $(\text{ALPHAR}(j) + \text{ALPHAI}(j) \times i) / \text{BETA}(j)$, for $j = 1, 2, \dots, N$, will be the generalized eigenvalues. $\text{ALPHAR}(j) + \text{ALPHAI}(j) \times i$, and $\text{BETA}(j)$, for $j = 1, 2, \dots, N$, are the diagonals of the complex Schur form (S, T) that would result if the 2 by 2 diagonal blocks of the real Schur form of (A, B) were further reduced to triangular form using 2 by 2 complex unitary transformations.
 If ALPHAI(j) is zero, then the jth eigenvalue is real; if positive, then the jth and (j + 1)st eigenvalues are a complex conjugate pair, with ALPHAI(j + 1) negative.
Note: the quotients $\text{ALPHAR}(j) / \text{BETA}(j)$ and $\text{ALPHAI}(j) / \text{BETA}(j)$ may easily overflow or underflow, and $\text{BETA}(j)$ may even be zero. Thus, you should avoid naively computing the ratio α / β . However, ALPHAR and ALPHAI will always be less than and usually comparable with $\|A\|_2$ in magnitude, and BETA will always be less than and usually comparable with $\|B\|_2$.
- 14: VSL(LDVSL,*) – **double precision** array *Output*
Note: the second dimension of the array VSL must be at least $\max(1, N)$ if JOBVSL = 'V', and at least 1 otherwise.
On exit: if JOBVSL = 'V', VSL will contain the left Schur vectors, Q.
 If JOBVSL = 'N', VSL is not referenced.

- 15: LDVSL – INTEGER *Input*
On entry: the first dimension of the array VSL as declared in the (sub)program from which F08XAF (DGGES) is called.
Constraints:
 if JOBVSL = 'V', $LDVSL \geq \max(1, N)$;
 otherwise $LDVSL \geq 1$.
- 16: VSR(LDVSR,*) – **double precision** array *Output*
Note: the second dimension of the array VSR must be at least $\max(1, N)$.
On exit: if JOBVSR = 'V', VSR will contain the right Schur vectors, Z .
 If JOBVSR = 'N', VSR is not referenced.
- 17: LDVSR – INTEGER *Input*
On entry: the first dimension of the array VSR as declared in the (sub)program from which F08XAF (DGGES) is called.
Constraints:
 if JOBVSR = 'V', $LDVSR \geq \max(1, N)$;
 otherwise $LDVSR \geq 1$.
- 18: WORK($\max(1, LWORK)$) – **double precision** array *Workspace*
On exit: if INFO = 0, WORK(1) contains the minimum value of LWORK required for optimal performance.
- 19: LWORK – INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F08XAF (DGGES) is called.
 If LWORK = -1, a workspace query is assumed; the routine only calculates the optimal size of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.
Suggested value: for optimal performance, LWORK must generally be larger than the minimum; add, say $nb \times N$, where nb is the optimal **block size**.
Constraints:
 if $N = 0$, $LWORK \geq 1$;
 otherwise $LWORK \geq \max(8 \times N, 6 \times N + 16)$.
- 20: BWORK(*) – LOGICAL array *Workspace*
Note: the dimension of the array BWORK must be at least 1 if SORT = 'N', and at least $\max(1, N)$ otherwise.
 If SORT = 'N', BWORK is not referenced.
- 21: IUSER(1) – INTEGER array *Input/Output*
- 22: RUSER(1) – **double precision** array *Input/Output*
- 23: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO = 1 to N

The QZ iteration failed. (A, B) are not in Schur form, but $\text{ALPHAR}(j)$, $\text{ALPHAI}(j)$, and $\text{BETA}(j)$ should be correct for $j = \text{INFO} + 1, \dots, N$.

INFO = N + 1

Unexpected error returned from F08XEF (DHGEQZ).

INFO = N + 2

After reordering, roundoff changed values of some complex eigenvalues so that leading eigenvalues in the generalized Schur form no longer satisfy $\text{SELCTG} = \text{.TRUE.}$. This could also be caused by underflow due to scaling.

INFO = N + 3

The eigenvalues could not be reordered because some eigenvalues were too close to separate (the problem is very ill-conditioned).

7 Accuracy

The computed generalized Schur factorization satisfies

$$A + E = QSZ^T, \quad B + F = QTZ^T,$$

where

$$\|(E, F)\|_F = O(\epsilon)\|(A, B)\|_F$$

and ϵ is the *machine precision*. See Section 4.11 of Anderson *et al.* (1999) for further details.

8 Further Comments

The total number of floating-point operations is proportional to n^3 .

The complex analogue of this routine is F08XNF (ZGGES).

9 Example

This example finds the generalized Schur factorization of the matrix pair (A, B) , where

$$A = \begin{pmatrix} 3.9 & 12.5 & -34.5 & -0.5 \\ 4.3 & 21.5 & -47.5 & 7.5 \\ 4.3 & 21.5 & -43.5 & 3.5 \\ 4.4 & 26.0 & -46.0 & 6.0 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 1.0 & 2.0 & -3.0 & 1.0 \\ 1.0 & 3.0 & -5.0 & 4.0 \\ 1.0 & 3.0 & -4.0 & 3.0 \\ 1.0 & 3.0 & -4.0 & 4.0 \end{pmatrix},$$

such that the real eigenvalues of (A, B) correspond to the top left diagonal elements of the generalized Schur form, (S, T) .

Note that the block size (NB) of 64 assumed in this example is not realistic for such a small problem, but should be suitable for large problems.

9.1 Program Text

```

*      F08XAF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          NB, NMAX
      PARAMETER        (NB=64,NMAX=10)
      INTEGER          LDA, LDB, LDVSL, LDVSR, LWORK
      PARAMETER        (LDA=NMAX,LDB=NMAX,LDVSL=NMAX,LDVSR=NMAX,
+      LWORK=8*NMAX+16+NMAX*NB)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, INFO, J, LWKOPT, N, SDIM
*      .. Local Arrays ..
      DOUBLE PRECISION A(LDA,NMAX), ALPHAI(NMAX), ALPHAR(NMAX),
+      B(LDB,NMAX), BETA(NMAX), VSL(LDVSL,NMAX),
+      VSR(LDVSR,NMAX), WORK(LWORK)
      LOGICAL          BWORK(NMAX)
*      .. External Functions ..
      LOGICAL          SELCTG
      EXTERNAL          SELCTG
*      .. External Subroutines ..
      EXTERNAL          DGGES, X04CAF
*      .. Intrinsic Functions ..
      INTRINSIC          INT
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F08XAF Example Program Results'
      WRITE (NOUT,*)
      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN

*
*          Read in the matrices A and B
*
      READ (NIN,*) ((A(I,J),J=1,N),I=1,N)
      READ (NIN,*) ((B(I,J),J=1,N),I=1,N)

*
*          Find the generalized Schur form
*
      CALL DGGES('Vectors (left)','Vectors (right)','Sort',SELCTG,N,
+      A,LDA,B,LDB,SDIM,ALPHAR,ALPHAI,BETA,VSL,LDVSL,VSR,
+      LDVSR,WORK,LWORK,BWORK,INFO)

*
      IF (INFO.GT.0 .AND. INFO.NE.(N+2)) THEN
        WRITE (NOUT,99999) 'Failure in DGGES. INFO =', INFO
      ELSE
        WRITE (NOUT,99999)
+      'Number of eigenvalues for which SELCTG is true = ', SDIM
        WRITE (NOUT,*)
        IF (INFO.EQ.(N+2)) THEN
          WRITE (NOUT,99998) '***Note that rounding errors mean ',
+      'that leading eigenvalues in the generalized',
+      'Schur form no longer satisfy SELCTG = .TRUE.'
          WRITE (NOUT,*)
        END IF

*
*          Print out the factors of the generalized Schur factorization
*
      IFAIL = 0
      CALL X04CAF('General',' ',N,N,A,LDA,
+      'Generalized Schur matrix S',IFAIL)

*
      WRITE (NOUT,*)
      CALL X04CAF('General',' ',N,N,B,LDB,
+      'Generalized Schur matrix T',IFAIL)

*
      WRITE (NOUT,*)
      CALL X04CAF('General',' ',N,N,VSL,LDVSL,
+      'Matrix of left generalized Schur vectors',

```

```

+          IFAIL)
*
      WRITE (NOUT,*)
      CALL X04CAF('General',' ',N,N,VSR,LDVSR,
+          'Matrix of right generalized Schur vectors',
+          IFAIL)
*
      LWKOPT = INT(WORK(1))
      IF (LWORK.LT.LWKOPT) THEN
        WRITE (NOUT,*)
        WRITE (NOUT,99997) 'Optimum workspace required = ',
+          LWKOPT, 'Workspace provided          = ', LWORK
      END IF
      END IF
    ELSE
      WRITE (NOUT,*)
      WRITE (NOUT,*) 'NMAX too small'
    END IF
*
99999 FORMAT (1X,A,I4)
99998 FORMAT (1X,2A,/1X,A)
99997 FORMAT (1X,A,I5,/1X,A,I5)
END
*
      LOGICAL FUNCTION SELCTG(AR,AI,B)
*
*      Logical function SELCTG for use with DGGES (F08XAF)
*
*      Returns the value .TRUE. if the imaginary part of the eigenvalue
*      (AR + AI*i)/B is zero, i.e. the eigenvalue is real
*
*      .. Scalar Arguments ..
      DOUBLE PRECISION AI, AR, B
*      .. Local Scalars ..
      LOGICAL          D
*      .. Executable Statements ..
      IF (AI.EQ.0.0D0) THEN
        D = .TRUE.
      ELSE
        D = .FALSE.
      END IF
*
      SELCTG = D
*
      RETURN
      END

```

9.2 Program Data

F08XAF Example Program Data

```

4          :Value of N
3.9  12.5 -34.5 -0.5
4.3  21.5 -47.5  7.5
4.3  21.5 -43.5  3.5
4.4  26.0 -46.0  6.0 :End of matrix A
1.0   2.0 -3.0  1.0
1.0   3.0 -5.0  4.0
1.0   3.0 -4.0  3.0
1.0   3.0 -4.0  4.0 :End of matrix B

```

9.3 Program Results

F08XAF Example Program Results

Number of eigenvalues for which SELCTG is true = 2

Generalized Schur matrix S

	1	2	3	4
1	3.8009	-69.4505	-50.3135	43.2884
2	0.0000	9.2033	0.2001	-5.9881

3	0.0000	0.0000	1.4279	4.4453
4	0.0000	0.0000	-0.9019	1.1962

Generalized Schur matrix T

	1	2	3	4
1	1.9005	-10.2285	-0.8658	5.2134
2	0.0000	2.3008	-0.7915	-0.4262
3	0.0000	0.0000	0.8101	0.0000
4	0.0000	0.0000	0.0000	0.2823

Matrix of left generalized Schur vectors

	1	2	3	4
1	0.4642	0.7886	-0.2915	-0.2786
2	0.5002	-0.5986	-0.5638	-0.2713
3	0.5002	0.0154	0.0107	0.8657
4	0.5331	-0.1395	0.7727	-0.3151

Matrix of right generalized Schur vectors

	1	2	3	4
1	0.9961	-0.0014	-0.0887	0.0026
2	0.0057	-0.0404	0.0938	0.9948
3	0.0626	0.7194	0.6908	-0.0363
4	0.0626	-0.6934	0.7114	-0.0956
