

NAG Library Routine Document

F12ACF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

Note: *this routine uses **optional parameters** to define choices in the problem specification. If you wish to use default settings for all of the optional parameters, then the option setting routine F12ADF need not be called. If, however, you wish to reset some or all of the settings please refer to Section 10 in F12ADF for a detailed description of the specification of the optional parameters.*

1 Purpose

F12ACF is a post-processing routine in a suite of routines consisting of F12AAF, F12ABF, F12ACF, F12ADF and F12AEF, that must be called following a final exit from F12ABF.

2 Specification

```

SUBROUTINE F12ACF(NCONV, DR, DI, Z, LDZ, SIGMAR, SIGMAI, RESID, V, LDV,
1          COMM, ICOMM, IFAIL)
    INTEGER          NCONV, LDZ, LDV, ICOMM(*), IFAIL
    double precision DR(*), DI(*), Z(LDZ,*), SIGMAR, SIGMAI, RESID(*),
1          V(LDV,*), COMM(*)

```

3 Description

The suite of routines is designed to calculate some of the eigenvalues, λ , (and optionally the corresponding eigenvectors, x) of a standard eigenvalue problem $Ax = \lambda x$, or of a generalized eigenvalue problem $Ax = \lambda Bx$ of order n , where n is large and the coefficient matrices A and B are sparse, real and nonsymmetric. The suite can also be used to find selected eigenvalues/eigenvectors of smaller scale dense, real and nonsymmetric problems.

Following a call to F12ABF, F12ACF returns the converged approximations to eigenvalues and (optionally) the corresponding approximate eigenvectors and/or an orthonormal basis for the associated approximate invariant subspace. The eigenvalues (and eigenvectors) are selected from those of a standard or generalized eigenvalue problem defined by real nonsymmetric matrices. There is negligible additional cost to obtain eigenvectors; an orthonormal basis is always computed, but there is an additional storage cost if both are requested.

F12ACF is based on the routine **dneupd** from the ARPACK package, which uses the Implicitly Restarted Arnoldi iteration method. The method is described in Lehoucq and Sorensen (1996) and Lehoucq (2001) while its use within the ARPACK software is described in great detail in Lehoucq *et al.* (1998). An evaluation of software for computing eigenvalues of sparse nonsymmetric matrices is provided in Lehoucq and Scott (1996). This suite of routines offers the same functionality as the ARPACK software for real nonsymmetric problems, but the interface design is quite different in order to make the option setting clearer and to simplify some of the interfaces.

F12ACF, is a post-processing routine that must be called following a successful final exit from F12ABF. F12ACF uses data returned from F12ABF and options, set either by default or explicitly by calling F12ADF, to return the converged approximations to selected eigenvalues and (optionally):

- the corresponding approximate eigenvectors;
- an orthonormal basis for the associated approximate invariant subspace;
- both.

4 References

Lehoucq R B (2001) Implicitly Restarted Arnoldi Methods and Subspace Iteration *SIAM Journal on Matrix Analysis and Applications* **23** 551–562

Lehoucq R B and Scott J A (1996) An evaluation of software for computing eigenvalues of sparse nonsymmetric matrices *Preprint MCS-P547-1195* Argonne National Laboratory

Lehoucq R B and Sorensen D C (1996) Deflation Techniques for an Implicitly Restarted Arnoldi Iteration *SIAM Journal on Matrix Analysis and Applications* **17** 789–821

Lehoucq R B, Sorensen D C and Yang C (1998) *ARPACK Users' Guide: Solution of Large-Scale Eigenvalue Problems with Implicitly Restarted Arnoldi Methods* SIAM, Philadelphia

5 Parameters

- 1: NCONV – INTEGER *Output*
On exit: the number of converged eigenvalues as found by F12ABF.
- 2: DR(*) – *double precision* array *Output*
Note: the dimension of the array DR must be at least NEV (see F12AAF).
On exit: the first NCONV locations of the array DR contain the real parts of the converged approximate eigenvalues.
- 3: DI(*) – *double precision* array *Output*
Note: the dimension of the array DI must be at least NEV (see F12AAF).
On exit: the first NCONV locations of the array DI contain the imaginary parts of the converged approximate eigenvalues.
- 4: Z(LDZ,*) – *double precision* array *Output*
Note: the second dimension of the array Z must be at least NEV + 1 if the default option Vectors = Ritz has been selected and at least 1 if the option Vectors = None or Schur has been selected (see F12AAF).
On exit: if the default option Vectors = Ritz has been selected then Z contains the final set of eigenvectors corresponding to the eigenvalues held in DR and DI. The complex eigenvector associated with the eigenvalue with positive imaginary part is stored in two consecutive columns. The first column holds the real part of the eigenvector and the second column holds the imaginary part. The eigenvector associated with the eigenvalue with negative imaginary part is simply the complex conjugate of the eigenvector associated with the positive imaginary part.
- 5: LDZ – INTEGER *Input*
On entry: the first dimension of the array Z as declared in the (sub)program from which F12ACF is called.
Constraints:
 if the default option Vectors = Ritz has been selected, $LDZ \geq N$;
 if the option Vectors = None or Schur has been selected, $LDZ \geq 1$.
- 6: SIGMAR – *double precision* *Input*
On entry: if one of the Shifted Inverse Real modes have been selected then SIGMAR contains the real part of the shift used; otherwise SIGMAR is not referenced.
- 7: SIGMAI – *double precision* *Input*
On entry: if one of the Shifted Inverse Real modes have been selected then SIGMAI contains the imaginary part of the shift used; otherwise SIGMAI is not referenced.

- 8: RESID(*) – **double precision** array *Input*
Note: the dimension of the array RESID must be at least N (see F12AAF).
On entry: must not be modified following a call to F12ABF since it contains data required by F12ACF.
- 9: V(LDV,*) – **double precision** array *Input/Output*
Note: the second dimension of the array V must be at least $\max(1, \text{NCV})$ (see F12AAF).
On entry: the NCV columns of V contain the Arnoldi basis vectors for OP as constructed by F12ABF.
On exit: if the option Vectors = Schur has been set, or the option Vectors = Ritz has been set and a separate array Z has been passed (i.e., Z does not equal V), then the first NCONV columns of V will contain approximate Schur vectors that span the desired invariant subspace.
- 10: LDV – INTEGER *Input*
On entry: the first dimension of the array V as declared in the (sub)program from which F12ACF is called.
Constraint: $\text{LDV} \geq \text{N}$.
- 11: COMM(*) – **double precision** array *Communication Array*
Note: the dimension of the array COMM must be at least $\max(1, \text{LCOMM})$ (see F12AAF).
On initial entry: must remain unchanged from the prior call to F12ABF.
On exit: contains data on the current state of the solution.
- 12: ICOMM(*) – INTEGER array *Communication Array*
Note: the dimension of the array ICOMM must be at least $\max(1, \text{LICOMM})$ (see F12AAF).
On initial entry: must remain unchanged from the prior call to F12ABF.
On exit: contains data on the current state of the solution.
- 13: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.
On exit: $\text{IFAIL} = 0$ unless the routine detects an error (see Section 6).
For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry $\text{IFAIL} = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

$\text{IFAIL} = 1$

On entry, $\text{LDZ} < \max(1, \text{N})$ or $\text{LDZ} < 1$ when no vectors are required.

$\text{IFAIL} = 2$

On entry, the option Vectors = Select was selected, but this is not yet implemented.

IFAIL = 3

The number of eigenvalues found to sufficient accuracy prior to calling F12ACF, as communicated through the parameter ICOMM, is zero.

IFAIL = 4

The number of converged eigenvalues as calculated by F12ABF differ from the value passed to it through the parameter ICOMM.

IFAIL = 5

Unexpected error during calculation of a real Schur form: there was a failure to compute all the converged eigenvalues. Please contact NAG.

IFAIL = 6

Unexpected error: the computed Schur form could not be reordered by an internal call. Please contact NAG.

IFAIL = 7

Unexpected error in internal call while calculating eigenvectors. Please contact NAG.

IFAIL = 8

Either the solver routine F12ABF has not been called prior to the call of this routine or a communication array has become corrupted.

IFAIL = 9

The routine was unable to dynamically allocate sufficient internal workspace. Please contact NAG.

IFAIL = 10

An unexpected error has occurred. Please contact NAG.

7 Accuracy

The relative accuracy of a Ritz value, λ , is considered acceptable if its Ritz estimate $\leq \text{Tolerance} \times |\lambda|$. The default Tolerance used is the *machine precision* given by X02AJF.

8 Further Comments

None.

9 Example

This example solves $Ax = \lambda Bx$ in regular-invert mode, where A and B are obtained from the standard central difference discretization of the one-dimensional convection-diffusion operator $\frac{d^2 u}{dx^2} + \rho \frac{du}{dx}$ on $[0, 1]$, with zero Dirichlet boundary conditions.

9.1 Program Text

```
*      F12ACF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
      INTEGER          LICOMM, NIN, NOUT
      PARAMETER        (LICOMM=140, NIN=5, NOUT=6)
      INTEGER          MAXN, MAXNCV, LDV
      PARAMETER        (MAXN=256, MAXNCV=30, LDV=MAXN)
      INTEGER          LCOMM
      PARAMETER        (LCOMM=3*MAXN+3*MAXNCV*MAXNCV+6*MAXNCV+60)
```

```

      INTEGER          IMON
      PARAMETER        (IMON=0)
      DOUBLE PRECISION ONE
      PARAMETER        (ONE=1.0D+0)
*    .. Local Scalars ..
      DOUBLE PRECISION H, RHO, SIGMAI, SIGMAR
      INTEGER          IFAIL, IFAIL1, INFO, IREVCM, J, N, NCONV, NCV,
+    NEV, NITER, NSHIFT, NX
*    .. Local Arrays ..
      DOUBLE PRECISION COMM(LCOMM), D(MAXNCV,3), MD(MAXN), ME(MAXN-1),
+    MX(MAXN), RESID(MAXN), V(LDV,MAXNCV), X(MAXN)
      INTEGER          ICOMM(LICOMM)
*    .. External Functions ..
      DOUBLE PRECISION DNRM2
      EXTERNAL         DNRM2
*    .. External Subroutines ..
      EXTERNAL         AV, DPTTRF, DPTTRS, F12AAF, F12ABF, F12ACF,
+    F12ADF, F12AEF, MV
*    .. Intrinsic Functions ..
      INTRINSIC        DBLE
*    .. Executable Statements ..
      WRITE (NOUT,*) 'F12ACF Example Program Results'
      WRITE (NOUT,*)
*    Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) NX, NEV, NCV, RHO
      N = NX*NX
      IF (N.LT.1 .OR. N.GT.MAXN) THEN
        WRITE (NOUT,99999) 'N is out of range: N = ', N
      ELSE IF (NCV.GT.MAXNCV) THEN
        WRITE (NOUT,99999) 'NCV is out of range: NCV = ', NCV
      ELSE
        IFAIL = 1
        CALL F12AAF(N,NEV,NCV,ICOMM,LICOMM,COMM,LCOMM,IFAIL)
*
*      IF (IFAIL.EQ.0) THEN
*        Set the mode.
*        IFAIL = 0
*        CALL F12ADF('REGULAR INVERSE',ICOMM,COMM,IFAIL)
*        Set problem type.
*        CALL F12ADF('GENERALIZED',ICOMM,COMM,IFAIL)
*        Use pointers to Workspace in calculating matrix vector
*        products rather than interfacing through the array X
*        CALL F12ADF('POINTERS=YES',ICOMM,COMM,IFAIL)
*
*        Construct M, and factorize using DPTTRF/F07JDF.
*        H = ONE/DBLE(N+1)
*        DO 20 J = 1, N - 1
*          MD(J) = 4.0D+0*H
*          ME(J) = H
20      CONTINUE
*        MD(N) = 4.0D+0*H
*
*        CALL DPTTRF(N,MD,ME,INFO)
*
*        IREVCM = 0
*        IFAIL = -1
40      CONTINUE
      CALL F12ABF(IREVCM,RESID,V,LDV,X,MX,NSHIFT,COMM,ICOMM,IFAIL)
      IF (IREVCM.NE.5) THEN
        IF (IREVCM.EQ.-1 .OR. IREVCM.EQ.1) THEN
*          Perform y <--- OP*x = inv[M]*A*x using DPTTRS/F07JEF.
          CALL AV(NX,RHO,COMM(ICOMM(1)),COMM(ICOMM(2)))
          CALL DPTTRS(N,1,MD,ME,COMM(ICOMM(2)),N,INFO)
        ELSE IF (IREVCM.EQ.2) THEN
*          Perform y <--- M*x.
          CALL MV(NX,COMM(ICOMM(1)),COMM(ICOMM(2)))
        ELSE IF (IREVCM.EQ.4 .AND. IMON.NE.0) THEN
*          Output monitoring information if required.
          CALL F12AEF(NITER,NCONV,D,D(1,2),D(1,3),ICOMM,COMM)
          WRITE (6,99998) NITER, NCONV, DNRM2(NEV,D(1,3),1)

```

```

        END IF
        GO TO 40
    END IF
    IF (IFAIL.EQ.0) THEN
*       Post-Process using F12ACF to compute eigenvalues/vectors.
        IFAIL1 = 0
        CALL F12ACF(NCONV,D,D(1,2),V,LDV,SIGMAR,SIGMAI,RESID,V,
+           LDV,COMM,ICOMM,IFAIL1)
*       Print computed eigenvalues.
        WRITE (NOUT,99996) NCONV
        DO 60 J = 1, NCONV
            WRITE (NOUT,99995) J, D(J,1), D(J,2)
60        CONTINUE
    END IF
    ELSE
        WRITE (NOUT,99997) IFAIL
    END IF
END IF
*
99999 FORMAT (1X,A,I5)
99998 FORMAT (1X,'Iteration',1X,I3,',', No. converged =',1X,I3,',', norm o',
+           'f estimates =',E16.8)
99997 FORMAT (1X,' ** F12AAF returned with IFAIL = ',I5)
99996 FORMAT (1X,' The ',I4,' generalized Ritz values of largest ',
+           'magnitude are:',/)
99995 FORMAT (1X,I8,5X,'( ',F12.4,', ',F12.4,', )')
END
*
SUBROUTINE AV(NX,RHO,V,W)
*   .. Parameters ..
DOUBLE PRECISION ONE, TWO
PARAMETER      (ONE=1.0D+0,TWO=2.0D+0)
*   .. Scalar Arguments ..
DOUBLE PRECISION RHO
INTEGER        NX
*   .. Array Arguments ..
DOUBLE PRECISION V(NX*NX), W(NX*NX)
*   .. Local Scalars ..
DOUBLE PRECISION DD, DL, DU, H, S
INTEGER        J, N
*   .. Intrinsic Functions ..
INTRINSIC      DBLE
*   .. Executable Statements ..
N = NX*NX
H = ONE/DBLE(N+1)
S = RHO/TWO
DD = TWO/H
DL = -ONE/H - S
DU = -ONE/H + S
W(1) = DD*V(1) + DU*V(2)
DO 20 J = 2, N - 1
    W(J) = DL*V(J-1) + DD*V(J) + DU*V(J+1)
20 CONTINUE
W(N) = DL*V(N-1) + DD*V(N)
RETURN
END
*
SUBROUTINE MV(NX,V,W)
*   .. Parameters ..
DOUBLE PRECISION ONE, FOUR
PARAMETER      (ONE=1.0D+0,FOUR=4.0D+0)
*   .. Scalar Arguments ..
INTEGER        NX
*   .. Array Arguments ..
DOUBLE PRECISION V(NX*NX), W(NX*NX)
*   .. Local Scalars ..
DOUBLE PRECISION H
INTEGER        J, N
*   .. External Subroutines ..
EXTERNAL       DSCAL
*   .. Intrinsic Functions ..

```

```

      INTRINSIC      DBLE
*      .. Executable Statements ..
      N = NX*NX
      W(1) = FOUR*V(1) + ONE*V(2)
      DO 20 J = 2, N - 1
        W(J) = ONE*V(J-1) + FOUR*V(J) + ONE*V(J+1)
20    CONTINUE
      W(N) = ONE*V(N-1) + FOUR*V(N)
      H = ONE/DBLE(N+1)
      CALL DSCAL(N,H,W,1)
      RETURN
      END

```

9.2 Program Data

F12ACF Example Program Data
 10 4 20 10.0 : Values for NX NEV NCV RHO

9.3 Program Results

F12ACF Example Program Results

The 4 generalized Ritz values of largest magnitude are:

1	(	20383.0384	,	0.0000	)
2	(	20338.7563	,	0.0000	)
3	(	20265.2844	,	0.0000	)
4	(	20163.1142	,	0.0000	)
