

NAG Library Routine Document

G05LDF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

G05LDF generates a vector of pseudorandom numbers taken from an F (or Fisher's variance ratio) distribution with μ and ν degrees of freedom.

2 Specification

```
SUBROUTINE G05LDF(DF1, DF2, N, X, IGEN, ISEED, IFAIL)
INTEGER          DF1, DF2, N, IGEN, ISEED(4), IFAIL
double precision X(N)
```

3 Description

The distribution has PDF (probability density function)

$$f(x) = \frac{\left(\frac{\mu+\nu-2}{2}\right)! x^{\frac{1}{2}\mu-1}}{\left(\frac{1}{2}\mu-1\right)!\left(\frac{1}{2}\nu-1\right)!\left(1+\frac{\mu}{\nu}x\right)^{\frac{1}{2}(\mu+\nu)}} \times \left(\frac{\mu}{\nu}\right)^{\frac{1}{2}\mu} \quad \text{if } x > 0,$$

$$f(x) = 0 \quad \text{otherwise.}$$

G05LDF calculates the values

$$\frac{\nu y_i}{\mu z_i}, \quad i = 1, \dots, n,$$

where y_i and z_i are generated by G05LFF from gamma distributions with parameters $(\frac{1}{2}\mu, 2)$ and $(\frac{1}{2}\nu, 2)$ respectively (i.e., from χ^2 -distributions with μ and ν degrees of freedom).

One of the initialization routines G05KBF (for a repeatable sequence if computed sequentially) or G05KCF (for a non-repeatable sequence) must be called prior to the first call to G05LDF.

4 References

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

5 Parameters

- | | | |
|----|--|--------------|
| 1: | DF1 – INTEGER | <i>Input</i> |
| | <i>On entry:</i> μ , the number of degrees of freedom of the distribution. | |
| | <i>Constraint:</i> $DF1 \geq 1$. | |
| 2: | DF2 – INTEGER | <i>Input</i> |
| | <i>On entry:</i> ν , the number of degrees of freedom of the distribution. | |
| | <i>Constraint:</i> $DF2 \geq 1$. | |
| 3: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the number of pseudorandom numbers to be generated. | |
| | <i>Constraint:</i> $N \geq 0$. | |

- 4: $X(N)$ – *double precision* array *Output*
On exit: the n pseudorandom numbers from the specified F -distribution.
- 5: IGEN – INTEGER *Input*
On entry: must contain the identification number for the generator to be used to return a pseudorandom number and should remain unchanged following initialization by a prior call to G05KBF or G05KCF.
- 6: ISEED(4) – INTEGER array *Communication Array*
On entry: contains values which define the current state of the selected generator.
On exit: contains updated values defining the new state of the selected generator.
- 7: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $DF1 < 1$.

IFAIL = 2

On entry, $DF2 < 1$.

IFAIL = 3

On entry, $N < 0$.

7 Accuracy

Not applicable.

8 Further Comments

The time taken by G05LDF increases with μ and ν .

9 Example

This example prints five pseudorandom numbers from an F -distribution with two and three degrees of freedom, generated by a single call to G05LDF, after initialization by G05KBF.

9.1 Program Text

```

*      G05LDF Example Program Text
*      Mark 20 Release. NAG Copyright 2001.
*      .. Parameters ..
      INTEGER          NOUT, N
      PARAMETER        (NOUT=6,N=5)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, IGEN
*      .. Local Arrays ..
      DOUBLE PRECISION X(N)
      INTEGER          ISEED(4)
*      .. External Subroutines ..
      EXTERNAL         G05KBF, G05LDF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'G05LDF Example Program Results'
      WRITE (NOUT,*)
*      Initialize the seed to a repeatable sequence
      ISEED(1) = 1762543
      ISEED(2) = 9324783
      ISEED(3) = 42344
      ISEED(4) = 742355
*      IGEN identifies the stream.
      IGEN = 1
      CALL G05KBF(IGEN,ISEED)
*
      IFAIL = 1
      CALL G05LDF(2,3,N,X,IGEN,ISEED,IFAIL)
*
      IF (IFAIL.EQ.0) THEN
*
          WRITE (NOUT,99999) (X(I),I=1,N)
*
      ELSE
          WRITE (NOUT,99998) IFAIL
      END IF
*
99999 FORMAT (1X,F10.4)
99998 FORMAT (1X,' ** G05LDF returned with IFAIL = ',I5)
      END

```

9.2 Program Data

None.

9.3 Program Results

G05LDF Example Program Results

```

14.2359
0.8889
0.4055
2.3299
0.0689

```
