

NAG Library Routine Document

M01ECF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

M01ECF rearranges a vector of character data into the order specified by a vector of ranks.

2 Specification

```
SUBROUTINE M01ECF(CH, M1, M2, IRANK, IFAIL)
INTEGER          M1, M2, IRANK(M2), IFAIL
CHARACTER*(*)    CH(M2)
```

3 Description

M01ECF is designed to be used typically in conjunction with the M01D ranking routines. After one of the M01D routines has been called to determine a vector of ranks, M01ECF can be called to rearrange a vector of character data into the rank order. If the vector of ranks has been generated in some other way, then M01ZBF should be called to check its validity before M01ECF is called.

4 References

None.

5 Parameters

- 1: CH(M2) – CHARACTER*(*) array *Input/Output*
On entry: elements M1 to M2 of CH must contain character data to be rearranged.
Constraint: the length of each element of CH must not exceed 255.
On exit: these values are rearranged into rank order. For example, if $IRANK(i) = M1$, then the initial value of $CH(i)$ is moved to $CH(M1)$.
- 2: M1 – INTEGER *Input*
- 3: M2 – INTEGER *Input*
On entry: the range of the ranks supplied in IRANK and the elements of CH to be rearranged.
Constraint: $0 < M1 \leq M2$.
- 4: IRANK(M2) – INTEGER array *Input/Output*
On entry: elements M1 to M2 of IRANK must contain a permutation of the integers M1 to M2, which are interpreted as a vector of ranks.
On exit: used as internal workspace prior to being restored and hence is unchanged.
- 5: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0 . **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry $IFAIL = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

$IFAIL = 1$

On entry, $M2 < 1$,
or $M1 < 1$,
or $M1 > M2$.

$IFAIL = 2$

On entry, the length of each element of CH exceeds 255.

$IFAIL = 3$

Elements $M1$ to $M2$ of IRANK contain a value outside the range $M1$ to $M2$.

$IFAIL = 4$

Elements $M1$ to $M2$ of IRANK contain a repeated value.

If $IFAIL = 3$ or 4 , elements $M1$ to $M2$ of IRANK do not contain a permutation of the integers $M1$ to $M2$. On exit, the contents of CH may be corrupted. To check the validity of IRANK without the risk of corrupting CH, use M01ZBF.

7 Accuracy

Not applicable.

8 Further Comments

The average time taken by the routine is approximately proportional to n , where $n = M2 - M1 + 1$.

9 Example

This example reads a file of 12-character records, each of which contains in characters 1 to 6 a name of a NAG routine, and in characters 7 to 12 an integer frequency. The program first calls M01DBF to rank the integers in descending order, and then calls M01ECF to rearrange the names into the order specified by the ranks.

9.1 Program Text

```
*      M01ECF Example Program Text
*      Mark 14 Revised. NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          MMAX
      PARAMETER        (MMAX=100)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, M
*      .. Local Arrays ..
      INTEGER          IFREQ(MMAX), IRANK(MMAX)
```

```

      CHARACTER*6      CH(MMAX)
*      .. External Subroutines ..
      EXTERNAL         M01DBF, M01ECF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'M01ECF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
      DO 20 M = 1, MMAX
         READ (NIN,99999,END=40) CH(M), IFREQ(M)
20    CONTINUE
40    M = M - 1
      IFAIL = 0
*
      CALL M01DBF(IFREQ,1,M,'Descending',IRANK,IFAIL)
      CALL M01ECF(CH,1,M,IRANK,IFAIL)
*
      WRITE (NOUT,*)
      WRITE (NOUT,*) 'Names in order of frequency'
      WRITE (NOUT,*)
      WRITE (NOUT,99998) (CH(I),I=1,M)
*
99999 FORMAT (A6,I6)
99998 FORMAT (1X,A)
      END

```

9.2 Program Data

M01ECF Example Program Data

A02AAF	289
A02ABF	523
A02ACF	531
C02ADF	169
C02AEF	599
C05ADF	1351
C05AGF	240
C05AJF	136
C05AVF	211
C05AXF	183
C05AZF	2181

9.3 Program Results

M01ECF Example Program Results

Names in order of frequency

C05AZF
 C05ADF
 C02AEF
 A02ACF
 A02ABF
 A02AAF
 C05AGF
 C05AVF
 C05AXF
 C02ADF
 C05AJF
